



004991  
ZW7-125

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Characteristics

Dimensions


## DELIVERY PROGRAM

Product range  
ZW7 current transformer-operated overload relays


Description  
Test/off button  
Reset pushbutton manual/auto  
Trip-free release  
Protection with heavy starting duty

Mounting type  
Separate mounting

### Setting range

Overload releases  [I<sub>n</sub>]  
85 - 125 A

Contact sequence



## Auxiliary contacts

NO = Normally open  
1 NO

NC = Normally closed  
1 NC

### Notes

The main current parameters are defined by the main current wiring which is used.

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +50 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Temperature compensation  
Continuous

Mounting position  
As required

Weight  
0.8 kg

Mechanical shock resistance

10  
Sinusoidal  
Shock duration 10 ms g

Degree of Protection  
IP00

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

### Main conducting paths

Rated impulse withstand voltage [ $U_{imp}$ ]  
8000 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
1000 V

Rated operational voltage [ $U_e$ ]  
1000 V AC

Safe isolation to EN 61140  
Between auxiliary contacts and main contacts  
440 V AC

Safe isolation to EN 61140  
Between main circuits  
440 V AC

Short-circuit protection Maximum fuse  
With overload relay in conjunction with a  
transformer as required for the contactor

Current heat loss (3 conductors)  
Lower value of the setting range  
3 W

Current heat loss (3 conductors)  
Maximum setting

10 W

Push-through opening [□]  
27 mm

### Auxiliary and control circuits

Rated impulse withstand voltage [ $U_{imp}$ ]  
4000 V

Overvoltage category/pollution degree  
III/3

Terminal capacities  
Solid  
1 x (0.75 - 4)  
2 x (0.75 - 4) mm<sup>2</sup>

Terminal capacities  
Flexible with ferrule  
1 x (0.75 - 2.5)  
2 x (0.75 - 2.5) mm<sup>2</sup>

Terminal capacities  
Solid or stranded  
2 x (18 - 14) AWG

Terminal screw  
M3.5

Tightening torque  
1.2 Nm

Stripping length  
8 mm

Tools  
Pozidriv screwdriver  
2 Size

Tools  
Standard screwdriver  
1 x 6 mm

Rated insulation voltage [ $U_i$ ]

500 V AC

Rated operational voltage [ $U_e$ ]  
500 V AC

Safe isolation to EN61140  
between the auxiliary contacts  
240 V AC

Conventional thermal current [ $I_{th}$ ]  
6 A

Rated operational current [ $I_e$ ]  
AC-15  
Make contact  
120 V [ $I_e$ ]  
1.5 A

Rated operational current [ $I_e$ ]  
AC-15  
Make contact  
220 V 230 V 240 V [ $I_e$ ]  
1.5 A

Rated operational current [ $I_e$ ]  
AC-15  
Make contact  
380 V 400 V 415 V [ $I_e$ ]  
0.5 A

Rated operational current [ $I_e$ ]  
AC-15  
Make contact  
500 V [ $I_e$ ]  
0.5 A

Rated operational current [ $I_e$ ]  
AC-15  
Break contact  
120 V [ $I_e$ ]  
1.5 A

Rated operational current [ $I_e$ ]  
AC-15  
Break contact  
220 V 230 V 240 V [ $I_e$ ]  
1.5 A

Rated operational current [ $I_e$ ]  
AC-15

Break contact  
380 V 400 V 415 V [ $I_e$ ]  
0.9 A

Rated operational current [ $I_e$ ]  
AC-15  
Break contact  
500 V [ $I_e$ ]  
0.8 A

Rated operational current [ $I_e$ ]  
DC L/R  $\square$  15 ms  
Switch-on and switch-off conditions based on  
DC-13, time constant as specified.

Rated operational current [ $I_e$ ]  
DC L/R  $\square$  15 ms  
24 V [ $I_e$ ]  
0.9 A

Rated operational current [ $I_e$ ]  
DC L/R  $\square$  15 ms  
60 V [ $I_e$ ]  
0.75 A

Rated operational current [ $I_e$ ]  
DC L/R  $\square$  15 ms  
110 V [ $I_e$ ]  
0.4 A

Rated operational current [ $I_e$ ]  
DC L/R  $\square$  15 ms  
220 V [ $I_e$ ]  
0.2 A

Short-circuit rating without welding  
max. fuse  
6 A gG/gL

## Notes

Ambient temperature: Operating range to IEC/EN  
60947, PTB: -5°C to +50°C

Terminal capacities Main circuits solid and flexible  
with ferrule: When connecting 2 conductors, only  
the following combinations are admissible:

Rated operational current: Making and breaking  
currents to DC-13, time constant as stated

Short-circuit rating: See transparent overlay  
"Fuses" for time/current characteristics (Please

enquire)

### Rating data for approved types

Auxiliary contacts  
Flot Duty  
AC operated  
B300 at opposite polarity  
B600 at same polarity

Auxiliary contacts  
Flot Duty  
DC operated  
R300

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
125 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
2.1 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
6.3 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+50 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.



10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

# TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss10.0.1-27-37-15-01 [AKF075014])

Adjustable current range  
85 - 125 A

Max. rated operation voltage  $U_e$   
690 V

Mounting method  
Separate positioning

Type of electrical connection of main circuit  
Screw connection

Number of auxiliary contacts as normally closed  
contact  
1

Number of auxiliary contacts as normally open  
contact  
1

Number of auxiliary contacts as change-over  
contact  
0

Release class  
Other

Reset function input  
No

Reset function automatic  
Yes

Reset function push-button  
Yes

# APPROVALS

Product Standards

UL 508; CSA-C22.2 No. 14; IEC/EN 60947-4-1; CE marking

UL File No.

E29184

UL Category Control No.

NKCR

CSA File No.

12528

CSA Class No.

3211-03

North America Certification

UL listed, CSA certified

Specially designed for North America

No

Suitable for

Branch circuits

Max. Voltage Rating


600 V AC

Degree of Protection

IEC: IP00, UL/CSA Type: -

# CHARACTERISTICS


Characteristic curve




These tripping characteristics are mean values of

the spread at 20 °C ambient air temperature in a cold state. Tripping time depends on response current. When the devices are at operational temperature the tripping time of the overload relay reduces to approx. 25 % of the read off value.

Characteristic curve



## DIMENSIONS



Reset/on



Permissible mounting positions





[Imprint](#) | [Privacy Policy](#) | [Legal Disclaimer](#) | [Terms and Conditions](#)  
© 2021 by Eaton Industries GmbH