

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



ZW7-240 - Current transformer-operated overload relay, 160-240A, 1NO+1NC



009737 ZW7-240

[Overview](#) [Specifications](#) [Resources](#)



## 009737 ZW7-240

Current transformer-operated overload relay, 160-240A, 1NO+1NC

Alternate Catalog No.

XTOT240C3S

EL-Nummer (Norway)

4131710

Current transformer-operated overload relay, Product range: ZW7 current transformer-operated overload relays, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Protection with heavy starting duty, Mounting type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00

- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)
- [Characteristics](#)
- [Dimensions](#)

### Delivery program

Product range

ZW7 current transformer-operated overload relays

Description

Test/off button

Reset pushbutton manual/auto

Trip-free release

Protection with heavy starting duty

Mounting type


Separate mounting

**Setting range**

Overload releases  [ ]

160 - 240 A

Contact sequence



Auxiliary contacts

N/O = Normally open

1 N/O

N/C = Normally closed

1 N/C

**Notes**

The main current parameters are defined by the main current wiring which is used.

### Technical data

General

Standards

IEC/EN 60947, VDE 0660, UL, CSA

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30  
 Ambient temperature Open  
 -25 - +50 °C  
 Ambient temperature Enclosed  
 - 25 - 40 °C  
 Temperature compensation  
 Continuous  
 Mounting position  
 As required  
 Weight  
 0.8 kg  
 Mechanical shock resistance  
 10  
 Sinusoidal  
 Shock duration 10 ms g  
 Degree of Protection  
 IP00  
 Protection against direct contact when actuated from front (EN 50274)  
 Finger and back-of-hand proof  
 Altitude  
 Max. 2000 m  
 Main conducting paths  
 Rated impulse withstand voltage [ $U_{imp}$ ]  
 8000 V AC  
 Overvoltage category/pollution degree  
 III/3  
 Rated insulation voltage [ $U_i$ ]  
 1000 V  
 Rated operational voltage [ $U_e$ ]  
 1000 V AC  
 Safe isolation to EN 61140 Between auxiliary contacts and main contacts  
 440 V AC  
 Safe isolation to EN 61140 Between main circuits  
 440 V AC  
 Short-circuit protection Maximum fuse  
 With overload relay in conjunction with a transformer as required for the contactor  
 Current heat loss (3 conductors) Lower value of the setting range  
 3 W  
 Current heat loss (3 conductors) Maximum setting  
 10 W  
 Push-through opening [ $\square$ ]  
 27 mm  
 Auxiliary and control circuits  
 Rated impulse withstand voltage [ $U_{imp}$ ]  
 4000 V  
 Overvoltage category/pollution degree  
 III/3  
 Terminal capacities Solid  
 1 x (0.75 - 4)  
 2 x (0.75 - 4) mm<sup>2</sup>  
 Terminal capacities Flexible with ferrule  
 1 x (0.75 - 2.5)  
 2 x (0.75 - 2.5) mm<sup>2</sup>  
 Terminal capacities Solid or stranded  
 2 x (18 - 14) AWG  
 Terminal screw  
 M3.5  
 Tightening torque  
 1.2 Nm  
 Stripping length  
 8 mm  
 Tools Pozidriv screw driver  
 2 Size  
 Tools Standard screw driver  
 1 x 6 mm  
 Rated insulation voltage [ $U_i$ ]  
 500 V AC  
 Rated operational voltage [ $U_e$ ]  
 500 V AC

Safe isolation to EN61140 between the auxiliary contacts

240 V AC

Conventional thermal current [ $I_{th}$ ]

6 A

Rated operational current [ $I_e$ ] AC-15 Make contact 120 V [ $I_e$ ]

1.5 A

Rated operational current [ $I_e$ ] AC-15 Make contact 220 V 230 V 240 V [ $I_e$ ]

1.5 A

Rated operational current [ $I_e$ ] AC-15 Make contact 380 V 400 V 415 V [ $I_e$ ]

0.5 A

Rated operational current [ $I_e$ ] AC-15 Make contact 500 V [ $I_e$ ]

0.5 A

Rated operational current [ $I_e$ ] AC-15 Break contact 120 V [ $I_e$ ]

1.5 A

Rated operational current [ $I_e$ ] AC-15 Break contact 220 V 230 V 240 V [ $I_e$ ]

1.5 A

Rated operational current [ $I_e$ ] AC-15 Break contact 380 V 400 V 415 V [ $I_e$ ]

0.9 A

Rated operational current [ $I_e$ ] AC-15 Break contact 500 V [ $I_e$ ]

0.8 A

Rated operational current [ $I_e$ ] DC L/R  $\square$  15 ms

Switch-on and switch-off conditions based on DC-13, time constant as specified.

Rated operational current [ $I_e$ ] DC L/R  $\square$  15 ms 24 V [ $I_e$ ]

0.9 A

Rated operational current [ $I_e$ ] DC L/R  $\square$  15 ms 60 V [ $I_e$ ]

0.75 A

Rated operational current [ $I_e$ ] DC L/R  $\square$  15 ms 110 V [ $I_e$ ]

0.4 A

Rated operational current [ $I_e$ ] DC L/R  $\square$  15 ms 220 V [ $I_e$ ]

0.2 A

Short-circuit rating without welding max. fuse

6 A gG/gL

Notes

Ambient temperature: Operating range to IEC/EN 60947, PTB: -5°C to +50°C

Terminal capacities Main circuits solid and flexible with ferrule: When connecting 2 conductors, only the following combinations are admissible:

Rated operational current: Making and breaking currents to DC-13, time constant as stated

Short-circuit rating: See transparent overlay "Fuses" for time/current characteristics (Please enquire)

Rating data for approved types

Auxiliary contacts Pilot Duty AC operated

B300 at opposite polarity

B600 at same polarity

Auxiliary contacts Pilot Duty DC operated

R300

## Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [ $I_n$ ]

240 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]

2.3 W

Equipment heat dissipation, current-dependent [ $P_{vid}$ ]

6.9 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]

0 W

Heat dissipation capacity [ $P_{diss}$ ]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+50 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss10.0.1-27-37-15-01 [AKF075014])

Adjustable current range

160 - 240 A

Max. rated operation voltage U<sub>e</sub>

690 V

Mounting method

Separate positioning

Type of electrical connection of main circuit

Screw connection

Number of auxiliary contacts as normally closed contact

1

Number of auxiliary contacts as normally open contact

1

Number of auxiliary contacts as change-over contact

0

Release class

Other

Reset function input

No

Reset function automatic

Yes

Reset function push-button

Yes

## Approvals

## Approvals

Product Standards

UL 508; CSA-C22.2 No. 14; IEC/EN 60947-4-1; CE marking

UL File No.

E29184

UL Category Control No.

NKCR

CSA File No.

12528

CSA Class No.

3211-03

North America Certification

UL listed, CSA certified

Specially designed for North America

No

Suitable for

Branch circuits

Max. Voltage Rating


600 V AC

Degree of Protection

IEC: IP00, UL/CSA Ttype: -


## Characteristics

Characteristic curve



These tripping characteristics are mean values of the spread at 20 °C ambient air temperature in a cold state. Tripping time depends on response current. When the devices are at operational temperature the tripping time of the overload relay reduces to approx. 25 % of the read off value.

Characteristic curve



## Dimensions



Reset/on



Permissible mounting positions

## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-zw7](#)  
File  
(Web)

## edz files


- [DA-CE-ETN.ZW7-240](#)  
File  
(Web)

## Step files

- [DA-CS-zw7](#)

File  
(Web)

## Wiring diagram



[230S006](#)

Line drawing

Current transformer-operated overload relay circuit symbol

## Dimensions single product

- [230X031](#)  
Line drawing  
Current transformer-operated overload relay
- [230X032](#)  
Line drawing  
Current transformer-operated overload relay  
 Reset/on

## 3D drawing

- [230I009](#)  
Line drawing  
Current transformer-operated overload relay

## Product photo



[230A040](#)


Photo

Current transformer-operated overload relay

## Instruction Leaflet


- [Tripping Characteristic ZW7-240 overload relay \(IL03407128Z\)](#)  
Asset  
(PDF, 08/2017, multilingual)
- [Overload relay, Current transformer-operated overload relay \(IL04210001Z\)](#)  
Asset  
(PDF, multilingual)

## Characteristic curve



[2300DIA-10](#)

Coordinate visualization



[230U008](#)

Coordinate visualization

Tripping characteristic

## Declaration of Conformity

# Declaration of Conformity

## EU

- [ZW7 \(DA-DC-00004078\)](#)  
Asset  
(PDF)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

