

BIMETAL OVERLOAD RELAYS

278435



Overview



Specifications



Resources

How to buy




Photo is representative




Photo is representative

278435

Eaton Moeller® series ZB Overload relay, ZB12, Ir-
Direct mounting, IP20

How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

218194

Eaton Moeller® series M22 Button plate, flat red, STOP

107023

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 5.5 kW, 24 V DC, DC operation

278111

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 5.5 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

278086

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 5.5 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series ZB Thermal overload relay
		CATALOG NUMBER	278435
Product specifications	>	MODEL CODE	ZB12-1
		EAN	4015082784355
		PRODUCT LENGTH/DEPTH	88 mm
		PRODUCT HEIGHT	67 mm
		PRODUCT WIDTH	45 mm
		PRODUCT WEIGHT	0.141 kg
		CERTIFICATIONS	IEC/EN 60947-4-1 UL 60947-4-1 CSA-C22.2 No. 60947-4-1-14 VDE 0660 UL UL Category Control No.: NKCR CSA Class No.: 3211-03 IEC/EN 60947 UL File No.: E29184 CSA CE CSA File No.: 012528

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	1 A
TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (0.75 - 2.5) mm ² , Control circuit cables 1 x (0.75 - 2.5) mm ² , Control circuit cables 2 x (1 - 4) mm ² , Main cables 1 x (1 - 4) mm ² , Main cables
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
STRIPPING LENGTH (CONTROL CIRCUIT CABLE)	8 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.

MOUNTING METHOD	Direct attachment Direct mounting
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
STRIPPING LENGTH (MAIN CABLE)	10 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RESET FUNCTION	Push-button Automatic
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	1 A, Class J/CC, max. Fuse, SCCR (UL/CSA) 100 kA, Fuse, SCCR (UL/CSA)
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
SCREW SIZE	M3.5, Terminal screw, Control circuit cables M4, Terminal screw
ADJUSTABLE CURRENT RANGE - MIN	0.6 A
PROTECTION	Finger and back-of-hand proof Protection against di actuated from front (EN 50274)
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
FEATURES	Trip-free release Test/off button Phase-failure sensitivity (according to IEC/EN 6094 102) Reset pushbutton manual/auto
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
VOLTAGE RATING - MAX	600 VAC
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
SAFE ISOLATION	240 V AC, Between auxiliary contacts, According to 440 V AC, Between main circuits, According to EN 440 V AC, Between auxiliary contacts and main co EN 61140
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A

CLASS	CLASS 10 A
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	2.3 W
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Accessories • Overload relay ZB up to 150 A
OVERLOAD RELEASE CURRENT SETTING - MIN	0.6 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	6.9 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	≤0.25 %/K, residual error for T > 40° Continuous
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 1 x (1 - 6) mm ² , Main cables 2 x (1 - 6) mm ² , Main cables 2 x (0.75 - 4) mm ² , Control circuit cables
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
OVERLOAD RELEASE CURRENT SETTING - MAX	1 A
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 8, Main cables 2 x (18 - 14), Control circuit cables

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP20
OVERVOLTAGE CATEGORY	III
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
TIGHTENING TORQUE	1.8 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
ADJUSTABLE CURRENT RANGE - MAX	1 A
FRAME SIZE	ZB12
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
SHORT-CIRCUIT PROTECTION RATING	Max. 6 A gG/gL, fuse, Without welding, Auxiliary 4 A gG/gL, Fuse, Type "2" coordination 25 A gG/gL, Fuse, Type "1" coordination
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	B300 at opposite polarity, AC operated (UL/CSA) B600 at opposite polarity, AC operated (UL/CSA) R300, DC operated (UL/CSA)

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Manuals and user guides

mCAD model

Wiring diagrams

278435



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

