



278455
ZB65-10

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Characteristics

Dimensions

DELIVERY PROGRAM

Product range
Overload relay ZB up to 150 A

Product range
Accessories

Accessories
Overload relays

Frame size
ZB65

Phase-failure sensitivity
IEC/EN 60947, VDE 0660 Part 102

Description
Test/off button
Reset pushbutton manual/auto
Trip-free release


Mounting type

Direct mounting



6 - 10 A

Contact sequence



Auxiliary contacts

NO = Normally open
1 NO

NC = Normally closed
1 NC

For use with

DILM40

DILM60

DILM65

DILM72

DILMF40

DILMF50

DILMF65

DIULM40

DIULM60

DIULM65

SDAINLM70

SDAINLM90

SDAINLM115

Short-circuit protection

Type "1" coordination \geq [gG/gL]
50 A

Type "2" coordination \geq [gG/gL]
25 A

Notes

Overload trigger: tripping class 10 A

Short circuit protection: observe the maximum permissible fuse of the contactor with direct device mounting.

Suitable for protection of Ex e-motors.

□ II(2)G [Ex d] [Ex e] [Ex px], II(2)D [Ex p] [Ex t]

PTB 10 ATEX 3010

Observe manual MN03407005Z-DE/EN

Notes

Fitted directly to the
contactor

Separate
mounting

□

□

1 Contactor

2 Bases

TECHNICAL DATA

General

Standards

IEC/EN 60947, VDE 0660, UL, CSA

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature

Operating range to IEC/EN 60947

PTB: -5 °C- +55 °C

Ambient temperature

Open

-25 - +55 °C

Ambient temperature

Enclosed

- 25 - 40 °C

Temperature compensation

Continuous

Weight

0.22 kg

Mechanical shock resistance

10

Sinusoidal
Shock duration 10 ms g

Degree of Protection
IP00

Protection against direct contact when actuated
from front (EN 50274)
Finger and back-of-hand proof

Altitude
Max. 2000 m

Main conducting paths

Rated impulse withstand voltage [U_{imp}]
6000 V AC

Overvoltage category/pollution degree
III/3

Rated insulation voltage [U_i]
690 V

Rated operational voltage [U_e]
690 V AC

Safe isolation to EN 61140
Between auxiliary contacts and main contacts
440 V AC

Safe isolation to EN 61140
Between main circuits
440 V AC

Temperature compensation residual error > 40 °C
 0.25 %/K

Current heat loss (3 conductors)
Lower value of the setting range
2.7 W

Current heat loss (3 conductors)
Maximum setting
7.5 W

Terminal capacities

Solid

1 x (1 - 16)

2 x (1 - 16) mm²

Terminal capacities

Flexible with ferrule

1 x (1 - 25)

2 x (1 - 25) mm²

Terminal capacities

Stranded

1 x (16 - 25) mm²

Terminal capacities

Solid or stranded

14 - 2 AWG

Terminal screw

M6

Tightening torque

3.5 Nm

Stripping length

11 mm

Tools

Pozidriv screwdriver

2 Size

Tools

Standard screw driver

1 x 6 mm

Auxiliary and control circuits

Rated impulse withstand voltage [U_{imp}]

4000 V

Overvoltage category/pollution degree

III/3

Terminal capacities

Solid

1 x (0.75 - 4)

2 x (0.75 - 4) mm²

Terminal capacities
Flexible with ferrule
1 x (0.75 - 2.5)
2 x (0.75 - 2.5) mm²

Terminal capacities
Solid or stranded
2 x (18 - 14) AWG

Terminal screw
M3.5

Tightening torque
1.2 Nm

Stripping length
8 mm

Tools
Pozidriv screwdriver
2 Size

Tools
Standard screwdriver
1 x 6 mm

Rated insulation voltage [U_i]
500 V AC

Rated operational voltage [U_e]
500 V AC

Safe isolation to EN 61140
between the auxiliary contacts
240 V AC

Conventional thermal current [I_{th}]
6 A

Rated operational current [I_e]
AC-15
Make contact
120 V [I_e]
1.5 A

Rated operational current [I_e]
AC-15
Make contact
220 V 230 V 240 V [I_e]
1.5 A

Rated operational current [I_e]
AC-15
Make contact
380 V 400 V 415 V [I_e]
0.5 A

Rated operational current [I_e]
AC-15
Make contact
500 V [I_e]
0.5 A

Rated operational current [I_e]
AC-15
Break contact
120 V [I_e]
1.5 A

Rated operational current [I_e]
AC-15
Break contact
220 V 230 V 240 V [I_e]
1.5 A

Rated operational current [I_e]
AC-15
Break contact
380 V 400 V 415 V [I_e]
0.9 A

Rated operational current [I_e]
AC-15
Break contact
500 V [I_e]
0.8 A

Rated operational current [I_e]
DC L/R \square 15 ms
Switch-on and switch-off conditions based on
DC-13, time constant as specified.

Rated operational current [I_e]
DC L/R \square 15 ms
24 V [I_e]
0.9 A

Rated operational current [I_e]
DC L/R □ 15 ms
60 V [I_e]
0.75 A

Rated operational current [I_e]
DC L/R □ 15 ms
110 V [I_e]
0.4 A

Rated operational current [I_e]
DC L/R □ 15 ms
220 V [I_e]
0.2 A

Short-circuit rating without welding
max. fuse
6 A gG/gL

Notes

Notes

Ambient air temperature: Operating range to IEC/EN
60947, PTB: -5°C to +55°C
Main circuits terminal capacity solid and flexible
conductors with ferrules: When using 2
conductors use equal cross-sections.

Rating data for approved types

Auxiliary contacts
Flot Duty
AC operated
B300 at opposite polarity
B600 at same polarity

Auxiliary contacts
Flot Duty
DC operated
R300

Short Circuit Current Rating
Basic Rating
SCCR
5 kA

Short Circuit Current Rating
Basic Rating
max. Fuse

40 A

Short Circuit Current Rating
Basic Rating
max. CB
40 A

Short Circuit Current Rating
480 V High Fault
SCCR (fuse)
100 kA

Short Circuit Current Rating
480 V High Fault
max. Fuse
15 Class J/CCA

Short Circuit Current Rating
480 V High Fault
SCCR (CB)
65 kA

Short Circuit Current Rating
480 V High Fault
max. CB
15 A

Short Circuit Current Rating
600 V High Fault
SCCR (fuse)
100 kA

Short Circuit Current Rating
600 V High Fault
max. Fuse
15 Class J/CCA

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
10 A

Heat dissipation per pole, current-dependent [P_{id}]

2.5 W

Equipment heat dissipation, current-dependent

[P_{id}]

7.5 W

Static heat dissipation, non-current-dependent [P_{st}]

0 W

Heat dissipation capacity [P_{diss}]

0 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+55 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.5 Lifting

Does not apply, since the entire switchgear needs

to be evaluated.

10.2 Strength of materials and parts

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss10.0.1-27-37-15-01 [AKF075014])

Adjustable current range
6 - 10 A

Max. rated operation voltage U_e
690 V

Mounting method
Direct attachment

Type of electrical connection of main circuit
Screw connection

Number of auxiliary contacts as normally closed contact
1

Number of auxiliary contacts as normally open contact

1

Number of auxiliary contacts as change-over
contact
0

Release class
CLASS 10

Reset function input
No

Reset function automatic
Yes

Reset function push-button
Yes

APPROVALS

Product Standards
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.
60947-4-1-14; CE marking

UL File No.
E29184

UL Category Control No.
NKCR

CSA File No.
12528

CSA Class No.
3211-03

North America Certification
UL listed, CSA certified

Specially designed for North America
No


Suitable for
Branch circuits

Max. Voltage Rating
600 V AC

Degree of Protection
IEC: IP00, UL/CSA Type: -


CHARACTERISTICS

Characteristic curve



These tripping characteristics are mean values of the spread at 20 °C ambient temperature in a cold state. Tripping time depends on response current. On devices at operating temperature the tripping time of the overload relay drops to approx. 25 % of the read value. Specific characteristics for each individual setting range can be found in the manual.

DIMENSIONS



- OFF
- Reset/ON



With base ZB65-XEZ

