

BIMETAL OVERLOAD RELAYS

278457



Overview



Specifications



Resources

How to buy




Photo is representative




Photo is representative

278457

Eaton Moeller® series ZB Overload relay, ZB65, Ir
Direct mounting, IP00

How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

278211

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 18.5 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

278261

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 30 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

278208

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 18.5 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

277864

Eaton Moeller® series DILM Contactors, 380 V 400 V 22 kW, 2 N/O, 2 NC, 230 V 50 Hz, 240 V 60 Hz, AC operation, terminals

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series ZB Thermal overload relay.**CATALOG NUMBER** 278457

Product specifications

>

MODEL CODE ZB65-24**EAN** 4015082784577**PRODUCT LENGTH/DEPTH** 88 mm**PRODUCT HEIGHT** 75 mm**PRODUCT WIDTH** 60 mm**PRODUCT WEIGHT** 0.22 kg

CERTIFICATIONS

CE
IEC/EN 60947-4-1
UL File No.: E29184
CSA-C22.2 No. 60947-4-1-14
CSA Class No.: 3211-03
UL
UL Category Control No.: NKCR
CSA
VDE 0660
CSA File No.: 012528
IEC/EN 60947
UL 60947-4-1

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 24 A**TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)**

1 x (0.75 - 2.5) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables
2 x (1 - 25) mm², Main cables
1 x (1 - 25) mm², Main cables

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications must be observed.

STRIPPING LENGTH (CONTROL CIRCUIT CABLE)

8 mm

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN

25 °C

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications must be observed.

MOUNTING METHOD	Direct attachment Direct mounting
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
STRIPPING LENGTH (MAIN CABLE)	11 mm
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V)	100 kA, Fuse, SCCR (UL/CSA) 50 A, max. CB, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 45 A, Class J/CC, max. Fuse, SCCR (UL/CSA)
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RESET FUNCTION	Push-button Automatic
SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	90 A, max. CB, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) 90 A, max. Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V)	100 kA, Fuse, SCCR (UL/CSA) 45 A, Class J/CC, max. Fuse, SCCR (UL/CSA)
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
SCREW SIZE	M6, Terminal screw, Main cables M3.5, Terminal screw, Control circuit cables
ADJUSTABLE CURRENT RANGE - MIN	16 A
PROTECTION	Finger and back-of-hand proof, Protection against di actuated from front (EN 50274)
TERMINAL CAPACITY (STRANDED)	1 x (16 - 25) mm ² , Main cables
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
FEATURES	Test/off button Trip-free release Reset pushbutton manual/auto Phase-failure sensitivity (according to IEC/EN 6094 102)
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
VOLTAGE RATING - MAX	600 VAC
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND	Does not apply, since the entire switchgear needs to

COMPONENTS	
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
SAFE ISOLATION	240 V AC, Between auxiliary contacts, According to 440 V, Between auxiliary contacts and main contact 61140 440 V AC, Between main circuits, According to EN
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
CLASS	CLASS 10 A
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the inf instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	1.9 W
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Accessories • Overload relay ZB up to 150 A
OVERLOAD RELEASE CURRENT SETTING - MIN	16 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	5.7 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	≤ 0.25 %/K, residual error for T > 40° Continuous
TERMINAL CAPACITY (SOLID)	2 x (1 - 16) mm ² , Main cables 1 x (0.75 - 4) mm ² , Control circuit cables 1 x (1 - 16) mm ² , Main cables 2 x (0.75 - 4) mm ² , Control circuit cables
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.

RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
OVERLOAD RELEASE CURRENT SETTING - MAX	24 A
TERMINAL CAPACITY (SOLID/STRANDED AWG)	14 - 2, Main cables 2 x (18 - 14), Control circuit cables
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP00
OVERVOLTAGE CATEGORY	III
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V (auxiliary and control circuits)
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
TIGHTENING TORQUE	3.5 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
ADJUSTABLE CURRENT RANGE - MAX	24 A
FRAME SIZE	ZB65
SCREWDRIVER SIZE	2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
SHORT-CIRCUIT PROTECTION RATING	63 A gG/gL, Fuse, Type "1" coordination Max. 6 A gG/gL, fuse, Without welding, Auxiliary 50 A gG/gL, Fuse, Type "2" coordination
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V

SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 m
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY)	B600 at opposite polarity, AC operated (UL/CSA) R300, DC operated (UL/CSA) B300 at opposite polarity, AC operated (UL/CSA)

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Manuals and user guides

mCAD model

Wiring diagrams

278457



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

