

BIMETAL OVERLOAD RELAYS

278458



Overview



Specifications



Resources

How to buy



Photo is representative




Photo is representative

278458

Eaton Moeller® series ZB Overload relay, ZB65, Ir-
Direct mounting, IP00

How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

278208

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 18.5 kW, 110 V 50 Hz, 120 V 60 Hz, AC operation

277864

Eaton Moeller® series DILM Contactor, 380 V 400 V 22 kW, 2 N/O, 2 NC, 400 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals

278211

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 18.5 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

278261

Eaton Moeller® series DIUL Reversing contactor combination, 380 V 400 V: 18.5 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series ZB Thermal overload relay.**CATALOG NUMBER** 278458

Product specifications

>

MODEL CODE ZB65-40**EAN** 4015082784584**PRODUCT LENGTH/DEPTH** 88 mm**PRODUCT HEIGHT** 75 mm**PRODUCT WIDTH** 60 mm**PRODUCT WEIGHT** 0.22 kg

CERTIFICATIONS

CE
CSA
VDE 0660
UL 60947-4-1
UL File No.: E29184
CSA Class No.: 3211-03
UL Category Control No.: NKCR
IEC/EN 60947-4-1
IEC/EN 60947
UL
CSA-C22.2 No. 60947-4-1-14
CSA File No.: 012528

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 40 A**TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)**

2 x (1 - 25) mm², Main cables
1 x (0.75 - 2.5) mm², Control circuit cables
2 x (0.75 - 2.5) mm², Control circuit cables
1 x (1 - 25) mm², Main cables

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications must be observed.

STRIPPING LENGTH (CONTROL CIRCUIT CABLE)

8 mm

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN

25 °C

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications must be observed.

| | |
|---|---|
| MOUNTING METHOD | Direct mounting Direct attachment |
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to |
| STRIPPING LENGTH (MAIN CABLE) | 11 mm |
| SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 480 V) | 60 A, max. CB, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 60 A, Class J/CC, max. Fuse, SCCR (UL/CSA) 100 kA, Fuse, SCCR (UL/CSA) |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX | 40 °C |
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
| RESET FUNCTION | Push-button Automatic |
| SHORT-CIRCUIT CURRENT RATING (BASIC RATING) | 125 A, max. CB, SCCR (UL/CSA) 125 A, max. Fuse, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) |
| SHORT-CIRCUIT CURRENT RATING (HIGH FAULT AT 600 V) | 60 A, Class J/CC, max. Fuse, SCCR (UL/CSA) 100 kA, Fuse, SCCR (UL/CSA) |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| SCREW SIZE | M6, Terminal screw, Main cables M3.5, Terminal screw, Control circuit cables |
| ADJUSTABLE CURRENT RANGE - MIN | 24 A |
| PROTECTION | Finger and back-of-hand proof, Protection against di actuated from front (EN 50274) |
| TERMINAL CAPACITY (STRANDED) | 1 x (16 - 25) mm ² , Main cables |
| AMBIENT OPERATING TEMPERATURE - MAX | 55 °C |
| CLIMATIC PROOFING | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| FEATURES | Trip-free release Reset pushbutton manual/auto Phase-failure sensitivity (according to IEC/EN 6094 102) Test/off button |
| STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS | 0 W |
| ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT | Screw connection |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| VOLTAGE RATING - MAX | 600 VAC |
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND | Does not apply, since the entire switchgear needs to |

| COMPONENTS | |
|---|--|
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to |
| SAFE ISOLATION | 440 V, Between auxiliary contacts and main contact 61140 440 V AC, Between main circuits, According to EN 240 V AC, Between auxiliary contacts, According to |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V | 1.5 A |
| CLASS | CLASS 10 A |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information instruction leaflet (IL) is observed. |
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS) | 1 |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V | 0.9 A |
| HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID | 3.1 W |
| PRODUCT CATEGORY | <ul style="list-style-type: none"> • Accessories • Overload relay ZB up to 150 A |
| OVERLOAD RELEASE CURRENT SETTING - MIN | 24 A |
| RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V | 0.75 A |
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID | 9,3 W |
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
| SUITABLE FOR | Branch circuits, (UL/CSA) |
| TEMPERATURE COMPENSATION | Continuous ≤ 0.25 %/K, residual error for T > 40° |
| TERMINAL CAPACITY (SOLID) | 2 x (0.75 - 4) mm ² , Control circuit cables 1 x (1 - 16) mm ² , Main cables 2 x (1 - 16) mm ² , Main cables 1 x (0.75 - 4) mm ² , Control circuit cables |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS) | 1 |
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |

| | |
|--|---|
| RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V | 0.2 A |
| CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN) | 6 A |
| OVERLOAD RELEASE CURRENT SETTING - MAX | 40 A |
| TERMINAL CAPACITY (SOLID/STRANDED AWG) | 2 x (18 - 14), Control circuit cables 14 - 2, Main cables |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| DEGREE OF PROTECTION | IP00 |
| OVERVOLTAGE CATEGORY | III |
| NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS) | 0 |
| POLLUTION DEGREE | 3 |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 6000 V AC 4000 V (auxiliary and control circuits) |
| 10.10 TEMPERATURE RISE | The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device |
| TIGHTENING TORQUE | 3.5 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables |
| ADJUSTABLE CURRENT RANGE - MAX | 40 A |
| FRAME SIZE | ZB65 |
| SCREWDRIVER SIZE | 2, Terminal screw, Pozidriv screwdriver 1 x 6 mm, Terminal screw, Standard screwdriver |
| RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V | 1.5 A |
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Meets the product standard's requirements. |
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS) | 1 |
| SHORT-CIRCUIT PROTECTION RATING | Max. 6 A gG/gL, fuse, Without welding, Auxiliary 125 A gG/gL, Fuse, Type "1" coordination 63 A gG/gL, Fuse, Type "2" coordination |
| NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS) | 1 |
| RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V | 0.4 A |
| RATED OPERATIONAL VOLTAGE (UE) - MAX | 690 V |

| | |
|--|--|
| SHOCK RESISTANCE | 10 g, Mechanical, Sinusoidal, Shock duration 10 m |
| RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V | 0.9 A |
| SWITCHING CAPACITY (AUXILIARY CONTACTS, PILOT DUTY) | R300, DC operated (UL/CSA) B300 at opposite polarity, AC operated (UL/CSA) B600 at opposite polarity, AC operated (UL/CSA) |

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Manuals and user guides

mCAD model

Wiring diagrams

278458



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

