


XENERGY SAFETY CI  
017527

  
Overview

  
Specifications

  
Resources

How to



# 017527

Eaton xEnergy Safety Ci LV systems LV switchgear  
top+bottom open, HxWxD=250x375x150mm

[Access the Online Catalog](#)

## GENERAL SPECIFICATIONS

General specifications >

**PRODUCT NAME** Eaton xEnergy Safety Ci empty enclosure insulated

**CATALOG NUMBER** 017527

Product specifications >

**MODEL CODE** CI43-125

**EAN** 4015080175278

**PRODUCT LENGTH/DEPTH** 150 mm

**PRODUCT HEIGHT** 250 mm

**PRODUCT WIDTH** 375 mm

**PRODUCT WEIGHT** 1.717 kg

**COMPLIANCES** RoHS conform

**CERTIFICATIONS** EN 62208  
EN 61439-2

## PRODUCT SPECIFICATIONS

<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility.
<b>CIRCUIT INTEGRITY</b>	Other
<b>TEMPERATURE RESISTANCE</b>	Temperature resistant: 85 °C (enclosure bolt) Temperature resistant: -40 °C - 120 °C (enclosure) Temperature resistant: 80 °C (gasket)
<b>PLATE THICKNESS (COVER/DOOR)</b>	6 mm
<b>RAL-NUMBER</b>	7035
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Is the panel builder's responsibility.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility.
<b>PLATE THICKNESS (CABINET)</b>	6 mm
<b>MOUNTING METHOD</b>	Surface mounted (plaster)
<b>10.2.5 LIFTING</b>	10 kg per enclosure with support frame and lifting aid and secured as per the latest applicable instruction leaflet
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>NUMBER OF OPENINGS (FLANGE PLATES)</b>	4
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>CHEMICAL RESISTANCE</b>	Not resistant to: alkalis, benzene Resistant against: acids < 10 %, mineral oil, alcohol salt solutions Partly resistant to: Acids > 10 %
<b>COVER/DOOR MODEL</b>	Closed
<b>INTERNAL DEPTH</b>	125 mm
<b>MOUNTING DEPTH WITH MOUNTING PLATE</b>	125 mm
<b>SPECIAL FEATURES</b>	Housing prepared for distribution board Two sides closed out two sides open Sealable cover fasteners Integrated mechanism for short-circuits
<b>COLOR</b>	Gray
<b>UNIT TYPE</b>	Single unit
<b>BUILT-IN DEPTH</b>	125 mm
<b>FEATURES</b>	UV resistance beneath protective shield Cover with overpressure release
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	8 kV
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Is the panel builder's responsibility.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Protection class 2, therefore not applicable.
<b>COVER/DOOR COLOR</b>	7035

<b>COVER/DOOR COLOR</b>	Transparent
<b>SURFACE PROTECTION</b>	Other
<b>COVER/DOOR TYPE</b>	None Transparent Optional
<b>10.13 MECHANICAL FUNCTION</b>	Meets the product standard's requirements.
<b>10.2.6 MECHANICAL IMPACT</b>	IK10
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Meets the product standard's requirements.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	IP65
<b>NOMINAL CURRENT</b>	1600 A
<b>FLAMMABILITY CHARACTERISTICS (UL)</b>	V1 (base) (UL94) V2 (cover) (UL94)
<b>SUITABLE FOR</b>	Lightning protection Outdoor use
<b>SURFACE FINISHING</b>	Resistant to corrosion
<b>NUMBER OF ROWS</b>	0
<b>PROTECTION CLASS</b>	II
<b>WIDTH IN NUMBER OF MODULAR SPACINGS</b>	15
<b>HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)</b>	39 W
<b>NUMBER OF CONDUIT INLETS</b>	76
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Lower part: 960 °C / cover: 850 °C
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	U <sub>i</sub> = 1000 V AC
<b>DEGREE OF PROTECTION</b>	IP65 Other IK10
<b>HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)</b>	20 W
<b>HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)</b>	18 W
<b>HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)</b>	41 W
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)</b>	37 W

<b>10.10 TEMPERATURE RISE</b>	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the devi
<b>MATERIAL</b>	Glass-fibre reinforced polycarbonate (base) Non-reinforced polycarbonate (cover) Halogen free
<b>FUNCTIONS</b>	Extension possible
<b>AMBIENT OPERATING TEMPERATURE DETAILS</b>	-40 °C - 80 °C
<b>HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)</b>	19 W
<b>SALINE SPRAY RESISTANCE</b>	IEC 60068-2-11
<b>ENCLOSURE MATERIAL</b>	Plastic
<b>TYPE</b>	Basic enclosure Panel enclosures xEnergy Safety Ci
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Not relevant to indoor installations.
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>SURFACE TREATMENT</b>	Resistant to corrosion
<b>NUMBER OF MODULES</b>	1

Brochures

Catalogs

Drawings

Installation instructions

mCAD model

017527



such is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.