

Select your language

- German
- English
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

C45E-200 - Insulated enclosure, +knockouts, HxWxD=500x375x225mm



001891 C45E-200

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

## 001891 CI45E-200

Insulated enclosure, +knockouts, HxWxD=500x375x225mm


EL-Nummer (Norway)

0004132086

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=1xM50/32 and 2xM40/25 and 8xM25/16 and 2xM20, each side=2xM50/32 and 12xM25/16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7035, grey (base), transparent smoky, (cover), mounting depth with mounting plate=200mm, cover type: transparent smoky, base type: knockout cover is optionally fitted by user with cylinder lock DVZ....-Cl.

### Delivery program

#### Dimensions



Product range  
xEnergy Safety Cl  
Basic function  
Basic enclosures  
Product function  
Individual enclosures  
Single unit/Complete unit  
Single unit

Standards  
EN 62208  
EN 61439-2  
Degree of Protection  
IP65

Description  
With metric knockouts in all sides of the enclosure  
Include fixing straps for wall mounting  
Sealable cover fasteners  
Full-area knockouts in the sides  
can be converted to a distribution board enclosure  
Integrated pressure-relief mechanism for short-circuits

Colour  
RAL 7035, light gray (base)  
Transparent, smoky gray (cover)

Width  
375 mm  
Height  
500 mm  
Depth  
225 mm  
Mounting depth with mounting plate  
200 mm  
Mounting depth for mounting rail 7.5 mm height  
192.5 mm  
Mounting depth for mounting rail 15 mm height  
185 mm

Enclosure depth  
 Legend for the graphic  
 Dimensions from top:  
 Mounting depth with mounting plate  
 Mounting depth for mounting rail 7.5 mm height  
 Mounting depth for mounting rail 15 mm height  
 Enclosure depth  
 Enclosure depth



For use with  
 Eaton Switching and protection devices

#### Notes

<b>D</b>
1 x M50/32 6 x M25/16
<b>E</b>
1 x M50/32 2 x M40/25 8 x M25/16 2 x M20

## Technical data

General  
 Standards  
 EN 62208  
 EN 61439-2  
 Ambient temperature  
 -40 - +80 °C  
 Degree of Protection  
 IP65  
 Material characteristics  
 Material  
 glass-fibre reinforced polycarbonate (base)  
 non-reinforced polycarbonate (cover)  
 Halogen free  
 Surface treatment  
 Resistant to corrosion  
 Material properties  
 Thermal Temperature resistant  
 -40 °C - 120 °C (enclosure)  
 85 °C (enclosure bolt)  
 80 °C (gasket)  
 Chemical resistance Chemical resistant  
 Resistant against: Acids < 10 %, mineral oil, alcohol, gasoline, greases, salt solutions  
 Partly resistant to: Acids > 10 %  
 Not resistant to: alkalis, benzene  
 Atmospheric Saline spray  
 IEC 60068-2-11  
 Atmospheric UV resistance  
 Beneath protective shield  
 Flammability characteristics Flammability classification according to UL94  
 V1 (base)  
 V2 (cover)

## Design verification as per IEC/EN 61439

Technical data for design verification

Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [P<sub>v</sub>]

36 W

Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [P<sub>v</sub>]

33 W

Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [P<sub>v</sub>]

31 W

Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [P<sub>v</sub>]

72 W

Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [P<sub>v</sub>]

67 W

Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [P<sub>v</sub>]

62 W  
 IEC/EN 61439 design verification  
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
 Lower part: 960 °C / cover: 850 °C, meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
 Not relevant to indoor installations.  
 10.2 Strength of materials and parts 10.2.5 Lifting  
 30 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.  
 10.2 Strength of materials and parts 10.2.6 Mechanical impact  
 IK10  
 10.2 Strength of materials and parts 10.2.7 Inscriptions  
 Meets the product standard's requirements.  
 10.3 Degree of protection of ASSEMBLIES  
 IP65  
 10.4 Clearances and creepage distances  
 Is the panel builder's responsibility.  
 10.5 Protection against electric shock  
 Protection class 2, therefore not applicable.  
 10.6 Incorporation of switching devices and components  
 Is the panel builder's responsibility.  
 10.7 Internal electrical circuits and connections  
 Is the panel builder's responsibility.  
 10.8 Connections for external conductors  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.2 Power-frequency electric strength  
 $U_i = 1000 \text{ V AC}$   
 10.9 Insulation properties 10.9.3 Impulse withstand voltage  
 8 kV  
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
 Meets the product standard's requirements.  
 10.10 Temperature rise  
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  
 10.11 Short-circuit rating  
 Is the panel builder's responsibility.  
 10.12 Electromagnetic compatibility  
 Is the panel builder's responsibility.  
 10.13 Mechanical function  
 Meets the product standard's requirements.

## Technical data ETIM 7.0

Distribution boards (EG000023) / Empty cabinet (EC000058)  
 Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Empty cabinet (small distribution board) (ecl@ss10.0.1-27-14-24-08 [ACN385011])  
 Mounting method  
 Surface mounted (plaster)  
 Type of cover  
 Optional  
 Cover model  
 Closed  
 Type of door  
 None  
 Transparent cover/door  
 Yes  
 With lock  
 No  
 Nominal current (In)  
 1600 A  
 Height  
 500 mm  
 Width  
 375 mm  
 Depth  
 225 mm  
 Built-in depth  
 200 mm  
 Internal depth  
 200 mm  
 Plate thickness cabinet  
 6 mm  
 Plate thickness door/cover  
 6 mm  
 Colour  
 Grey  
 RAL-number  
 7035  
 Number of modules  
 1  
 Number of rows  
 0  
 Width in number of modular spacings

17  
 Number of openings for flange plates  
 6  
 Extension possible  
 Yes  
 Number of conduit inlets  
 104  
 Material housing  
 Plastic  
 Surface protection  
 Other  
 With mounting plate  
 No  
 Suitable for outdoor use  
 Yes  
 Suitable for lightning protection  
 Yes  
 Degree of protection (IP)  
 IP65  
 Degree of protection (NEMA)  
 Other  
 Protection class  
 II  
 Impact strength  
 IK10  
 Circuit integrity  
 Other

### Dimensions



## AWA32-567 Ci insulated enclosure

- [AWA32-567 Ci insulated enclosure](#)  
(PDF)

## Additional product information


- [Manufacturer's Declaration C-RoHS](#)  
(PDF)
- [Declaration of conformity](#)  
(PDF)
- [model certification xEnergy Safety Ci](#)  
(Web)
- [Save time – we assist you with expert pre-assembly](#)  
(Web)
- [product information xEnergy Safety Ci](#)  
(Web)
- [tool for calculating the power loss for switching device combinations](#)  
(Web)
- [configurator - xEnergy family](#)  
(Web)

## Product photo




[Photo](#)  
 INSULATED ENCLOSURE C45  
 Product photo  
 Photo

## Dimensions single product



[Dimensions](#)  
 Individual enclosure  
 Dimensions single product  
 Line drawing




[Enclosure depth](#)  
 Mounting depth  
 Dimensions single product

Line drawing

- [320X029](#)  
Individual enclosure, panel enclosure  
Dimensions single product  
Line drawing
- [320X032](#)  
Panel enclosure  
Dimensions single product  
Line drawing
- [320X033](#)  
Panel enclosure  
Dimensions single product  
Line drawing
- [320X184](#)  
Dimensions single product  
Line drawing

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2020 by Eaton Industries GmbH