



**Cable grommet, PG21, IP65**

**Part no. KT21**  
**Catalog No. 026777**

**EL-Nummer 4132343**  
**(Norway)**

**Delivery program**

|   |  |                 |                                    |
|---|--|-----------------|------------------------------------|
| Product range                                 |  |                 | General switchboard accessories    |
| Accessories                                   |  |                 | Cable management                   |
| Accessories                                   |  |                 | Cable grommets                     |
| For use with                                  |  |                 | For wall thickness 2 - 8 mm        |
| Material                                      |  |                 | Soft PVC<br>cadmium- and lead-free |
| Surface finish                                |  |                 | similar RAL 7035                   |
| Cable entry                                   |  |                 | PG 21                              |
| Hole diameter                                 |  | mm              | 29,5                               |
| Outer cable diameter                          |  | mm              | 12.5 - 20                          |
| Example of application: NYM/NYY cable, 4-core |  | mm <sup>2</sup> | 1,5 - 16                           |

**Technical data**

**Material characteristics**

|          |  |  |                                    |
|----------|--|--|------------------------------------|
| Material |  |  | Soft PVC<br>cadmium- and lead-free |
|----------|--|--|------------------------------------|

**Technical data ETIM 7.0**

|  |  |    |                          |
|--|--|----|--------------------------|
| Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879)  |  |    |                          |
| Electric engineering, automation, process control engineering / Electrical installation, device / Connection devices / Feed through spout (ecl@ss10.0.1-27-14-44-21 [AD1139007]) |  |    |                          |
| Model  |  |    | Closed                   |
| Insert for cable gland   |  |    | No                       |
| Cable entry  |  |    | Round                    |
| Number of cables   |  |    | 1 - 1                    |
| Suitable for cable diameter  |  | mm | 12.5 - 20                |
| Bore diameter  |  | mm | 29.5                     |
| For wall thickness   |  | mm | 2 - 8                    |
| Thread size (metric)   |  |    | 0                        |
| Thread size PG   |  |    | 21                       |
| Total length   |  | mm | 0                        |
| With strain relief   |  |    | No                       |
| Shrink technique   |  |    | No                       |
| Angle model  |  |    | No                       |
| Material   |  |    | Plastic                  |
| Material quality   |  |    | Polyvinyl chloride (PVC) |
| Surface protection   |  |    | Other                    |
| Halogen free   |  |    | No                       |
| Colour   |  |    | Grey                     |
| Gastight   |  |    | Yes                      |
| Fire resistant   |  |    | No                       |
| Watertight   |  |    | Yes                      |
| Degree of protection (IP)  |  |    | IP65                     |
| Working temperature  |  | °C | -5 - 40                  |

## Dimensions

