DATASHEET - KT36



Cable grommet, PG36

Part no. KT36 Catalog No. 033896

EL-Nummer (Norway) 4132345



Delivery program

Product range			General switchboard accessories
Accessories			Cable management
Accessories			Cable grommets
For use with			For wall thickness 2 - 8 mm
Material			Soft PVC cadmium- and lead-free
Surface finish			similar RAL 7035
Cable entry			PG 36
Hole diameter	r	mm	48
Outer cable diameter	r	mm	18 - 40
Example of application: NYM/NYY cable, 4-core	r	mm ²	10 - 70

Technical data

Material characteristics

Material	Soft PVC
	cadmium- and lead-free

Technical data ETIM 7.0

Cable and wire entry systems (EG000009) / Cable entry sleeve (EC000879)		
Electric engineering, automation, process control engineering / Electrical installation	n, device / Connection	n devices / Feed through spout (ecl@ss10.0.1-27-14-44-21 [ADI139007])
Model		Closed
Insert for cable gland		No
Cable entry		Round
Number of cables		1-1
Suitable for cable diameter	mm	18 - 40
Bore diameter	mm	48
For wall thickness	mm	2 - 8
Thread size (metric)		0
Thread size PG		36
Total length	mm	0
With strain relief		No
Shrink technique		No
Angle model		No
Material		Plastic
Material quality		Polyvinyl chloride (PVC)
Surface protection		Other
Halogen free		No
Colour		Grey
Gastight		Yes
Fire resistant		No
Watertight		Yes
Degree of protection (IP)		IP66
Working temperature	°C	-5 - 40

Dimensions

