

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English




K3X240/4 - Connection terminal, 1000A, 4p, flat/round



055866 K3X240/4

[Overview](#) [Specifications](#) [Resources](#)



055866 K3X240/4

Connection terminal, 1000A, 4p, flat/round

EL-Nummer (Norway)

4132428

K connecting terminals, for AL and CU, one side round and the other side flat, rated operational current $I_e=1000$ A, number pole=4, terminal capacities: Copper round cable stranded, sectoral stranded, round cable solid, sectoral solid and aluminium round conductor solid, sectoral solid=2x150-300 or 3x50-240 or aluminum sectoral solid=2x150-240 or 3x150-185 mm². Other side: copper band 2x(11x21x1.10) or 40x1x10 or 50x1x60 or Cu bar=15x mm, notes: Conversion kits for strip terminal in cable connection available separately, terminal covers available separately

- [Delivery program](#)
- [Technical data ETIM 7.0](#)

Delivery program

Product range

General switchboard accessories

Product function

Accessories panel building

Accessories

Terminations

Accessories

Terminals, 160 – 1000 A

Rated insulation voltage [U]

1000 V AC

Description

Including labels for terminal marking U, V, W - X, Y, Z - L1, L2, L3 - T1, T2, T3 - PE, N, PEN, □

Relationship of rated operational current → terminal capacity to IEC/EN 60439, VDE 0660 Part 500 or EN 50021

Outer terminal for round or sectoral conductor, other side for Cu strip

Rated operational current [I_e]

1000 A

Pole

4

Terminal capacity

Cu/Al cable

Cu

□ Round stranded

□ Sectoral stranded

○ Round solid

□ Sectoral solid

Al

○ Round solid

□ Sectoral solid

Cu/Al cable

2 x 150 - 300

3 x 50 - 240

Al cable
Al
 Sectoral solid
Al cable
2 x 150 - 240
3 x 150 - 185
Copper band
2 x (11 x 21 x 1)
10 x 40 x 1
10 x 50 x 1 mm
 copper strip
conductor
60 x 15
 Cu bar

Notes

Conversion kits for strip terminal in cable connection available separately
Terminal covers available separately

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Rail terminal bar (EC000275)
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system/ Rail terminal bar clamp (ecl@ss10.0.1-27-40-06-03 [ACC0369011])

Number of poles

4

Nominal current

1000 A

Connection type

Screwing

Mounting method

Screw

Number of connections total

8

Number of connections < 6 mm²

0

Number of connections 10 mm²

0

Number of connections 16 mm²

0

Number of connections 25 mm²

0

Number of connections > 25 mm²

8

Number of connections < AWG 6

0

Number of connections AWG 6

0

Number of connections AWG 4

0

Number of connections AWG 2

0

Number of connections AWG 4/0

0

Number of connections 250 kcmil

0

Number of connections > 250 kcmil

0

Contact safe

Yes

Height


196 mm

Width

334 mm

Depth


165 mm



430Z001

Line drawing
Terminals

3D drawing



430I069

Line drawing
Terminal

Product photo



4300PIC-292

Photo
Connection terminals

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH