

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Z-S24/SO - Impulse relay, 24AC/12DC, 1NO+1NC, 16A, 50Hz, 1SU



265539 Z-S24/SO

[Overview](#) [Specifications](#) [Resources](#)



265539 Z-S24/SO

Impulse relay, 24AC/12DC, 1NO+1NC, 16A, 50Hz, 1SU

EL-Nummer (Norway) 4133972

Impulse relay, control voltage 24V AC / 12V DC, function: 1 NO and 1 NC, rated operational current at 250V AC according to IEC/EN 60669-2-2: 16A, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5–10 mm² solid and flexible / 0.5–6 mm² flexible with ferrule

- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Dimensions

Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [I_n]

16 A

Heat dissipation per pole, current-dependent [P_{vd}]

1.5 W

Equipment heat dissipation, current-dependent [P_{vd}]

3 W

Operating ambient temperature min.

-20 °C

Operating ambient temperature max.

+45 °C

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Latching relay (EC000188)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Latching relay for distribution board (ecl@ss10.0.1-27-14-23-06 [AFZ818015])

Function

Mechanical switch

Mounting method


DIN rail

Width in number of modular spacings

1

Built-in depth

60 mm



1221166

Line drawing
Pushbutton

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH