



**Replacement coil, RA 250: 110 - 250 V 40-60 Hz/110 - 250 V DC, AC operation, For use with: DILM400, DILM500**

**Part no. DILM500-XSP/E(RA250)**  
**Catalog No. 208256**  
**Alternate Catalog No. XTCERENCOILMA**  
**EL-Nummer (Norway) 4134024**

### Delivery program

Actuating voltage		RA 250: 110 - 250 V 40-60 Hz/110 - 250 V DC
Voltage AC/DC		AC and DC operation
For use with		DILM400 DILM500

### Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-40
Operating ambient temperature max.	°C	60

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Coil for relay (EC001043)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Reel for contactor (ecl@ss10.0.1-27-37-10-12 [AKF021013])		
Rated control supply voltage Us at AC 50HZ	V	110 - 250
Rated control supply voltage Us at AC 60HZ	V	110 - 250
Rated control supply voltage Us at DC	V	110 - 250
Voltage type for actuating		AC/DC

### Approvals

Product Standards		IEC/EN 60947-4-1; UL 508; CSA-C22.2 No. 14-05; CE marking
UL File No.		E29096
UL Category Control No.		NLDX
CSA File No.		012528
CSA Class No.		3211-04
North America Certification		UL listed, CSA certified
Specially designed for North America		No