

BIMETAL OVERLOAD RELAYS

278463



Overview



Specifications



Resources

How to buy




Photo is representative




Photo is representative

278463

Eaton Moeller® series ZB Overload relay, ZB150, IP00
Direct mounting, IP00

How to buy




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216423

Eaton Moeller® series M22 Button plate, flat red, blank

239541

Eaton Moeller® series DILM Contactor, 380 V 400 V 45 kW, 2 N/O, 2 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals

239598

Eaton Moeller® series DILM Contactor, 380 V 400 V 75 kW, 2 N/O, 2 NC, RAC 240: 190 - 240 V 50/60 Hz, AC operation, Screw terminals

239577

Eaton Moeller® series DILM Contactor, 380 V 400 V 55 kW, 2 N/O, 2 NC, RAC 240: 110 - 120 V 50/60 Hz, AC operation, Screw terminals

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series ZB Thermal overload relay.**CATALOG NUMBER** 278463

Product specifications

>

MODEL CODE ZB150-70**EAN** 4015082784638**PRODUCT LENGTH/DEPTH** 134 mm**PRODUCT HEIGHT** 135 mm**PRODUCT WIDTH** 118 mm**PRODUCT WEIGHT** 1.208 kg

CERTIFICATIONS

UL File No.: E29184

UL

UL Category Control No.: NKCR

CE

CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA File No.: 012528

CSA Class No.: 3211-03

IEC/EN 60947-4-1

VDE 0660

UL 60947-4-1

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 70 A**TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)**2 x (0.75 - 2.5) mm², Control circuit cables1 x (4 - 70) mm², Main cables2 x (4 - 70) mm², Main cables1 x (0.75 - 2.5) mm², Control circuit cables**10.11 SHORT-CIRCUIT RATING**

Is the panel builder's responsibility. The specifications must be observed.

STRIPPING LENGTH (CONTROL CIRCUIT CABLE)

8 mm

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN

25 °C

10.4 CLEARANCES AND CREEPAGE DISTANCES

Meets the product standard's requirements.

10.12 ELECTROMAGNETIC COMPATIBILITY

Is the panel builder's responsibility. The specifications must be observed.

MOUNTING METHOD	Direct attachment Direct mounting
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
STRIPPING LENGTH (MAIN CABLE)	24 mm
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
RESET FUNCTION	Automatic Push-button
SHORT-CIRCUIT CURRENT RATING (BASIC RATING)	250 A, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA)
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
SCREW SIZE	M3.5, Terminal screw, Control circuit cables M10, Terminal screw, Main cables 5 mm AF, Hexagon socket-head spanner, Terminal
ADJUSTABLE CURRENT RANGE - MIN	50 A
PROTECTION	Finger and back-of-hand proof, Protection against direct contact, actuated from front (EN 50274)
TERMINAL CAPACITY (STRANDED)	2 x (16 - 70) mm ² , Main cables 1 x (16 - 70) mm ² , Main cables
AMBIENT OPERATING TEMPERATURE - MAX	55 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-1:2011, 102) Reset pushbutton manual/auto Trip-free release Test/off button
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
VOLTAGE RATING - MAX	600 VAC
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
SAFE ISOLATION	440 V AC, Between main circuits, According to EN 60439-1 240 V AC, Between auxiliary contacts, According to EN 60439-1

	440 V, Between auxiliary contacts and main contact 61140
RATED OPERATIONAL CURRENT (IE) AT AC-15, 220 V, 230 V, 240 V	1.5 A
CLASS	CLASS 10 A
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
RATED OPERATIONAL CURRENT (IE) AT AC-15, 380 V, 400 V, 415 V	0.9 A
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	7.2 W
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Accessories • Overload relay ZB up to 150 A
OVERLOAD RELEASE CURRENT SETTING - MIN	50 A
RATED OPERATIONAL CURRENT (IE) AT DC-13, 60 V	0.75 A
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	21.6 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Branch circuits, (UL/CSA)
TEMPERATURE COMPENSATION	Continuous ≤ 0.25 %/K, residual error for T > 40°
TERMINAL CAPACITY (SOLID)	1 x (0.75 - 4) mm ² , Control circuit cables 2 x (4 - 16) mm ² , Main cables 1 x (4 - 16) mm ² , Main cables 2 x (0.75 - 4) mm ² , Control circuit cables
NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	1
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
RATED OPERATIONAL CURRENT (IE) AT DC-13, 220 V, 230 V	0.2 A
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A

OVERLOAD RELEASE CURRENT SETTING - MAX	70 A
TERMINAL CAPACITY (SOLID/STRANDED AWG)	3/0, Main cables 2 x (18 - 14), Control circuit cables
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP00
OVERVOLTAGE CATEGORY	III
NUMBER OF AUXILIARY CONTACTS (CHANGE-OVER CONTACTS)	0
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V (auxiliary and control circuits) 8000 V AC
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
TIGHTENING TORQUE	10 Nm, Screw terminals, Main cables 1.2 Nm, Screw terminals, Control circuit cables
ADJUSTABLE CURRENT RANGE - MAX	70 A
FRAME SIZE	ZB150
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Control circuit cables, Schneider 2, Terminal screw, Control circuit cables, Pozidriv
RATED OPERATIONAL CURRENT (IE) AT AC-15, 120 V	1.5 A
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1
SHORT-CIRCUIT PROTECTION RATING	250 A gG/gL, Fuse, Type "1" coordination Max. 6 A gG/gL, fuse, Without welding, Auxiliary 160 A gG/gL, Fuse, Type "2" coordination
NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	1
RATED OPERATIONAL CURRENT (IE) AT DC-13, 110 V	0.4 A
RATED OPERATIONAL VOLTAGE (UE) - MAX	1000 V
SHOCK RESISTANCE	10 g, Mechanical, Sinusoidal, Shock duration 10 ms
RATED OPERATIONAL CURRENT (IE) AT DC-13, 24 V	0.9 A
SWITCHING CAPACITY (AUXILIARY CONTACTS, NORMALLY OPEN CONTACTS)	B300 at opposite polarity, AC operated (UL/CSA) R300, DC operated (UL/CSA)

Catalogs

Characteristic curve

Declarations of conformity

Drawings

eCAD model

Installation instructions

Manuals and user guides

mCAD model

Wiring diagrams

278463



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

