

SL4/SL7 SIGNAL TOWERS
171330


Overview


Specifications


Resources

Contact

171330

Eaton Moeller® series SL4 Continuous light modul

How to buy

Photo is representative

Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

171297

Eaton Moeller® series SL4 Base module;100-mm aluminum tube and foot

171303

Eaton Moeller® series SL4 Base module;for vertical mounting on one sides

171302

Eaton Moeller® series SL4 Base module;external fixing holes

171305

Eaton Moeller® series SL4 Base module;100 mm aluminum tube

[View more](#)[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

| | |
|---------------------|---|
| PRODUCT NAME | Eaton Moeller® series SL4 Continuous light modu |
|---------------------|---|

| | |
|-----------------------|--------|
| CATALOG NUMBER | 171330 |
|-----------------------|--------|

Product specifications

>

| | |
|-------------------|------------|
| MODEL CODE | SL4-L230-A |
|-------------------|------------|

| | |
|------------|---------------|
| EAN | 4015081678679 |
|------------|---------------|

| | |
|-----------------------------|-------|
| PRODUCT LENGTH/DEPTH | 43 mm |
|-----------------------------|-------|

| | |
|-----------------------|-------|
| PRODUCT HEIGHT | 75 mm |
|-----------------------|-------|

| | |
|----------------------|-------|
| PRODUCT WIDTH | 43 mm |
|----------------------|-------|

| | |
|-----------------------|----------|
| PRODUCT WEIGHT | 0.043 kg |
|-----------------------|----------|

CERTIFICATIONS

CSA-C22.2 No. 14-10
UL Category Control No.: NKCR
IEC/EN 60529
UL report applies to both US and Canada
Certified by UL for use in Canada
IEC/EN 60947-5-1
UL File No.: E29184
CSA Class No.: NKCR7
UL
UL 508
CE
CSA-C22.2 No. 94-91

PRODUCT SPECIFICATIONS

| | |
|-------------------------|------------------|
| PRODUCT CATEGORY | SL signal towers |
|-------------------------|------------------|

| | |
|------------------------|-------|
| ENCLOSURE COLOR | Black |
|------------------------|-------|

| | |
|------------------------|-------|
| RADIATION ANGLE | 360 ° |
|------------------------|-------|

| | |
|------------------------|---------|
| LEAKAGE CURRENT | 0.003 A |
|------------------------|---------|

| | |
|-------------------------|-------|
| OUTSIDE DIAMETER | 43 mm |
|-------------------------|-------|

| | |
|----------------------|-----|
| LIGHT MODULES | LED |
|----------------------|-----|

| | |
|---|-------|
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN | 230 V |
|---|-------|

| | |
|-------------------|------------------|
| LIGHT TYPE | Continuous light |
|-------------------|------------------|

| | |
|-----------------------------|-----------------|
| DEGREE OF PROTECTION | NEMA 13 IP66 |
|-----------------------------|-----------------|

| | |
|-----------------------------|-----|
| OVERVOLTAGE CATEGORY | III |
|-----------------------------|-----|

| | |
|--|---|
| RATED OPERATIONAL VOLTAGE(UE) AT DC - MIN | 0 V |
| RATED OPERATIONAL VOLTAGE(UE) AT DC - MAX | 0 V |
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
| RATED OPERATIONAL VOLTAGE(UE) AT AC - MAX | 240 V |
| POLLUTION DEGREE | 3 |
| CLIMATIC PROOFING | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| COLOR | Orange |
| RATED IMPULSE WITHSTAND VOLTAGE(UIMP) | 4000 V AC |
| CONNECTION TO SMARTWIRE-DT | No |
| FUNCTIONS | Continuous light |
| MATERIAL | Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC) |
| LAMP TYPE | LED |
| LIFESPAN, ELECTRICAL | 100,000 h |
| AMBIENT OPERATING TEMPERATURE - MIN | -30 °C |
| TYPE | Continuous light module |
| MOUNTING POSITION | As required |
| CURRENT CONSUMPTION | 0.03 A, at 230/240 V AC |
| SHOCK RESISTANCE | 15 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| VOLTAGE TYPE | AC |
| NUMBER OF MODULES | Max. 5 (with standard base) Max. 10 (with base for mounting on both sides) |
| RATED INSULATION VOLTAGE (UI) | 250 V |

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model



[Contact me](#)

171330

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

