

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

M30-F14 - Surface mounting enclosure, Insulated material, With high-grade steel screws, Number of locations 4, 4 x 30.5



197238 M30-F14

[Overview](#) [Specifications](#) [Resources](#)



197238 M30-F14

Surface mounting enclosure, Insulated material, With high-grade steel screws, Number of locations 4, 4 x 30.5

EL-Nummer (Norway) 4300438

Surface mounting enclosure, Housing: Insulated material, With high-grade steel screws, Number of locations: 4, Cable entry: rear: 1 x M20, lateral: 2 x M20 (1 x each side), Colour RAL Value: RAL 7035, Colour: Enclosure base anthracite, Connection to SmartWire-DT: no, For use with: 4 x 30.5, For use with: (Illuminated) pushbuttons, (Illuminated) selector switches, Key-operated pushbuttons, Indicator light, EMERGENCY STOP/EMERGENCY OFF buttons with yellow set of adapter rings M22Y-R30, Flat rear contacts M22-FK..., Flat Rear LED elements M22-FLED-...

- [Delivery program](#)
- [Technical data](#)

Delivery program

Basic function accessories
Surface mounting enclosure

- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals
- Dimensions

Housing
 Insulated material
 With high-grade steel screws
 Number of locations
 4 Qty.
 Cable entry knockouts
 Cable entry
 rear: 1 x M20
 lateral: 2 x M20 (1 x each side)
 Degree of Protection
 IP66, IP67, IP69
 Impact resistance
 IK06 according to EN 50102
 Colour



RAL Value
 RAL 7035
 Colour
 Enclosure base anthracite
 Connection to SmartWire-DT
 no
 For use with
 4 x □ 30.5
 For use with
 (Illuminated) pushbuttons
 (Illuminated) selector switches
 Key-operated pushbuttons
 Indicator light
 EMERGENCY STOP/EMERGENCY OFF buttons with yellow set of adapter rings M22Y-R30
 Flat rear contacts M22-FK...
 Flat Rear LED elements M22-FLED-...

Technical data

General
 Degree of Protection
 IP66, IP67, IP69
 Ambient temperature Open
 -25 - +70 °C

Design verification as per IEC/EN 61439

Operating ambient temperature min.
 -25 °C
 Operating ambient temperature max.
 +70 °C
 Impact resistance
 IK06 according to EN 50102

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)
 Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss10.0.1-27-37-12-05 [AKF023014])
 Number of command positions
 4
 Construction type housing
 Surface mounting housing
 Material housing
 Plastic
 Material quality housing
 Other
 Diameter openings
 30 mm
 Colour housing cover
 Grey

Degree of protection (IP)
IP67/IP69K
Degree of protection (NEMA)
Other
Width
43 mm
Height
301 mm
Depth
44 mm

Approvals

Product Standards
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.
E29184
UL Category Control No.
NKCR
CSA File No.
012528
CSA Class No.
3211-03
North America Certification
UL listed, CSA certified
Degree of Protection
UL/CSA Type 1, 3R, 4X

Dimensions

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-m30_fi4](#)
File
(Web)

edz files

- [DA-CE-ETN.M30-F4](#)
File
(Web)

Step files

- [DA-CS-m30_fi4](#)
File
(Web)

Product photo



[M30-F4_C](#)
Photo




3D drawing



Dimensions single product

- [1160DIM-200](#)
Line drawing
- [1160DIM-203](#)
Line drawing

Symbol

- 
[000Z083](#)
Logo
totally insulated (en, de, fr, es, it, zh, ru, nl, sv, cs, pl, tr)

- 
[116C062](#)
Graphic
Button plate, grey

Instruction Leaflet

- [RMQ-Titan: Flat enclosure \(IL047023ZU\)](#)
Asset
(PDF, 07/2018, multilingual)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

