

RMQ TITAN MODULAR PILOT DEVICES
121462



Overview





Specifications



Resources




How to



121462

Eaton Moeller® series M22 Emergency stop/emerg
pushbutton, RMQ-Titan, Palm-tree shape, 45 mm, M
release function, Red, yellow, RAL 3000

Contact me about this product



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

216380

Eaton Moeller® series M22 Contact element, Screw terminals, Base 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC10

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series M22 Emergency stop/emergency stop pushbutton

Product specifications

>

CATALOG NUMBER 121462

MODEL CODE M22-PVT45P

EAN 4015081192823

PRODUCT LENGTH/DEPTH 67 mm

PRODUCT HEIGHT 45 mm

PRODUCT WIDTH 45 mm

PRODUCT WEIGHT 0.043 kg

CERTIFICATIONS

IEC/EN 60947
VDE 0660
DNV
GL
LR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 0 A

10.11 SHORT-CIRCUIT RATING Is the panel builder's responsibility. The specifications must be observed.

OPENING DIAMETER 22.5 mm

RAL-NUMBER 3000

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements

	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
DESIGN	Palm-tree shaped Classical
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FRONT ELEMENT TYPE	High
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ILLUMINATION	Non-illuminated
SUPPLY VOLTAGE LAMP	0 V
ACTUATING FORCE	50 N
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Other
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
COLOR	Red
FEATURES	Tamper-proof (according to ISO 13850, EN 418)
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
BASE COLOR	Yellow
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	As required
ACTUATOR FUNCTION	Switching function latching Turn-to-release
BUTTON COLOR	Red
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to

10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
ACTUATOR DIAMETER	45 mm
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
OPERATING FREQUENCY	600 Operations/h
PRODUCT CATEGORY	RMQ-Titan
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
DIAMETER CAP	45 mm
SUITABLE FOR	Emergency stop
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	100,000 Operations
BEZEL MATERIAL	Other
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP67/IP69K NEMA 4X
ACTUATOR COLOR	Red
OPENING HEIGHT	0 mm
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
LENS TYPE	Round
TYPE	Controlled stop pushbutton/emergency-stop button
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
UNLOCKING METHOD	Tum-release
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 50 g, Mechanical, According to IEC/EN 60068-2-27

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

System overview

121462



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

