

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



M22-FLED-RG - LED element, Flat Rear, red/green, front mounting



180799 M22-FLED-RG

[Overview](#) [Specifications](#) [Resources](#)



180799 M22-FLED-RG

LED element, Flat Rear, red/green, front mounting

Alternate Catalog No.

M22-FLED-RG

EL-Nummer (Norway)

4315750

LED element, Fixing: Front fixing, Connection technique: Cage Clamp, Description: Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany, Rated operational voltage: $U_e = 24$ V DC V, Rated operational current: $I_e = 10 - 15$ mA, Power consumption: $P_{max} = 0.36$ W, at 24 V, Colour: Red/green, Degree of Protection: IP20, Connection to SmartWire-DT: no, Standards: IEC 60947-5-1

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals
- Dimensions

Delivery program

Basic function accessories

LED elements

Description

Cage Clamp is a registered trademark of Wago Kontakttechnik GmbH/Minden, Germany

Connection technique

Cage Clamp, Push-in

Fixing

Front fixing

Rated operational voltage [U_e]

24 V DC V

Rated operational current [I_e]

10 - 15 mA

Power consumption [P_{max}]

0.36 W

Lifespan to EN 60064 at $t_a = +25$ °C [t_{mean} (AC)]

100000 h

Degree of Protection

IP20

at 24 V

Colour

Red/green



Connection to SmartWire-DT

no
Approval



Connection technique
Cage Clamp, Push-in

Notes

For indicator lights, illuminated pushbutton actuators, and illuminated selector switch actuators, the following applies:
Only in combination with M22-...-W

Terminal diagram

| | Colors | Pin | | | |
|--------------|-----------|-----|----|------|----|
| | | X1 | X2 | X3 | X4 |
| | | +R | +G | BGND | |
| M22-FLED-RG | red | x | | | x |
| | green | | x | | x |
| | yellow | x | x | | x |
| M22-FLED-RGB | red | x | | | x |
| | green | | x | | x |
| | yellow | x | x | | x |
| | White | x | x | x | x |
| | blue | | | x | x |
| | Violet | x | | x | x |
| | Turquoise | | x | x | x |

Technical data

General

Standards

IEC 60947-5-1

Degree of Protection

IP20

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Dry heat to IEC 60068-2-2

Ambient temperatureOpen

-25 - +70 °C

Ambient temperatureStorage

- 40 - + 85 °C

Mounting position

As required

Mechanical shock resistance according to IEC 60068-2-27

Shock duration 11 ms, half-sinusoidal

> 50 g

Terminal capacitiesSolid

1 x 1 (0.2 - 1.5)

1 x 1 (0.75 - 1.5) Can be plugged without tools mm²

Terminal capacitiesStranded

1 x 1 (0.2 - 1.5) mm²

Terminal capacitiesFlexible with ferrule

1 x 1 (0.25 - 1)

Use WAGO Variocrimp 4 crimping tool; please enquire for others mm²

Terminal capacitiesSolid or stranded

20 AWG

Contacts

Rated impulse withstand voltage [U_{imp}]

4000 V AC

Rated insulation voltage [U_i]

250 V

Overvoltage category/pollution degree

III/3

Indoor and protected outdoor installation

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Lamp holder block for control circuit devices (EC000204)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Bulb socket block for command and alarm devices (ecl@ss10.0.1-27-37-12-09 [AKF027014])

Transformer integrated

No

With integrated voltage decreasing resistor

No

With light source

Yes

With integrated diode

Yes

Lamp holder

None

Rated voltage Ue at AC 50 Hz

0 - 0 V

Rated voltage Ue at AC 60 Hz

0 - 0 V

Rated voltage Ue at DC

24 - 24 V

Voltage type for actuating

DC

Lamp type

LED

Connection type auxiliary circuit

Spring clamp connection

Colour lamp

Other

Type of fastening

Front fastening

Approvals

Product Standards

IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking

UL File No.

E29184

UL Category Control No.

NKCR

CSA File No.

012528

CSA Class No.

3211-03


North America Certification

UL listed, CSA certified

Degree of Protection

UL/CSA Type: -

Dimensions



CAD data

- [Product-specific CAD data \(Web\)](#)
- [3D Preview](#)

(Web)

DWG files

- [DA-CD-m22_fled_rg](#)
File
(Web)

edz files

- [DA-CE-ETN.M22-FLED-RG](#)
File
(Web)

Step files

- [DA-CS-m22_fled_rg](#)
File
(Web)

Product photo



• [1160PIC-1835](#)

Photo

LED contact element, flat rear

Symbol



• [1160SFC-87](#)

Graphic

Color combination, red/green


3D drawing



• [1160DRW-365](#)

Line drawing

Dimensions single product



• [1160DIM-121](#)

Line drawing

LED contact element, flat rear

Instruction Leaflet

- [RMQ-Titan System \(IL04716002Z\)](#)
Asset
former AWA1160-1745, IL04716001E
(PDF, 09/2020, multilingual)

Standards

- [000Z330](#)
Logo
LED logo



- [116Z024](#)
Logo
LED logo

Declaration of Conformity

EU

- [Emergency-stop operating devices RMQ Titan & accessories M22-..., M30-... \(DA-DC-00003622\)](#)
Asset
(PDF)
- [RMQ Titan \(Operating and signalling devices\) M22.../M30.../C22.../C30... \(DA-DC-00003657\)](#)
Asset
(PDF)

UK

- [RMQ Titan \(Operating and signalling devices\) M22.../M30.../C22.../C30... \(DA-DC-00003960\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH