

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)

- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)

- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)

- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)

- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)

- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)

- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)

- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



PKZ motor protection circuit breaker
072732

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Download](#) [Zoom](#)





Photo is representative

[Download](#) [Zoom](#)

Photo is representative

[Previous](#) [Next](#)

[Download](#) [Zoom](#)

- 
- 
- 
- 

[Previous](#) [Next](#)

072732

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker, 0.09 kW, 0.25 - 0.4 A, Screw terminals

[Add a free sample to the cart](#) [How to buy](#)

- [Learn about our Push-in terminals](#)
- [Configure Motor Start Combination](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

[Keep My Cart](#)

[Create a New Cart](#)

×



Item is already in the cart.

Okay

Photo is representative

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [082882](#)
082882
Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals
- [072896](#)
072896
Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals
- [032720](#)
032720
Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0
- [219654](#)
219654
Eaton Moeller® series CI-K Insulated enclosure, for PKZ0, 160 x 100 x 130 mm, +rotary handle, black/grey
- [072894](#)
072894
Eaton Moeller® series NHI Standard auxiliary contact, 2N/O+1N/C, screw connection
- [101452](#)
101452
Eaton Moeller® series BBA Busbar adapter, 45 mm, 32 A, DIN rail: 2 BBA0-32
- [073138](#)
073138
Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 400 V 50 Hz, Screw terminals
- [073135](#)
073135
Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 230 V 50 Hz, Screw terminals
- [101451](#)

101451

Eaton Moeller® series BBA Busbar adapter, 45 mm, 25 A, DIN rail: 1 BBA0-25

- [219655](#)

219655

Eaton Moeller® series CI-K Insulated enclosure, for PKZ0, +rotary handle, red/yellow CI-K2-PKZ0-GR

- [063961](#)

063961

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 2, 90 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [106133](#)

106133

Eaton Moeller® series PKZ0 Door coupling handle, suitable for emergency stop

- [082884](#)

082884

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, Can be fitted to the front, Screw terminals

- [063960](#)

063960

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 4, 180 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [232289](#)

232289

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 3, 135 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [232290](#)

232290

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 5, 225 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [101481](#)

101481

Eaton Moeller® series BBA Busbar adapter, 45 mm, 25 A, DIN rail: 2

- [262518](#)

262518

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0-E

- [082881](#)

082881

Eaton Moeller® series PKZ0 Current limiter, 3p, 63A, 400VAC/100kA, 690VAC/10kA

- [106132](#)

106132

Eaton Moeller® series PKZ0 Door coupling handle, EN60204

[Go to Previous Item](#)

[Go to Next Item](#)

- [082882](#)

082882

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

- [072896](#)

072896

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals

- [032720](#)

032720

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0

- [219654](#)

219654

Eaton Moeller® series CI-K Insulated enclosure, for PKZ0, 160 x 100 x 130 mm, +rotary handle, black/grey

- [072894](#)

072894

Eaton Moeller® series NHI Standard auxiliary contact, 2N/O+1N/C, screw connection

- [101452](#)

101452

Eaton Moeller® series BBA Busbar adapter, 45 mm, 32 A, DIN rail: 2 BBA0-32

- [073138](#)

073138

Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 400 V 50 Hz, Screw terminals

- [073135](#)

073135

Eaton Moeller® series U-PKZ0 Undervoltage release PKZ0(4), PKE, AC, 230 V 50 Hz, Screw terminals

- [101451](#)

101451

Eaton Moeller® series BBA Busbar adapter, 45 mm, 25 A, DIN rail: 1 BBA0-25

- [219655](#)

219655

Eaton Moeller® series CI-K Insulated enclosure, for PKZ0, +rotary handle, red/yellow CI-K2-PKZ0-GR

- [063961](#)

063961

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 2, 90 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [106133](#)

106133

Eaton Moeller® series PKZ0 Door coupling handle, suitable for emergency stop

- [082884](#)

082884

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, Can be fitted to the front, Screw terminals

- [063960](#)

063960

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 4, 180 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [232289](#)

232289

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 3, 135 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [232290](#)

232290

Eaton Moeller® series B3 Three-phase busbar link, Circuit-breaker: 5, 225 mm, For PKZM0-... or PKE12, PKE32 without side mounted auxiliary contacts or voltage releases

- [101481](#)

101481

Eaton Moeller® series BBA Busbar adapter, 45 mm, 25 A, DIN rail: 2

- [262518](#)

262518

Eaton Moeller® series PKZ Extension terminal, 3p, 25mm² BK25/3-PKZ0-E

- [082881](#)

082881

Eaton Moeller® series PKZ0 Current limiter, 3p, 63A, 400VAC/100kA, 690VAC/10kA

- [106132](#)

106132

Eaton Moeller® series PKZ0 Door coupling handle, EN60204

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

General specifications

Product Name

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker

Catalog Number

072732

Model Code

PKZM0-0,4

EAN

4015080727323

Product Length/Depth

76 mm

Product Height

93 mm

Product Width

45 mm

Product Weight

0.243 kg

Certifications

CE

IEC/EN 60947

CSA

UL

CSA Class No.: 3211-05

IEC/EN 60947-4-1

UL File No.: E36332

CSA File No.: 165628

VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL Category Control No.: NLRV

Product specifications

Rated operational current for specified heat dissipation (In)

0.4 A

Terminal capacity (flexible with ferrule)

2 x (1 - 6) mm², ferrule to DIN 46228

1 x (1 - 6) mm², ferrule to DIN 46228

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Ambient operating temperature (enclosed) - min

25 °C

Rated operational power at AC-3, 380/400 V, 50 Hz

0.09 kW

Short-circuit current rating (type E)

50 kA, 600 Y/347 V, SCCR (UL/CSA)

65 kA, 240 V, SCCR (UL/CSA)

Accessories required BK25/3-PKZ0-E

65 kA, 480 Y/277 V, SCCR (UL/CSA)

Rated short-circuit breaking capacity Ics at 440 V AC

150 kA

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Switching capacity

0.4 A, AC-3 up to 690 V

0.4 A (3 contacts in series), DC-5 up to 250V

Stripping length (main cable)

10 mm

Ambient operating temperature (enclosed) - max

40 °C

Rated short-circuit breaking capacity Icu at 400 V AC

150 kA

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Adjustment range undelayed short-circuit release - max

6.2 A

10.8 Connections for external conductors

Is the panel builder's responsibility.

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Actuator type

Turn button

Rated operational power at AC-3, 440 V, 50 Hz

0.12 kW

Ambient operating temperature - max

55 °C

Rated operational power at AC-3, 220/230 V, 50 Hz

0.06 kW

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Device construction

Built-in device fixed built-in technique

Features

Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)

Lifespan, electrical

100,000 operations

Static heat dissipation, non-current-dependent Pvs

0 W

Electrical connection type of main circuit

Screw connection

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Number of poles

Three-pole

Rated short-circuit breaking capacity Icu at 690 V AC

150 kA

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Mounting position
Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.

Rated uninterrupted current (I_u)
0.4 A

Tripping characteristic
Overload trigger: tripping class 10 A

Short-circuit release
6.2 A, I_{rm}, Setting range max.
± 20% tolerance, Trip blocks

Basic device fixed 15.5 x I_u, Trip Blocks

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.3 Degree of protection of assemblies
Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent P_{vid}
1.74 W

Operating frequency
40 Operations/h

Product category
Motor protective circuit breaker

Short-circuit current rating (group protection)
50 kA, 600 V High Fault, Fuse, SCCR (UL/CSA)
600 A, 600 V High Fault, max. Fuse, SCCR (UL/CSA)
600 A, 600 V High Fault, max. CB, SCCR (UL/CSA)
50 kA, 600 V High Fault, CB, SCCR (UL/CSA)

Overload release current setting - min
0.25 A

Rated operational power at AC-3, 690 V, 50 Hz
0.18 kW

Rated short-circuit breaking capacity I_{cs} at 400 V AC
150 kA

Rated short-circuit breaking capacity I_{cu} at 440 V AC
150 kA

Equipment heat dissipation, current-dependent P_{vid}
5.22 W

Heat dissipation capacity P_{diss}
0 W

Rated operational current (I_e)
0.4 A

Suitable for
Also motors with efficiency class IE3

Branch circuit: Manual type E if used with terminal, or suitable for group installations, (UL/CSA)

Internal resistance
10500 mΩ

Temperature compensation
≤ 0.25 %/K, residual error for T > 40°
-5 - 40 °C to IEC/EN 60947, VDE 0660
-25 - 55 °C, Operating range

Terminal capacity (solid)
2 x (1 - 6) mm²
1 x (1 - 6) mm²

Rated frequency - min
50 Hz

Short-circuit current
60 kA DC, up to 250 VDC, Main conducting paths

Power loss
5.22 W

10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects
Meets the product standard's requirements.

Lifespan, mechanical

100,000 Operations

Terminal capacity (solid/stranded AWG)

18 - 10

Overload release current setting - max

0.4 A

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Rated short-circuit breaking capacity Ics at 500 V AC

150 kA

Overvoltage category

III

Degree of protection

IP20

Terminals: IP00

Rated frequency - max

60 Hz

Switch off technique

Thermomagnetic

Ambient storage temperature - max

80 °C

Adjustment range undelayed short-circuit release - min

6.2 A

Pollution degree

3

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Rated impulse withstand voltage (Uimp)

6000 V AC

Connection

Screw terminals

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

Phase failure sensitive

Motor protection

Tightening torque

1.7 Nm, Screw terminals, Main cable

1 Nm, Screw terminals, Control circuit cables

Rated short-circuit breaking capacity Icu at 500 V AC

150 kA

Rated operational voltage (Ue) - min

690 V

Explosion safety category for dust

ATEX dust-ex-protection, PTB 10, ATEX 3013, Ex II(2) GD

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Rated short-circuit breaking capacity Ics at 690 V AC

150 kA

Rated operational power at AC-3, 500 V, 50 Hz

0.12 kW

Shock resistance

25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Rated operational voltage (Ue) - max

690 V

Altitude

Max. 2000 m

Serial Number Verified :

Authenticated: 

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Brochures

- [Save time and space thanks to the new link module PKZM0-XDM32ME](#)
- [Motor Starters in System xStart - brochure](#)

Download all files

Catalogs

- [Switching and protecting motors - catalog](#)
- [Product Range Catalog Switching and protecting motors](#)

Characteristic curve

- [eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)
- [eaton-manual-motor-starters-characteristic-characteristic-curve-009.eps](#)
- [eaton-manual-motor-starters-characteristic-characteristic-curve-003.eps](#)

Download all files

Declarations of conformity

- [DA-DC-00004921.pdf](#)
- [DA-DC-00004892.pdf](#)

Drawings

- [eaton-manual-motor-starters-pkz-dimensions.eps](#)
- [eaton-manual-motor-starters-pkzm0-dimensions-003.eps](#)
- [eaton-manual-motor-starters-pkz-dimensions-002.eps](#)
- [eaton-general-ie-ready-dilm-contactor-standards.eps](#)
- [eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps](#)
- [eaton-manual-motor-starters-pkzm0-3d-drawing-004.eps](#)
- [eaton-manual-motor-starters-mounting-3d-drawing-002.eps](#)

Download all files

eCAD model

- [DA-CE-ETN.PKZM0-0,4](#)

Installation instructions

- [IL03407011Z](#)
- [IL03402034Z](#)

Download all files

Installation videos

- [WIN-WIN with push-in technology](#)

Manuals and user guides

- [IL122023ZU](#)
- [eaton-motor-protective-circuit-breaker-pkzm0-overload-monitoring-exe-manual-mm03402003z-de-de-en-us.pdf](#)

Download all files

mCAD model

- [DA-CD-pkzm0](#)

- [DA-CS-pkzm0](#)

Download all files

Wiring diagrams

- [eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps](#)
- [eaton-manual-motor-starters-starter-nzm-mccb-wiring-diagram.eps](#)

Download all files

[Export product specification](#)

-

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 072732

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)
- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

Back to top of the page

Are you sure?

Cancel Sign out

Are you sure?

Cancel Sign out

x

x