



073187
A-PKZ0(230V50HZ)

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM7.0

Approvals

Characteristics

Dimensions

DELIVERY PROGRAM

Product range
Accessories

Accessories
Shunt release

Actuating voltage
230 V 50 Hz

Voltage type
Standard voltage

Current actuation
AC

Contact sequence



Connection technique
Screw terminals

For use with
Shunt release FKZO(4), FKE

For use with
FKZM0
FKZM4
FKZM0-T
FKM0
FKZM01
FKE

Notes

Can be fitted to the left of:
Motor protective circuit-breaker
Cannot be combined with:
U-FKZO undervoltage release

TECHNICAL DATA

General

Terminal capacities
Solid or flexible conductor, with ferrule
1 x (0,75 - 2,5)
2 x (0,75 - 2,5) mm²

Terminal capacities
Solid or stranded
1 x (18 - 14)
2 x (18 - 14) AWG

Actuating voltage
230 V 50 Hz

Operating range

Alternating voltage
0.7- 1.1 x U_S

Power consumption

AC
Pull-in power [Pick-up]
5 VA

AC
Sealing power [Sealing]
3 VA

DESIGN VERIFICATION AS PER IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat
dissipation [I_n]
0 A

Heat dissipation per pole, current-dependent [P_{vid}]
0 W

Equipment heat dissipation, current-dependent
[P_{vid}]
0 W

Static heat dissipation, non-current-dependent [P_{vs}]
0.5 W

Heat dissipation capacity [P_{diss}]
0 W

Operating ambient temperature min.
-25 °C

Operating ambient temperature max.
+55 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts
10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts
10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts
10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties
10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)

Rated control supply voltage U_s at AC 50-HZ
230 - 230 V

Rated control supply voltage U_s at AC 60-HZ
0 - 0 V

Rated control supply voltage U_s at DC
0 - 0 V

Voltage type for actuating
AC

Initial value of the undelayed short-circuit release -
setting range
0 A

End value adjustment range undelayed short-
circuit release
0 A

Type of electric connection
Screw connection

Number of contacts as normally open contact
0

Number of contacts as normally closed contact
0

Number of contacts as change-over contact
0

Suitable for power circuit breaker
No

Suitable for off-load switch
No

Suitable for motor safety switch
Yes

Suitable for overload relay
No

APPROVALS

Product Standards
UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE
marking

UL File No.
E36332

UL Category Control No.
NLRV


CSA File No.
165628

CSA Class No.
3211-05

North America Certification
UL listed, CSA certified

Specially designed for North America
No

CHARACTERISTICS



Accessories
1: Motor-protective circuit-breakers

DIMENSIONS

