


RMQ TITAN MODULAR PILOT DEVICES
216881


Overview


Specifications


Resources

How to



216881

Eaton Moeller® series M22 Key-operated actuator
Key withdrawable: 0, Bezel: titanium

[Contact me about this product](#)

Photo is representative




Photo is representative




Photo is representative




Photo is representative




Photo is representative



Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

216374

Eaton Moeller® series M22 Mounting clamp

216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series M22 Key-operated actuator

CATALOG NUMBER 216881

Product specifications

>

MODEL CODE M22-WS

EAN 4015082168810

PRODUCT LENGTH/DEPTH 70 mm

PRODUCT HEIGHT 30 mm

PRODUCT WIDTH 30 mm

PRODUCT WEIGHT 0.034 kg

COMPLIANCES CE Marked

CERTIFICATIONS

EN 60947-5
 CSA Std. C22.2 No. 14-05
 UL 508
 CSA Std. C22.2 No. 94-91
 IEC 60947-5
 VDE
 VDE 0660
 CSA
 CSA-C22.2 No. 94-91
 CSA File No.: 012528
 IEC/EN 60947
 UL File No.: E29184
 CSA Class No.: 3211-03
 CSA-C22.2 No. 14-05
 CE
 IEC/EN 60947-5

UL
 UL Category Control No.: NKCR
 DNV
 GL
 LR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
OPENING DIAMETER	22.5 mm
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
OPERATING TORQUE	0.5 Nm
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
DESIGN	Key operated Classical
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FITTED WITH:	Front ring
DEGREE OF PROTECTION (FRONT SIDE)	IP66
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ACTUATOR TYPE	Key
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Titanium
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
INDICATOR COLOR	Other
CONNECTION TO SMARTWIRE-DT	Yes With SWD-RMQ connections
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	As required
ACTUATOR FUNCTION	Spring-return Key withdrawable in position 0 Momentary
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
OPERATING FREQUENCY	100 Operations/h
PRODUCT CATEGORY	RMQ-Titan
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
ACCESSORIES	1 key included with supplied equipment.
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	100,000 Operations
BEZEL MATERIAL	Plastic
SWITCHING ANGLE	40 °
NUMBER OF SWITCH POSITIONS	2
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	NEMA 4X, 13
ACTUATOR COLOR	Black
OPENING HEIGHT	0 mm
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.

FUNCTIONS	Stay-put/spring-return function, can be changed with XC-Y
SIZE	Front diameter: 29.7 mm
LENS TYPE	Round
TYPE	Key-operated button
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

Specifications and datasheets

System overview



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.