



RMQ TITAN MODULAR PILOT DEVICES
216772



Overview





Specifications



Resources

How to






216772

Eaton Moeller® series M22 Indicator light, RMQ-T

Contact me about this product





Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216374

Eaton Moeller® series M22 Mounting clamp

216535

Eaton Moeller® series M22 Surface mounting enclosure, 1 mounting location

216559

Eaton Moeller® series M22 LED element, green, front mount, 12-30VAC/DC

216558

Eaton Moeller® series M22 LED red, front mount, 12-30VAC/DC

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series M22 Indicator light

CATALOG NUMBER 216772

Product specifications

>

MODEL CODE M22-L-R

EAN 4015082167721

PRODUCT LENGTH/DEPTH 30 mm

PRODUCT HEIGHT 30 mm

PRODUCT WIDTH 30 mm

PRODUCT WEIGHT 0.007 kg

COMPLIANCES CE Marked

CERTIFICATIONS

IEC 60947-5
UL 508
EN 60947-5
CSA Std. C22.2 No. 94-91
CSA Std. C22.2 No. 14-05
VDE
CSA File No.: 012528
IEC/EN 60947-5
VDE 0660
UL
UL File No.: E29184
CSA Class No.: 3211-03
IEC/EN 60947
UL Category Control No.: NKCR
CSA-C22.2 No. 14-05
CSA-C22.2 No. 94-91
CE
CSA

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
OPENING DIAMETER	22.5 mm
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
DESIGN	Flush
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FITTED WITH:	Front ring
DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
LENS COLOR	Red
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Chrome
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
CONNECTION TO SMARTWIRE-DT	Yes With SWD-RMQ connections
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be tested.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be tested.
MOUNTING POSITION	As required
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the installation instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be tested.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
PRODUCT CATEGORY	RMQ-Titan
TERMINAL CAPACITY	0.5 - 1.5 mm ² , stranded 0.5 - 1.5 mm ² , solid
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
BEZEL MATERIAL	Other
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	NEMA 4X, 13
OPENING HEIGHT	22.5 mm
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	4000 V AC
10.10 TEMPERATURE RISE	Not applicable.
SIZE	Front diameter: 29.7 mm
LENS TYPE	Round Flat
TYPE	Indicator lights
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SUITABLE FOR NUMBER OF BUILT-IN SIGNAL LIGHTS	1
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms
RATED INSULATION VOLTAGE (UI)	250 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

System overview

216772



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

