


RMQ TITAN MODULAR PILOT DEVICES
216931


Overview


Specifications


Resources

 How to



216931

Eaton Moeller® series M22 Illuminated pushbutton
Flush, momentary, Blue, Blank, Bezel: titanium

[Contact me about this product](#)

Photo is representative

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

216374

Eaton Moeller® series M22 Mounting clamp

216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME Eaton Moeller® series M22 Illuminated pushbutton

Product specifications

>

CATALOG NUMBER 216931

MODEL CODE M22-DL-B

EAN 4015082169312

PRODUCT LENGTH/DEPTH 30 mm

PRODUCT HEIGHT 30 mm

PRODUCT WIDTH 30 mm

PRODUCT WEIGHT 0.01 kg

COMPLIANCES CE Marked

CERTIFICATIONS

CSA Std. C22.2 No. 94-91
IEC 60947-5
CSA Std. C22.2 No. 14-05
UL 508
EN 60947-5
VDE
UL Category Control No.: NKCR
CSA Class No.: 3211-03
CSA-C22.2 No. 94-91
IEC/EN 60947
IEC/EN 60947-5
CSA-C22.2 No. 14-05
UL File No.: E29184
UL
CE
VDE 0660
CSA
CSA File No.: 012528
DNV
GL
LR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 0 A

10.11 SHORT-CIRCUIT RATING Is the panel builder's responsibility. The specification must be observed.

OPENING DIAMETER 22.5 mm

10.4 CLEARANCES AND CREEPAGE DISTANCES Meets the product standard's requirements.

10.12 ELECTROMAGNETIC COMPATIBILITY Is the panel builder's responsibility. The specification must be observed.

10.2.5 LIFTING Does not apply, since the entire switchgear needs to

FINISH Flush

DESIGN	Classical
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FRONT ELEMENT TYPE	Flat
FITTED WITH:	Front ring
INSCRIPTION	Blank
DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K NEMA 4X
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ACTUATING FORCE	5 N
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Titanium
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	With SWD-RMQ connections Yes
NUMBER OF COMMAND POSITIONS	1
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	As required
ACTUATOR FUNCTION	Momentary Spring-return
BUTTON COLOR	Blue
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the inf instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

OPERATING FREQUENCY	3600 Operations/h
PRODUCT CATEGORY	RMQ-Titan
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Illumination
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	5,000,000 Operations
BEZEL MATERIAL	Plastic
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	IP66 NEMA 4X NEMA 12 NEMA 13 IP67 NEMA 3R IP69K
ACTUATOR COLOR	Blue
OPENING HEIGHT	0 mm
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
SIZE	Front dimensions: 22 x 22 mm
LENS TYPE	Round
TYPE	Illuminated pushbutton actuator
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

System overview

216931



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

