


RMQ TITAN MODULAR PILOT DEVICES
216562


Overview


Specifications


Resources

How to



216562

Eaton Moeller® series M22 LED element, green, ba

[Contact me about this product](#)

Photo is representative

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216778

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Extended, conical, white

216782

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Extended, conical, Blue

216779

Eaton Moeller® series M22 Indicator light, RMQ-Titan, Extended, conical, Red

216780

Eaton Moeller® series M22 Indi RMQ-Titan, Extended, conical,

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications	>	PRODUCT NAME	Eaton Moeller® series M22 Accessory LED
		CATALOG NUMBER	216562
Product specifications	>	MODEL CODE	M22-LEDC-G
		EAN	4015082165628
		PRODUCT LENGTH/DEPTH	38 mm
		PRODUCT HEIGHT	10 mm
		PRODUCT WIDTH	37 mm
		PRODUCT WEIGHT	0.011 kg
		COMPLIANCES	CE Marked
		CERTIFICATIONS	CSA Std. C22.2 No. 14-05 UL 508 CSA Std. C22.2 No. 94-91 EN 60947-5 IEC 60947-5 VDE CSA-C22.2 No. 94-91 CSA File No.: 012528 IEC 60947-5-1 UL File No.: E29184 CSA-C22.2 No. 14-05 CE CSA UL CSA Class No.: 3211-03 IEC/EN 60947-5 UL Category Control No.: NKCR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT (IE) - MAX	14 mA
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
LAMP HOLDER	None
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
OPERATING TORQUE	0.8 Nm
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.

AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
FITTED WITH:	Diode Light source
RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	12 V
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
TERMINAL CAPACITY (STRANDED)	0.5 - 2.5 mm ²
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0.45 W
LIFESPAN, ELECTRICAL	100,000 h (at 25°C, according to EN60064)
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
FASTENING TYPE	Floor fastening
MOUNTING POSITION	As required
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
VOLTAGE TYPE	AC/DC
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
CONNECTION TYPE (AUXILIARY CIRCUIT)	Screw connection
TERMINAL CAPACITY (SOLID)	0.75 - 2.5 mm ²
POWER CONSUMPTION	Max. 0.26 W

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
CONNECTION TYPE	Base fixing
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
RATED OPERATIONAL VOLTAGE (UE) AT DC - MIN	12 V
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	IP20
LIGHT COLOR	Green
RATED OPERATIONAL VOLTAGE (UE) AT DC - MAX	30 V
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	30 V
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature Eaton will provide heat dissipation data for the device
LAMP TYPE	LED
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
RATED OPERATIONAL CURRENT (IE) - MIN	5 mA
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms
RATED INSULATION VOLTAGE (UI)	500 V

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

System overview

216562



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

