

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



M22-XC-R - Coding part



216406 M22-XC-R

[Overview](#) [Specifications](#) [Resources](#)



216406 M22-XC-R

Coding part

Alternate Catalog No.

M22-XC-RQ

EL-Nummer (Norway)

4355420

Coded partial set for converting between maintained and spring-return function and key withdraw with key-operated button of the RQM system 22.3 mm

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Approvals

Delivery program

Accessories

Coding kit

Basic function accessories

Coding kit

Function

For changing the key withdraw

Function



Not for key-operated button for master key systems

Connection to SmartWire-DT

no

For use with

All selector switch actuators

All key-operated actuators

Technical data

General

Ambient temperature Open

-25 - +70 °C

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]

0 A

Heat dissipation per pole, current-dependent [P_{rd}]

0 W

Equipment heat dissipation, current-dependent [P_{rd}]

0 W
 Static heat dissipation, non-current-dependent [P_{vs}]
 0 W
 Heat dissipation capacity [P_{diss}]
 0 W
 Operating ambient temperature min.
 -25 °C
 Operating ambient temperature max.
 +70 °C
 IEC/EN 61439 design verification
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
 Meets the product standard's requirements.
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
 Please enquire
 10.2 Strength of materials and parts 10.2.5 Lifting
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.6 Mechanical impact
 Does not apply, since the entire switchgear needs to be evaluated.
 10.2 Strength of materials and parts 10.2.7 Inscriptions
 Meets the product standard's requirements.
 10.3 Degree of protection of ASSEMBLIES
 Does not apply, since the entire switchgear needs to be evaluated.
 10.4 Clearances and creepage distances
 Meets the product standard's requirements.
 10.5 Protection against electric shock
 Does not apply, since the entire switchgear needs to be evaluated.
 10.6 Incorporation of switching devices and components
 Does not apply, since the entire switchgear needs to be evaluated.
 10.7 Internal electrical circuits and connections
 Is the panel builder's responsibility.
 10.8 Connections for external conductors
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.2 Power-frequency electric strength
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.3 Impulse withstand voltage
 Is the panel builder's responsibility.
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
 Is the panel builder's responsibility.
 10.10 Temperature rise
 Not applicable.
 10.11 Short-circuit rating
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.12 Electromagnetic compatibility
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.
 10.13 Mechanical function
 The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)

Type of electrical accessory

Other

Type of mechanical accessory

Other

Approvals

North America Certification

UL/CSA certification not required

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)


DWG files

- [DA-CD-anschlag_rot_grun](#)
File
(Web)

Step files

- [DA-CS-anschlag_rot_grun](#)
File
(Web)

3D drawing



116J011

Line drawing

Coding adapter green/red

Product photo




116A223

Photo

Coding adapters

Symbol



000Z363

Graphic

Set of coding adapters

Instruction Leaflet

- [RMQ-Titan System \(IL04716002Z\)](#)
Asset
former AWA1160-1745, IL04716001E
(PDF, 09/2020, multilingual)

Declaration of Conformity

EU

- [RMQ Titan \(Operating and signalling devices\) M22.../M30.../C22.../C30...](#) (DA-DC-00003657)
Asset
(PDF)

UK

- [RMQ Titan \(Operating and signalling devices\) M22.../M30.../C22.../C30...](#) (DA-DC-00003960)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH