


**RMQ TITAN MODULAR PILOT DEVICES**  
**216407**

  
Overview

  
Specifications

  
Resources

How to



**216407**

Eaton Moeller® series M22 Coding part M22-XC-Y

[Contact me about this product](#)

**GENERAL SPECIFICATIONS**

General specifications >

**PRODUCT NAME** Eaton Moeller® series M22 Accessory Coding kit

**CATALOG NUMBER** 216407

Product specifications >

**MODEL CODE** M22-XC-Y

**EAN** 4015082164072

**PRODUCT LENGTH/DEPTH** 19 mm

**PRODUCT HEIGHT** 16 mm

**PRODUCT WIDTH** 11 mm

**PRODUCT WEIGHT** 0.002 kg

**CERTIFICATIONS** UL/CSA certification not required

**CATALOG NOTES** Not for key-operated button for master key systems

## PRODUCT SPECIFICATIONS

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>ACCESSORY/SPARE PART TYPE</b>	Accessory
<b>MECHANICAL ACCESSORY TYPE</b>	Other
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be lifted.
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>ELECTRICAL ACCESSORY TYPE</b>	Other
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>COLOR</b>	Yellow
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>FUNCTIONS</b>	For converting between stay-put and spring-return functions.
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.

<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the instruction leaflet (IL) is observed.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W

Brochures

---

Catalogs

---

Certification reports

---

Drawings

---

Installation instructions

---

Installation videos

---

mCAD model

---

System overview

---



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.