Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



M22-A4 - Mounting clamp, 4 mounting locations



279437 M22-A4

Overview Specifications Resources



279437 M22-A4

Mounting clamp, 4 mounting locations

Mounting clamp with four installation points for contact and LED elements from the M22 RMQ range of products. The normal M22-A adapter has three points only. The fourth adapter is required, for example, for 4-actuator buttons and 4 joysticks, as well as for cases when four contacts need to be connected in series.

- Delivery program
- Technical data

Design verification as per IEC/EN 61439

- Technical data ETIM 7.0
- Approvals
- Dimensions

Delivery program

Basic function accessories

Mounting adaptor

Function

Mounting clamp (front mounting) for 4-contact L⊞ elements

Fixing

Front fixing

Connection to SmartWire-DT

nc

For use with

Contact elements M22-(C)K

M22-WR4, -D4, -WJ..., -WRJ...

Configuration

1 4 2 3

Technical data

General
Climatic proofing
Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30
Ambient temperatureOpen
-25 - +70 °C

Technical data for design verification

Rated operational current for specified heat dissipation [l_n]

0 A

Heat dissipation per pole, current-dependent [P_{id}]

0 W

Equipment heat dissipation, current-dependent [Pid]

0 W

Static heat dissipation, non-current-dependent [P_{vs}]

0 W

Heat dissipation capacity [Pdiss]

0 W

Operating ambient temperature min.

-25°C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEVBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse with stand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Adapter for control circuit devices (EC001020)

Bectric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Adapter for command devices (ecl@ss10.0.1-27-37-12-26 [AKF044014])

Built-in diameter

22 mm

Number of appliances to build in

4

Approvals

Product Standards

IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking

UL File No.

E29184

UL Category Control No.

NKCR

CSA File No.

012528

CSA Class No.

3211-03

North America Certification

UL listed, CSA certified

Dimensions





mounting clamp

Fixing adapter (front mount) for 4

CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)


DWG files

DA-CD-adapter_4_fach File (Web)

Step files

DA-CS-adapter_4_fach File (Web)


3D drawing



Line drawing

Fixing adapter, front, 4 contact elements

Dimensions single product



Fixing adapter

Symbol

• 1 4 2 3

1160SPC-14

Graphic

Fixing adapter assignment

Product photo



Instruction Leaflet

RMQ-Titan System (IL04716002Z)
 Asset
 former AWA1160-1745, IL04716001E
 (PDF, 09/2020, multilingual)

Declaration of Conformity

EU

- E-stop operating devices RMQ Titan & acc. M22/M30(S)-PV(LT)30... (DA-DC-00003323)
 Asset (PDF)
- Emergency-stop operating devices RWQ Titan & accessories M22-..., M30-... (DA-DC-00003622)
 Asset (PDF)
- RMQ Titan (Operating and signalling devices) M22.../M30.../C22.../C30... (DA-DC-00003657) Asset (PDF)

UK

RWQ Titan (Operating and signalling devices) W22.../W30.../C22.../C30... (DA-DC-00003960)
 Asset
 (PDF)

Download-Center

- Download-Center (this item)
 Eaton EVEA Download-Center download data for this item
- Download-Center
 Eaton EMEA Download-Center

Generate data sheet in PDF format

Generate data sheet in Excel format

Imprint Privacy Policy Legal Disclaimer Terms and Conditions

© 2021 by Eaton Industries GmbH