

RMQ TITAN MODULAR PILOT DEVICES
216638


Overview


Specifications


Resources

 How to




Photo is representative

216638

Eaton Moeller® series M22 Pushbutton, RMQ-Titanium
White, Blank, Bezel: titanium

[Contact me about this product](#)

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

216374

Eaton Moeller® series M22 Mounting clamp

216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series M22 Pushbutton
---------------------	--------------------------------------

Product specifications

>

CATALOG NUMBER	216638
-----------------------	--------

MODEL CODE	M22-DH-W
-------------------	----------

EAN	4015082166380
------------	---------------

PRODUCT LENGTH/DEPTH	30 mm
-----------------------------	-------

PRODUCT HEIGHT	35 mm
-----------------------	-------

PRODUCT WIDTH	30 mm
----------------------	-------

PRODUCT WEIGHT	0.012 kg
-----------------------	----------

CERTIFICATIONS

CSA
UL
IEC/EN 60947-5
VDE 0660
CSA Class No.: 3211-03
UL 508
CSA File No.: 012528
CSA-C22.2 No. 94-91
UL File No.: E29184
CE
CSA-C22.2 No. 14-05
IEC/EN 60947
UL Category Control No.: NKCR
DNV
GL
LR

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
--	-----

10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
-----------------------------------	---

OPENING DIAMETER	22.5 mm
-------------------------	---------

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
---	--

10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
--	---

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
-----------------------	---

DESIGN	Extended Classical
---------------	-----------------------

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
---	--

AMBIENT STORAGE TEMPERATURE - MIN	40 °C
--	-------

FRONT ELEMENT TYPE	High
FITTED WITH:	Front ring
INSCRIPTION	Blank
DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K NEMA 4X
FORCE FOR POSITIVE OPENING - MIN	0 N
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ACTUATING FORCE	5 N
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Chrome
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
CONNECTION TO SMARTWIRE-DT	Yes With SWD-RMQ connections
NUMBER OF COMMAND POSITIONS	1
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	As required
ACTUATOR FUNCTION	Momentary Spring-return
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
OPERATING FREQUENCY	3600 Operations/h
PRODUCT CATEGORY	RMQ-Titan
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W

HEAT DISSIPATION CAPACITY PDISS	0 W
WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	5,000,000 Operations
BEZEL MATERIAL	Plastic
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	NEMA 3R NEMA 4X IP66 NEMA 12 NEMA 13 IP67 IP69K
ACTUATOR COLOR	White
OPENING HEIGHT	0 mm
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
SIZE	Front dimensions: 22 x 22 mm
LENS TYPE	Round
TYPE	Pushbutton actuator
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27

Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

Installation videos

mCAD model

Specifications and datasheets

System overview

216638



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

