

RMQ TITAN MODULAR PILOT DEVICES  
216681

  
Overview

  
Specifications

  
Resources

How to




Photo is representative




Photo is representative

# 216681

Eaton Moeller® series M22 Pushbutton, RMQ-Titanium  
White, inscribed, Bezel: titanium

[Contact me about this product](#)

## Designed to work together

Discover other Eaton products and accessories built to enhance this product.

### 216376

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K10

### 216374

Eaton Moeller® series M22 Mounting clamp

### 216378

Eaton Moeller® series M22 Contact element, Screw terminals, Front fixing, 1 NC, 24 V 3 A, 220 V 230 V 240 V 6 A M22-K01

### 216384

Eaton Moeller® series M22 Contact element, Cage Clamp, Front fixing, 24 V 3 A, 220 V 230 V 240 V 6 A

[View more](#)[View less](#)

## GENERAL SPECIFICATIONS

General specifications

>

**PRODUCT NAME**

Eaton Moeller® series M22 Pushbutton

**CATALOG NUMBER**

216681

Product specifications

>

**MODEL CODE**

M22-DRH-W-X1

**EAN**

4015082166816

**PRODUCT LENGTH/DEPTH**

30 mm

**PRODUCT HEIGHT**

35 mm

**PRODUCT WIDTH**

30 mm

**PRODUCT WEIGHT**

0.013 kg

## CERTIFICATIONS

CSA Class No.: 3211-03

IEC/EN 60947-5

IEC/EN 60947

CSA-C22.2 No. 14-05

CSA-C22.2 No. 94-91

UL

UL File No.: E29184

VDE 0660

CSA

UL 508

CE

CSA File No.: 012528

UL Category Control No.: NKCR

DNV

GL

LR

## PRODUCT SPECIFICATIONS

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>OPENING DIAMETER</b>	22.5 mm
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be lifted.
<b>DESIGN</b>	Extended Classical
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>AMBIENT STORAGE TEMPERATURE - MIN</b>	-40 °C
<b>FRONT ELEMENT TYPE</b>	High
<b>FITTED WITH:</b>	Front ring
<b>INSCRIPTION</b>	Inscribed
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP67/IP69K NEMA 4X
<b>FORCE FOR POSITIVE OPENING - MIN</b>	0 N
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>ACTUATING FORCE</b>	5 N
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	70 °C
<b>BEZEL COLOR</b>	Chrome
<b>CLIMATIC PROOFING</b>	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>FEATURES</b>	Labelled
<b>CONNECTION TO SMARTWIRE-DT</b>	Yes With SWD-RMQ connections
<b>NUMBER OF COMMAND POSITIONS</b>	1
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be lifted.

<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to
<b>MOUNTING POSITION</b>	As required
<b>ACTUATOR FUNCTION</b>	Maintained Switching function latching
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the inf instruction leaflet (IL) is observed.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>OPERATING FREQUENCY</b>	1800 Operations/h
<b>PRODUCT CATEGORY</b>	RMQ-Titan
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>WIDTH OPENING</b>	0 mm
<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>LIFESPAN, MECHANICAL</b>	1,000,000 Operations (AC operated)
<b>BEZEL MATERIAL</b>	Plastic
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>DEGREE OF PROTECTION</b>	NEMA 13 IP69K IP66 IP67 NEMA 3R NEMA 12 NEMA 4X
<b>ACTUATOR COLOR</b>	White
<b>OPENING HEIGHT</b>	0 mm
<b>AMBIENT STORAGE TEMPERATURE - MAX</b>	80 °C
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>FUNCTIONS</b>	Stay-put/spring-return function can be changed on d

<b>SIZE</b>	Front dimensions: 22 x 22 mm
<b>LENS TYPE</b>	Round
<b>TYPE</b>	Pushbutton actuator
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>SHOCK RESISTANCE</b>	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms

Brochures

---

Catalogs

---

Certification reports

---

Drawings

---

eCAD model

---

Installation instructions

---

Installation videos

---

mCAD model

---

System overview

---

216681



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.