



216933  
M22-DL-X

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Dimensions

## DELIVERY PROGRAM

Product range  
RMQ-Titan

Basic function  
Illuminated pushbutton actuators

Mounting hole diameter [□]  
22.5 mm

Single unit/Complete unit  
Single unit

Design  
Flush

momentary

### Button plate

button plate

Without button plate

Degree of Protection  
IP66, IP67, IP69

Front ring  
Bezel: titanium

Connection to SmartWire-DT  
yes  
with SWD-RMQ connections

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947  
VDE 0660

Lifespan, mechanical [Operations]  
> 5 x 10<sup>6</sup>

Operating frequency [Operations/h]  
 3600

Actuating force  
 5 n

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Degree of Protection  
IP66, IP67, IP69

Ambient temperature  
Open  
-25 - +70 °C

Mounting position  
As required

Mechanical shock resistance  
30  
Shock duration 11 ms  
Sinusoidal  
according to IEC 60068-2-27 g

shipping classification  
DNV  
GL  
LR



## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
0 A

Heat dissipation per pole, current-dependent [ $P_{vid}$ ]  
0 W

Equipment heat dissipation, current-dependent  
[ $P_{vid}$ ]  
0 W

Static heat dissipation, non-current-dependent [ $P_{vs}$ ]  
0 W

Heat dissipation capacity [ $P_{diss}$ ]  
0 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+70 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Please enquire

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

# TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Front element for push button (EC0000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])

Colour button  
Without button plate

Number of command positions  
1

Construction type lens  
Round

Hole diameter  
22.5 mm

Width opening  
0 mm

Height opening  
0 mm

Type of button  
Flat

Suitable for illumination  
Yes

With protective cover  
No

Labelled  
No

Switching function latching  
No

Spring-return  
Yes

With front ring  
Yes

Material front ring  
Plastic

Colour front ring  
Chrome

Degree of protection (IP), front side  
IP67/IP69K

Degree of protection (NEMA), front side  
4X

## APPROVALS

Product Standards  
IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05;  
CSA-C22.2 No. 94-91; CE marking

UL File No.  
E29184

UL Category Control No.  
NKCR

CSA File No.  
012528

CSA Class No.  
3211-03

North America Certification  
UL listed, CSA certified

Degree of Protection  
UL/CSA Type 3R, 4X, 12, 13

# DIMENSIONS

