



RMQ TITAN MODULAR PILOT DEVICES
208689



Overview





Specifications



Resources

How to





208689

Eaton Moeller® series M22 Indicator light, red

Contact me about this product





Designed to work together

Discover other Eaton products and accessories built to enhance this product.



229753

Eaton Moeller® series FAK Enclosure base,
black

[View more](#)

[View less](#)

GENERAL SPECIFICATIONS

General specifications

>

PRODUCT NAME	Eaton Moeller® series M22 Indicator light
CATALOG NUMBER	208689
MODEL CODE	L-R
EAN	4015082086893
PRODUCT LENGTH/DEPTH	30 mm
PRODUCT HEIGHT	30 mm
PRODUCT WIDTH	60 mm
PRODUCT WEIGHT	0.035 kg
CERTIFICATIONS	Request filed for UL and CSA

Product specifications

>

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
PRODUCT CATEGORY	Accessories
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
OPENING DIAMETER	22.5 mm
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be lifted.
DESIGN	Conical
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FITTED WITH:	Front ring
WIDTH OPENING	0 mm
DEGREE OF PROTECTION (FRONT SIDE)	IP67/IP69K
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT	Meets the product standard's requirements.

HEAT/FIRE BY INTERNAL ELECT. EFFECTS	
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
BEZEL MATERIAL	Plastic
LENS COLOR	Red
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
DEGREE OF PROTECTION	NEMA 4X, 13
OPENING HEIGHT	22.5 mm
AMBIENT OPERATING TEMPERATURE - MAX	70 °C
BEZEL COLOR	Other
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
CONNECTION TO SMARTWIRE-DT	No
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
LENS TYPE	Round High
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
SUITABLE FOR NUMBER OF BUILT-IN SIGNAL LIGHTS	1
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
SHOCK RESISTANCE	30 g, Mechanical, According to IEC/EN 60068-2-27 11 ms, 3 Impacts
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

System overview

208689



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

