


RMQ TITAN MODULAR PILOT DEVICES
226161


Overview


Specifications


Resources

How to



226161

Eaton Moeller® series M22 Telescopic adapters

[Contact me about this product](#)

GENERAL SPECIFICATIONS

General specifications >

PRODUCT NAME Eaton Moeller® series M22 Accessory Telescopic c

CATALOG NUMBER 226161

Product specifications >

MODEL CODE M22-TA

EAN 4015082261610

PRODUCT LENGTH/DEPTH 80 mm

PRODUCT HEIGHT 40 mm

PRODUCT WIDTH 45 mm

PRODUCT WEIGHT 0.043 kg

COMPLIANCES CE Marked

CSA Std. C22.2 No. 94-91
EN 60947-5

CSA Std. C22.2 No. 14-05
 IEC 60947-5
 UL 508
 VDE
 UL
 CE
 CSA Class No.: 3211-03
 UL Category Control No.: NKCR
 CSA-C22.2 No. 14-05
 CSA File No.: 012528
 CSA-C22.2 No. 94-91
 IEC/EN 60947-5
 CSA
 UL File No.: E29184

CERTIFICATIONS

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
PRODUCT CATEGORY	<ul style="list-style-type: none"> • Accessories • Compact PLCs • Control relay easyRelay
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specification must be observed.
ACCESSORY/SPARE PART TYPE	Accessory
MECHANICAL ACCESSORY TYPE	Other
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specification must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FITTED WITH:	35 mm top-hat rail (according to IEC/EN 60715)
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
ELECTRICAL ACCESSORY TYPE	Other

AMBIENT OPERATING TEMPERATURE - MAX	70 °C
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
CONNECTION TO SMARTWIRE-DT	No
FUNCTIONS	For equalization of the mounting depth of rear mounted enclosures, and in cabinets with mounting depths of 100 mm. For mounting of EASY, FAZ, PKZ, DIL etc. weight
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be
USED WITH	PKE EC4P easy200/500/700/800 PKZM0 MFD-CP8
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instructions in the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W

Brochures

Catalogs

Certification reports

Drawings

Installation instructions

Installation videos

mCAD model

System overview

226161



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.