

[United States](#) [Select your location](#)

[Sign in](#)

We make what matters work*

[Products](#) [Digital Services](#) [Markets](#) [Support](#) [Company](#)

Search

[Products](#)

- [Actuators and motion control](#)
- [Backup power, UPS, surge & IT power distribution](#)
- [Clutches and brakes](#)
- [Conduit, cable & wire management](#)
- [Cylinders](#)
- [Differentials](#)
- [Ducting solutions](#)
- [Electrical circuit protection](#)
- [Electric vehicles and EV charging](#)
- [Electronic components](#)

- [Enclosures](#)
- [Energy storage systems](#)
- [Engine solutions](#)
- [Filtration solutions](#)
- [Fuel systems, emissions and components](#)
- [Furniture](#)
- [Golf grips](#)
- [Hose, tubing, fittings and connectors](#)
- [Hydraulic motors and generators](#)

- [Hydraulic power packs and accumulators](#)
- [Industrial controls, drives, automation and sensors](#)
- [Life support systems](#)
- [Lighting and controls](#)
- [Low-voltage power distribution & control systems](#)
- [Medium-voltage power distribution & control systems](#)
- [Plastics](#)
- [Process safety, automation, test and measurement](#)
- [Pumps](#)

- [Residential](#)
- [Safety, security & emergency communications](#)
- [Server racks, enclosures & airflow management](#)
- [Support systems](#)
- [Transmissions](#)
- [Utility & grid solutions](#)
- [Valves](#)
- [Wiring devices & connectivity](#)

[Digital](#)

- [Brightlayer Experience Hub](#)
- [Explore our digital catalog](#)
- [Discover Brightlayer](#)
- [Understanding Industry 4.0](#)

- [For developers](#)

[Services](#)

Close Search

[Markets](#)

Close Search

- [Aerospace](#)
- [Buildings](#)
- [Data centers](#)
- [Eaton Experience Centers](#)
- [Food and beverage](#)
- [Government and military](#)
- [Healthcare](#)
- [Machine building](#)

- [Marine](#)
- [Mining, metals and minerals](#)
- [Oil and gas](#)
- [Rail](#)
- [Renewables](#)
- [Residential](#)
- [Utilities](#)

- [Vehicles](#)

[Support](#)

Close Search

- [Contact technical support](#)
- [Download center](#)
- [How to buy](#)
- [Terms and conditions](#)
- [Tools](#)
- [Training and education](#)
- [Warranty and returns](#)

[Company](#)

Close Search

- [Overview](#)
- [About us](#)
- [News & insights](#)
- [Careers](#)
- [Investor relations](#)
- [Research & development](#)

- [Corporate governance](#)
- [Sustainability](#)
- [Inclusion & diversity](#)
- [Ethics & compliance](#)
- [Partnering with Eaton](#)

- [Selling to Eaton](#)

[MyEaton](#)

Close Search

Quick links



RMQ Titan modular pilot devices
266137

[Overview](#) [Specifications](#) [Resources](#)

How to buy

[Back to search](#)

[Download](#) [Zoom](#)

Download [Zoom](#)

266137

Eaton Moeller® series M22 Mounting clamp, RMQ-Titan

[Add a free sample to the cart](#) [Contact me about this product](#)

×



Products cannot be sold together

Products in your cart cannot be sold together in one transaction. Please choose to either keep your existing cart, or create a new cart with this product.

You can purchase your products in separate transactions.

Keep My Cart

Create a New Cart

×



Item is already in the cart.

Okay

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

- [266122](#)

266122

Eaton Moeller® series LSE Safety position switch, LSE, Position switch with electronically adjustable operating point, Basic device, expandable, 2 NC, Yellow, Insulated material, Cage Clamp, -25 - +70 °C

- [266121](#)

266121

Eaton Moeller® series LSE Safety position switch, LSE, Position switch with electronically adjustable operating point, Basic device, expandable, 1 N/O, 1 NC, Yellow, Insulated material, Cage Clamp, -25 - +70 °C

- [266122](#)

266122

Eaton Moeller® series LSE Safety position switch, LSE, Position switch with electronically adjustable operating point, Basic device, expandable, 2 NC, Yellow, Insulated material, Cage Clamp, -25 - +70 °C

- [266121](#)

266121

Eaton Moeller® series LSE Safety position switch, LSE, Position switch with electronically adjustable operating point, Basic device, expandable, 1 N/O, 1 NC, Yellow, Insulated material, Cage Clamp, -25 - +70 °C

[View more](#) [View less](#)

- [General specifications](#)
- [Product specifications](#)

General specifications

Product Name

Eaton Moeller® series M22 Accessory Mounting clamp

Catalog Number

266137

Model Code

M22-LS

EAN

4015082661373

Product Length/Depth

30 mm

Product Height

27 mm

Product Width

37 mm

Product Weight

0.006 kg

Certifications

UL/CSA certification not required

Product specifications

Rated operational current for specified heat dissipation (In)

0 A

Product category

Accessories

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdis

0 W

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Force for positive opening - min

0 N

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Degree of protection

None

Ambient operating temperature - max

70 °C

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Number of appliances to build in

1

Built-in diameter

22 mm

Features

Actuation through front element RMQ-Titan®

10.10 Temperature rise

Not applicable.

Connection to SmartWire-DT

No

Static heat dissipation, non-current-dependent Pvs

0 W

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Enclosure material

Insulated material

Ambient operating temperature - min

-25 °C

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.7 Inscriptions

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Heat dissipation per pole, current-dependent Pvid

0 W

Serial Number Verified :

Authenticated: ✓

The product is verified as being authentic; however, this does not guarantee the condition or fit for purpose of the product.

Brochures

- [RMQ Titan - brochure](#)
- [RMQ Small E-Stop - Flyer](#)
- [RMQ Titan emergency stop push button - Flyer](#)
- [RMQ Flat Enclosure - Flyer](#)
- [RMQ MCI - Flyer](#)

Download all files

Catalogs

- [Flip catalog - Product Range Catalog - Command and indication](#)
- [Product Range Catalog Command and Indication Control Circuit Devices, Signal Towers](#)

Certification reports

- [DA-DC-00004135.pdf](#)
- [DA-DC-00004157.pdf](#)

Drawings

- [eaton-position-switches-adapter-m22-mounting-clamp-3d-drawing.eps](#)

Installation instructions

- [IL04716002Z](#)

Installation videos

- [RMQ Flat Design](#)

mCAD model

- [adapter_ls](#)
- [adapter_ls.stp](#)

Download all files

System overview

- [Pilot devices - selection aid](#)

Export product specification

•

x



Enter your city, state, or zip code or [Locate me](#)

City, state

Search

Show locations that offer:

- Product pickup
- Order online and ship product

- 266137

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

Company

- [About us](#)
- [Careers](#)
- [Inclusion and Diversity](#)
- [Investor relations](#)
- [Sustainability](#)
- [News and insights](#)
- [Slavery and human trafficking statement](#)

Quick links

- [Sign in](#)
- [Support](#)

- [Policies and statements](#)
- [Terms and conditions](#)
- [Responsible sourcing of conflict minerals](#)
- [Subscribe to emails](#)

Let's talk big ideas

-
-
-
-

[View all social media](#)

- [Sitemap](#)
- [Privacy, cookies & data protection policy](#)
- [Do not sell my data request \(CCPA and other states\)](#)

© 2023 Eaton. All Rights Reserved.

[Back to top of the page](#)

Are you sure?

[Cancel](#) [Sign out](#)

Are you sure?

[Cancel](#) [Sign out](#)

[×](#)

[×](#)