


**RMQ16 MODULAR PILOT DEVICES**  
**086299**

  
Overview

  
Specifications

  
Resources

**How to buy**



**086299**

Eaton Moeller® series RMQ16 Pushbutton, red 0, 1

**How to buy**

[Configure pilot devices online](#)

**Designed to work together**

Discover other Eaton products and accessories built to enhance this product.

**090351**

Eaton Moeller® series E10 Accessory Contact element, 1 N/O, Front fastening, Blade terminal

**090401**

Eaton Moeller® series E01 Contact element, 1 N/C, front mount, screw connection

**046299**

Eaton Moeller® series RMQ16 Surface mounting enclosure, 8 mounting locations

**036976**

Eaton Moeller® series RMQ16 plug, black, IP65\_x Q25BS

[View more](#)

[View less](#)

**GENERAL SPECIFICATIONS**

General specifications	>	<b>PRODUCT NAME</b>	Eaton Moeller® series RMQ16 Pushbutton
		<b>CATALOG NUMBER</b>	086299
Product specifications	>	<b>MODEL CODE</b>	Q18D-10
		<b>EAN</b>	4015080862994
		<b>PRODUCT LENGTH/DEPTH</b>	50 mm
		<b>PRODUCT HEIGHT</b>	18 mm
		<b>PRODUCT WIDTH</b>	18 mm
		<b>PRODUCT WEIGHT</b>	0.007 kg
		<b>CERTIFICATIONS</b>	CSA-C22.2 No. 14-05 IEC/EN 60947 CSA File No.: 46552 VDE 0660 UL 508 CE CSA Class No.: 3211-03 IEC/EN 60947-5 UL CSA UL Category Control No.: NKCR UL File No.: E29184

## PRODUCT SPECIFICATIONS

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	25 °C
<b>OPENING DIAMETER</b>	16 mm
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications must be observed.
<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>DESIGN</b>	Flat
<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
<b>FRONT ELEMENT TYPE</b>	Flat
<b>FITTED WITH:</b>	Front ring


<b>INSCRIPTION</b>	Inscribed
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP65 NEMA 1
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>ACTUATING FORCE</b>	4 N
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>BEZEL COLOR</b>	Black
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>FEATURES</b>	Labelled
<b>CONNECTION TO SMARTWIRE-DT</b>	No
<b>NUMBER OF COMMAND POSITIONS</b>	1
<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to
<b>MOUNTING POSITION</b>	As required
<b>ACTUATOR FUNCTION</b>	Spring-return Momentary
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the instruction leaflet (IL) is observed.
<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to
<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
<b>OPERATING FREQUENCY</b>	3600 Operations/h
<b>PRODUCT CATEGORY</b>	RMQ16
<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
<b>WIDTH OPENING</b>	0 mm

<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
<b>LIFESPAN, MECHANICAL</b>	3,000,000 Operations
<b>BEZEL MATERIAL</b>	Plastic
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>DEGREE OF PROTECTION</b>	IP65 NEMA 1
<b>ACTUATOR COLOR</b>	Red
<b>OPENING HEIGHT</b>	0 mm
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>SIZE</b>	Front dimensions: 18 x 18 mm
<b>LENS TYPE</b>	Square
<b>TYPE</b>	Pushbutton actuator
<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
<b>SHOCK RESISTANCE</b>	Mechanical, According to IEC/EN 60068-2-27 40 g, Mechanical, According to IEC/EN 60068-2-27 11 ms




## Configurator

RMQ pushbuttons & pilot devices



## Machine operation

The human-machine interface of tomorrow



## Label Editor

Download certificate  
"Labeleditor"

Brochures

Catalogs

Certification reports

Drawings

---

eCAD model

---

Installation instructions

---

mCAD model

---

086299



Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.