


RMQ16 MODULAR PILOT DEVICES
089202


Overview


Specifications


Resources

How to buy



089202

Eaton Moeller® series RMQ16 Illuminated pushbutton
momentary Q18LT-WS

How to buy

[Configure pilot devices online](#)

Designed to work together

Discover other Eaton products and accessories built to enhance this product.

090351

Eaton Moeller® series E10 Accessory
Contact element, 1 N/O, Front fastening,
Blade terminal

090401

Eaton Moeller® series E01 Contact element,
1 N/C, front mount, screw connection

208728

Eaton Moeller® series RMQ16 LED,
W2x4.6d, 18-30VDC, 7-12.5mA, white

046299

Eaton Moeller® series RMQ16
mounting enclosure, 8 mounting

View more

View less

GENERAL SPECIFICATIONS


General specifications	>	PRODUCT NAME	Eaton Moeller® series RMQ16 Illuminated pushbutton
		CATALOG NUMBER	089202
Product specifications	>	MODEL CODE	Q18LT-WS
		EAN	4015080892021
		PRODUCT LENGTH/DEPTH	59 mm
		PRODUCT HEIGHT	18 mm
		PRODUCT WIDTH	18 mm
		PRODUCT WEIGHT	0.009 kg
		CERTIFICATIONS	CE IEC/EN 60947 CSA File No.: 46552 UL CSA Class No.: 3211-03 UL 508 UL File No.: E29184 IEC/EN 60947-5 CSA UL Category Control No.: NKCR CSA-C22.2 No. 14-05

PRODUCT SPECIFICATIONS

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications must be observed.
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
OPENING DIAMETER	16 mm
TERMINAL SIZE	2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-c
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications must be observed.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
DESIGN	Flat
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
FRONT ELEMENT TYPE	Flat

FITTED WITH:	Front ring LED W2x4, 6d, max. 30 V, 1 W
INSCRIPTION	Blank
DEGREE OF PROTECTION (FRONT SIDE)	NEMA 1 IP65
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
ACTUATING FORCE	4 N
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
BEZEL COLOR	Black
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
CONNECTION TO SMARTWIRE-DT	No
NUMBER OF COMMAND POSITIONS	1
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to
MOUNTING POSITION	As required
ACTUATOR FUNCTION	Spring-return Momentary
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the instruction leaflet (IL) is observed.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
OPERATING FREQUENCY	3600 Operations/h
PRODUCT CATEGORY	RMQ16
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
SUITABLE FOR	Illumination

WIDTH OPENING	0 mm
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
LIFESPAN, MECHANICAL	3,000,000 Operations
BEZEL MATERIAL	Plastic
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
CONTROL CIRCUIT RELIABILITY	1 failure per 10,000,000 switching operations (Statistical, 24 V DC/5 mA) 1 failure per 5,000,000 switching operations (statistical, 5 V DC/1 mA)
OVERVOLTAGE CATEGORY	III
DEGREE OF PROTECTION	IP65 NEMA 1
ACTUATOR COLOR	White
OPENING HEIGHT	0 mm
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	24 V
POLLUTION DEGREE	3
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	800 V AC
10.10 TEMPERATURE RISE	Not applicable.
SIZE	Front dimensions: 18 x 18 mm
LENS TYPE	Square
TYPE	Illuminated pushbutton actuator
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
SHOCK RESISTANCE	40 g, Mechanical, According to IEC/EN 60068-2-27 11 ms Mechanical, According to IEC/EN 60068-2-27
RATED INSULATION VOLTAGE (UI)	250 V



Brochures

Catalogs

Certification reports

Drawings

eCAD model

Installation instructions

mCAD model

089202

Eaton is an intelligent power management company dedicated to improving the quality of life and protecting the environment for people everywhere. We are guided by our commitment to do business right, to operate sustainably and to help our customers manage power — today and well into the future. By capitalizing on the global growth trends of electrification and digitalization, we're accelerating the planet's transition to renewable energy and helping to solve the world's most urgent power management challenges.

