Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norw egian Bokmål

Worldwide English



L-PKZ0(400V) - Indicator light, white, 400V neon lamp

082152 L-PKZ0(400V) Overview Specifications Resources



082152 L-PKZ0(400V)

Indicator light, white, 400V neon lamp

Alternate Catalog No. EL-Nummer (Norway) XTPAXILWN 4357218

Indicator light with neon bulb can be used for the motor-protective circuit-breaker's systeminstallation housing, color white

Delivery program



- Technical data ETIM 7.0
- Approvals

Delivery program

Product range Accessories Accessories Indicator lights Colour



white Voltage 230 - 400 V Voltage [Us] 230 - 400 V For use with CI-K2-PKZ0-... CI-K4-PKZ4 CI-PKZ0(1) E-PKZ0(1)

Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [I_n] 0 A Heat dissipation per pole, current-dependent [P_{id}] 0 W Equipment heat dissipation, current-dependent [P_{id}] 0 W Static heat dissipation, non-current-dependent [P_{vs}] 0.46 W Heat dissipation capacity [P_{diss}]

0 W Operating ambient temperature min. -25 °C Operating ambient temperature max. +55 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiation **Please enquire** 10.2 Strength of materials and parts 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2 Strength of materials and parts10.2.7 Inscriptions Meets the product standard's requirements. 10.3 Degree of protection of ASSEVBLIES Does not apply, since the entire switchgear needs to be evaluated. 10.4 Clearances and creepage distances Meets the product standard's requirements. 10.5 Protection against electric shock Does not apply, since the entire switchgear needs to be evaluated. 10.6 Incorporation of switching devices and components Does not apply, since the entire switchgear needs to be evaluated. 10.7 Internal electrical circuits and connections Is the panel builder's responsibility. 10.8 Connections for external conductors Is the panel builder's responsibility. 10.9 Insulation properties 10.9.2 Pow er-frequency electric strength Is the panel builder's responsibility. 10.9 Insulation properties 10.9.3 Impulse withstand voltage Is the panel builder's responsibility. 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material Is the panel builder's responsibility. 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Indicator light complete (EC000272) Bectric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Indicator light complete (ecl@ss10.0.1-27-37-12-23 [AKF041014]) Number of indicator lights 10 Colour lens Clear Type of lamp socket Other With light source Yes Rated operating voltage Ue 230 - 400 V Voltage type AC/DC Type of electric connection

Flat plug-in connection Construction type lens Rectangular Type of lens Flat Hole diameter 16 mm Width opening 0 mm Height opening 0 mm With front ring No Material front ring Other Colour front ring Other Degree of protection (IP) IP65 Degree of protection (NEVA) Other

Approvals

Specially designed for North America No

Additional product information

- Motor starters and "Special Purpose Ratings" for the North American market (PDF)
- Busbar Component Adapters for modern Industrial control panels
 (PDF)

3D drawing



Line drawing Indicator lights with neon bulb



Line drawing Indicator lights with neon bulb

Dimensions single product



Product photo

121A100 Photo Indicator lights with neon bulb

Symbol

•	\bigcirc
	116C063
	Graphic
	Button plate, white

Declaration of Conformity

EU

- FKZM0 (DA-DC-00003629) Asset (FDF)
- FKZMD-T (DA-DC-00004064) Asset (PDF)
- PKM0 (DA-DC-00004075) Asset (PDF)
- PKZMD -EA (DA-DC-00004076) Asset (PDF)

Instruction Leaflet

 Indicator light for motor-protective circuit-breaker (IL03402035Z) Asset (PDF, multilingual)

CAD data

edz files

• DA-CE-ETN.L-PKZ0(400V) File (Web)

Download-Center

- Dow nload-Center (this item)
 Eaton EVEA Dow nload-Center dow nload data for this item
 Dow nload-Center
- Eaton EVEA Dow nload-Center

ß

- Generate data sheet in PDF format
- X
- Generate data sheet in Excel format
- ہے Write a comment
- Imprint Privacy Policy Legal Disclaimer Terms and Conditions © 2021 by Eaton Industries GmbH