

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMB-4-XSVS - Socket, 4p, 630A



168473 NZMB-4-XSVS

[Overview](#) [Specifications](#) [Resources](#)



## 168473 NZM3-4-XSVS

Socket, 4p, 630A

Alternate Catalog No.

EL-Nummer (Norway)


NZMB-4-XSVS

4357581

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple.

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0

### Delivery program



Product range

Accessories

Accessories

Plug-in socket for basic unit

Standard/Approval

IEC

Installation type

Plug-in units

Construction size

NZMB

Description

Plug base for use with basic units NZM...-SVE of the respective size

Number of poles

4 pole

Standard equipment

Screw connection

### Technical data

General

Standards  
 IEC/EN 60947  
 Protection against direct contact  
 Finger and back-of-hand proof to VDE 0106 part 100  
 Climatic proofing  
 Damp heat, constant, to IEC 60068-2-78  
 Damp heat, cyclic, to IEC 60068-2-30  
 Ambient temperature Ambient temperature, storage  
 - 40 - + 70 °C  
 Operation  
 -25 - +70 °C  
 Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27  
 20 (half-sinusoidal shock 20 ms) g  
 Safe isolation to EN 61140 Between auxiliary contacts and main contacts  
 500 V AC  
 Safe isolation to EN 61140 between the auxiliary contacts  
 300 V AC  
 Mounting position  
 Vertical and 90° right/left  
 Direction of incoming supply  
 as required  
 Degree of protection  
 Device  
 IP2X (in the area of the plug-in area)

## Design verification as per IEC/EN 61439

Technical data for design verification  
 Equipment heat dissipation, current-dependent [ $P_{vid}$ ]  
 83.35 W  
 Operating ambient temperature min.  
 -25 °C  
 Operating ambient temperature max.  
 +70 °C  
 IEC/EN 61439 design verification  
 10.2 Strength of materials and parts 10.2.2 Corrosion resistance  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.5 Lifting  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts 10.2.6 Mechanical impact  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts 10.2.7 Inscriptions  
 Meets the product standard's requirements.  
 10.3 Degree of protection of ASSEMBLIES  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.4 Clearances and creepage distances  
 Meets the product standard's requirements.  
 10.5 Protection against electric shock  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.6 Incorporation of switching devices and components  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.7 Internal electrical circuits and connections  
 Is the panel builder's responsibility.  
 10.8 Connections for external conductors  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.2 Power-frequency electric strength  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.3 Impulse withstand voltage  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])

Rated current In

500 A

Number of poles

4

Version as busbar adapter

No

Version as built-in device

Yes

Type of electrical connection of main circuit

Screw connection

## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-nzm3\\_4\\_xsvs](#)  
File  
(Web)


## edz files

- [DA-CE-ETN.NZMB-4-XSVS](#)  
File  
(Web)

## Step files

- [DA-CS-nzm3\\_4\\_xsvs](#)  
File  
(Web)

## 3D drawing



1231713

Line drawing

Removable compartment

## Product photo



1230PIC-815

Photo

## Instruction Leaflet

- [IL01219058Z2](#)  
Asset  
(PDF, Language independent)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH