



**Undervoltage release, 208-240VAC**

**Part no.** IZM-UVR230AC  
**Catalog No.** 122952  
**Alternate Catalog No.** 2A10705G02  
**EL-Nummer (Norway)** 4357837

**Delivery program**

Accessories			Voltage release
Accessories			Undervoltage release
For use with			IZM20, 32, 40, 63... IN20, 32,40, 63...
<b>Instructions</b>			If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

**Technical data**

**Rated control voltage**

AC 50/60 Hz	$U_s$	V	208 - 240
-------------	-------	---	-----------

**Power consumption**

AC		VA	10 (pick-up 400)
Circuit-breaker response time at $U_s$		ms	70

**Operating range**

Drop-out voltage		$x U_s$	
AC operated, 50/60 Hz, pick-up	Drop-out	$x U_c$	According to the IEC standard
Pick-up voltage		$x U_s$	
	Pick-up	$x U_c$	According to the IEC standard

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

**Technical data ETIM 4.0**

Rated control supply voltage $U_s$ at AC 50HZ		V	208 - 240
Rated control supply voltage $U_s$ at AC 60HZ		V	208 - 240
Rated control supply voltage $U_s$ at DC		V	0 - 0
Voltage type for actuating			AC
Type of electric connection			Flat plug-in connection
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Delayed			No
Suitable for power circuit breaker			Yes
Suitable for switch disconnecter			Yes
Suitable for motor safety switch			No
Suitable for overload relay			No