

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



ZM-UVR230AC - Undervoltage release, 208-240VAC



122952 IZM-UVR230AC

[Overview](#) [Specifications](#) [Resources](#)



# 122952 IZM-UVR230AC

Undervoltage release, 208-240VAC

Alternate Catalog No.

2A10705G02

EL-Nummer (Norway)

4357837

Undervoltage release, For use with: IZM20, 32, 40, 63... , IN20, 32,40, 63... , If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71



- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 4.0

## Delivery program

Accessories

Voltage release

Accessories

Undervoltage release

For use with

IZM20, 32, 40, 63...

IN20, 32,40, 63...

### Instructions

If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

## Technical data

Rated control voltage [ $U_s$ ]

AC 50/60 Hz [ $U_s$ ]

208 - 240 V

Power consumption

AC

10 (pick-up 400) VA

Circuit-breaker response time at  $U_s$

70 ms

Operating range

Drop-out voltage AC operated, 50/60 Hz, pick-up [Drop-out]

According to the IEC standard x  $U_c$

Pick-up voltage [Pick-up]

According to the IEC standard x  $U_c$

## Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

## Technical data ETIM 4.0

Rated control supply voltage  $U_s$  at AC 50HZ

208 - 240 V

Rated control supply voltage  $U_s$  at AC 60HZ

208 - 240 V

Rated control supply voltage  $U_s$  at DC

0 - 0 V

Voltage type for actuating

AC

Type of electric connection

Flat plug-in connection

Number of contacts as normally open contact

0

Number of contacts as normally closed contact

0

Number of contacts as change-over contact

0

Delayed

No

Suitable for power circuit breaker

Yes

Suitable for switch disconnecter

Yes

Suitable for motor safety switch

No

Suitable for overload relay

No


## Product photo



[CPC\\_ACB\\_MAG](#)

Photo

## 3D drawing



[1230DRW-841](#)

Line drawing

## CAD data

### edz files

- [DA-CE-ETN.IZM-UVR230AC](#)

File

(Web)

## Download-Center

- [Download-Center \(this item\)](#)

Eaton EMEA Download-Center - download data for this item

- [Download-Center](#)

Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

