

# Eaton 259080

Catalog Number: 259080

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 125A, B, frame1, A125



Photo is representative

## General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker thermo-magnetic	259080
	Model Code
	NZMB1-A125
EAN	Product Length/Depth
4015082590802	88 mm
Product Height	Product Width
145 mm	90 mm
Product Weight	Compliances
1.068 kg	RoHS conform
Certifications	
IEC/EN 60947	
IEC	

## Type

Circuit breaker

## Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity  $I_{cn}$ )  
 Rated current = rated uninterrupted current: 125 A  
 Terminal capacity hint: Up to 95 mm<sup>2</sup> can be connected depending on the cable manufacturer.

## Application

Use in unearthed supply systems at 440 V

## Amperage Rating

125 A

## Voltage rating

440 V - 440 V

## Circuit breaker frame type

NZM1

## Features

Protection unit

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

## Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

## Certification reports

[DA-DC-NZM1-UKCA.pdf](#)

## Characteristic curve

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-051.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-038.eps](#)

[eaton-circuit-breaker-characteristic-power-defense-mccb-characteristic-curve-032.eps](#)

## Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-017.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-014.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-3-d-drawing-006.eps](#)

## eCAD model

[ETN.NZMB1-A125](#)

## Installation instructions

[eaton-circuit-breaker-switch-disconnector-nzmb-il01203004z.pdf](#)

## Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

## mCAD model

[DA-CD-nzm1\\_3p](#)

[DA-CS-nzm1\\_3p](#)

## Technical data sheets

[eaton-nzm-technical-information-sheet](#)

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Pollution degree

3

#### Mounting Method

Built-in device fixed built-in technique

Fixed

DIN rail (top hat rail) mounting optional

#### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

#### Equipment heat dissipation, current-dependent

26.72 W

#### Utilization category

A (IEC/EN 60947-2)

#### Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

70 °C

#### Ambient storage temperature - min

40 °C

#### Number of auxiliary contacts (change-over contacts)

0

#### Number of auxiliary contacts (normally closed contacts)

0

#### Number of auxiliary contacts (normally open contacts)

0

#### Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part

110

#### Degree of protection

IP20 (basic degree of protection, in the operating controls area)

IP20

#### Direction of incoming supply

As required

#### Electrical connection type of main circuit

Frame clamp

#### Lifespan, mechanical

20000 operations

#### Overvoltage category

III

#### Degree of protection (IP), front side

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

#### Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

#### Number of poles

Three-pole

#### Terminal capacity (copper strip)

Max. 9 segments of 9 mm x 0.8 mm at box terminal

Min. 2 segments of 9 mm x 0.8 mm at box terminal

#### Lifespan, electrical

7500 operations at 415 V AC-1

7500 operations at 400 V AC-1

#### Functions

System and cable protection

#### Shock resistance

20 g (half-sinusoidal shock 20 ms)

#### Position of connection for main current circuit

Front side

#### Rated operational current for specified heat dissipation (I<sub>n</sub>)

125 A

#### Power loss

26.7 W

#### Release system

Thermomagnetic release

#### Short-circuit total breaktime

< 10 ms

#### Short-circuit release non-delayed setting - max

1250 A

#### Short-circuit release non-delayed setting - min

750 A

#### Terminal capacity (control cable)

0.75 mm<sup>2</sup> - 2.5 mm<sup>2</sup> (1x)

0.75 mm<sup>2</sup> - 1.5 mm<sup>2</sup> (2x)

#### Terminal capacity (copper busbar)

M6 at rear-side screw connection

Min. 12 mm x 5 mm direct at switch rear-side connection

Max. 16 mm x 5 mm direct at switch rear-side connection

#### Terminal capacity (copper solid conductor/cable)

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) at box terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) at box terminal

6 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

#### Terminal capacity (aluminum solid conductor/cable)

16 mm<sup>2</sup> (1x) at tunnel terminal

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (1x) direct at switch rear-side connection

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

#### Terminal capacity (copper stranded conductor/cable)

10 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) at box terminal

10 mm<sup>2</sup> - 70 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> (2x) direct at switch rear-side connection

6 mm<sup>2</sup> - 25 mm<sup>2</sup> (2x) at box terminal

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

#### Terminal capacity (aluminum stranded conductor/cable)

25 mm<sup>2</sup> - 35 mm<sup>2</sup> (2x) direct at switch rear-side connection

25 mm<sup>2</sup> - 95 mm<sup>2</sup> (1x) at tunnel terminal

25 mm<sup>2</sup> - 35 mm<sup>2</sup> (1x) direct at switch rear-side connection

#### Handle type

Rocker lever

#### Short delay current setting (I<sub>sd</sub>) - max

0 A

#### Short delay current setting (I<sub>sd</sub>) - min

0 A

#### Instantaneous current setting (I<sub>i</sub>) - max

1250 A

#### Instantaneous current setting (I<sub>i</sub>) - min

750 A

#### Number of operations per hour - max

120

Overload current setting (I<sub>r</sub>) - max

125 A

Overload current setting (I<sub>r</sub>) - min

100 A

Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 230 V, 50/60 Hz

30 kA

Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 400/415 V, 50/60 Hz

25 kA

Rated short-circuit breaking capacity I<sub>cs</sub> (IEC/EN 60947) at 440 V, 50/60 Hz

18.5 kA

Rated short-circuit making capacity I<sub>cm</sub> at 400/415 V, 50/60 Hz

53 kA

Rated short-circuit making capacity I<sub>cm</sub> at 440 V, 50/60 Hz

53 kA

Standard terminals

Box terminal

Optional terminals

Connection on rear. Screw terminal. Tunnel terminal

Rated short-circuit making capacity I<sub>cm</sub> at 240 V, 50/60 Hz

63 kA

Rated impulse withstand voltage (U<sub>imp</sub>) at auxiliary contacts

6000 V

Rated impulse withstand voltage (U<sub>imp</sub>) at main contacts

6000 V

Rated insulation voltage (U<sub>i</sub>)

690 V AC



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)