

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMN3-4-VE630 - Circuit-breaker, 4p, 630A



265960 NZMN3-4-VE630

[Overview](#) [Specifications](#) [Resources](#)



## 265960 NZMN3-4-VE630

Circuit-breaker, 4p, 630A

EL-Nummer (Norway)

0004358861

Circuit-breaker NZM3, 4 pole, Switching capacity 400/415 V 50 Hz( I<sub>cu</sub> ): 50 kA, Rated current = rated uninterrupted current Rated current = rated uninterrupted current( I<sub>n</sub> = I<sub>u</sub> ): 630 A, Installation type: Fixed, Screw connection, Standard/Approval: IEC, Protective function: Systems, cable, selectivity and generator protection

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

### Delivery program

Product range  
Circuit-breaker  
Protective function  
Systems, cable, selectivity and generator protection  
Standard/Approval  
IEC  
Installation type  
Fixed  
Release system  
Electronic release  
Construction size  
NZM3  
Description  
R.m.s. value measurement and "thermal memory"  
Adjustable time delay setting to overcome current peaks  $t_r$  at  $6 \times I_r$  also infinity (without overload releases)  
Adjustable delay time  $t_{sd}$   
 $i^2t$  constant function: switchable  
Number of poles  
4 pole  
Standard equipment  
Screw connection  
Switching capacity  
400/415 V 50 Hz [I<sub>cu</sub>]  
50 kA  
Rated current = rated uninterrupted current [I<sub>n</sub> = I<sub>u</sub>]


Rated current = rated uninterrupted current [ $I_n = I_u$ ]

630 A

Neutral conductor [% of phase conductor]

100 %

### Setting range

Overload trip  [ $I_t$ ]

315 - 630 A

Overload trip Main pole  [ $I_t$ ]

315 - 630 A

Short-circuit releases  [ $I_{rm}$ ] Non-delayed  [ $I_t = I_n \times \dots$ ]

2 - 8

Short-circuit releases  [ $I_{rm}$ ] Delayed  [ $I_{sd} = I_t \times \dots$ ]

1.5 - 7

## Technical data

General

Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature Ambient temperature, storage

- 40 - + 70 °C

Ambient temperature Operation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g


Safe isolation to EN 61140 Between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

Mounting position

Vertical and 90° in all directions	
	With XFI earth-fault release:
	- N2M1, N1, N2M2, N2: vertical and 90° in all directions
	with plug-in unit
	- N2M1, N1, N2M2, N2: vertical, 90° right/left
	with withdrawable unit:
	- N3M3, N3: vertical, 90° right/left
	- N4M4, N4: vertical
with remote operator:	
- N2M2, N(S)2, N3M3, N(S)3, N4M4, N(S)4: vertical and 90° in all directions	

Direction of incoming supply

as required

Degree of protection Device

In the operating controls area: IP20 (basic degree of protection)

Degree of protection Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [ $I_n = I_u$ ]

630 A

Rated surge voltage invariability [ $U_{imp}$ ] Main contacts

8000 V

Rated surge voltage invariability [ $U_{imp}$ ] Auxiliary contacts

6000 V

Rated operational voltage [ $U_e$ ]

690 V AC

Overvoltage category/pollution degree  
 III/3  
 Rated insulation voltage [U]  
 1000 V  
 Use in unearthed supply systems  
 690 V  
 Switching capacity  
 Rated short-circuit making capacity [I<sub>cm</sub>]240 V [I<sub>cm</sub>]  
 187 kA  
 Rated short-circuit making capacity [I<sub>cm</sub>]400/415 V [I<sub>cm</sub>]  
 105 kA  
 Rated short-circuit making capacity [I<sub>cm</sub>]440 V 50/60 Hz [I<sub>cm</sub>]  
 74 kA  
 Rated short-circuit making capacity [I<sub>cm</sub>]525 V 50/60 Hz [I<sub>cm</sub>]  
 53 kA  
 Rated short-circuit making capacity [I<sub>cm</sub>]690 V 50/60 H [I<sub>cm</sub>]  
 40 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cu</sub> to IEC/EN 60947 test cycle O-t-CO [I<sub>cu</sub>]240 V 50/60 Hz [I<sub>cu</sub>]  
 85 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cu</sub> to IEC/EN 60947 test cycle O-t-CO [I<sub>cu</sub>]400/415 V 50/60 Hz [I<sub>cu</sub>]  
 50 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cu</sub> to IEC/EN 60947 test cycle O-t-CO [I<sub>cu</sub>]440 V 50/60 Hz [I<sub>cu</sub>]  
 35 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cu</sub> to IEC/EN 60947 test cycle O-t-CO [I<sub>cu</sub>]525 V 50/60 Hz [I<sub>cu</sub>]  
 25 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cu</sub> to IEC/EN 60947 test cycle O-t-CO [I<sub>cu</sub>]690 V 50/60 Hz [I<sub>cu</sub>]  
 20 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cs</sub> to IEC/EN 60947 test cycle O-t-CO-t-CO [I<sub>cs</sub>]240 V 50/60 Hz [I<sub>cs</sub>]  
 85 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cs</sub> to IEC/EN 60947 test cycle O-t-CO-t-CO [I<sub>cs</sub>]400/415 V 50/60 Hz [I<sub>cs</sub>]  
 50 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cs</sub> to IEC/EN 60947 test cycle O-t-CO-t-CO [I<sub>cs</sub>]440 V 50/60 Hz [I<sub>cs</sub>]  
 35 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cs</sub> to IEC/EN 60947 test cycle O-t-CO-t-CO [I<sub>cs</sub>]525 V 50/60 Hz [I<sub>cs</sub>]  
 13 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]I<sub>cs</sub> to IEC/EN 60947 test cycle O-t-CO-t-CO [I<sub>cs</sub>]690 V 50/60 Hz [I<sub>cs</sub>]  
 5 kA  
 Rated short-circuit breaking capacity I<sub>cn</sub> [I<sub>cn</sub>]  
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.  
 Rated short-time withstand currentt = 0.3 s [I<sub>cw</sub>]  
 3.3 kA  
 Rated short-time withstand currentt = 1 s [I<sub>cw</sub>]  
 3.3 kA  
 Utilization category to IEC/EN 60947-2  
 A  
 Lifespan, mechanical(of which max. 50 % trip by shunt/undervoltage release) [Operations]  
 15000  
 Lifespan, electricalAC-1400 V 50/60 Hz [Operations]  
 5000  
 Lifespan, electricalAC-1415 V 50/60 Hz [Operations]  
 5000  
 Lifespan, electricalAC-1690 V 50/60 Hz [Operations]  
 3000  
 Lifespan, electricalAC--3400 V 50/60 Hz [Operations]  
 2000  
 Lifespan, electricalAC--3415 V 50/60 Hz [Operations]  
 2000  
 Lifespan, electricalAC--3690 V 50/60 Hz [Operations]  
 2000  
 Lifespan, electricalMax. operating frequency  
 60 Ops/h  
 Total break time at short-circuit  
 < 10 ms  
**Terminal capacity**  
 Standard equipment  
 Screw connection  
 Optional accessories  
 Box terminal

Tunnel terminal  
 connection on rear  
 Round copper conductor Box terminal Solid  
 2 x 16 mm<sup>2</sup>  
 Round copper conductor Box terminal Stranded  
 1 x (35 - 240)  
 2 x (25-120) mm<sup>2</sup>  
 Round copper conductor Tunnel terminal Solid  
 1 x 16 mm<sup>2</sup>  
 Round copper conductor Tunnel terminal Stranded 1-hole  
 1 x (16 - 185) mm<sup>2</sup>  
 Round copper conductor Tunnel terminal Stranded Double hole fitting  
 2 x (50 - 240) mm<sup>2</sup>  
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Solid  
 1 x 16  
 2 x 16 mm<sup>2</sup>  
 Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded  
 1 x (25 - 240)  
 2 x (25 - 240) mm<sup>2</sup>  
 Round copper conductor Bolt terminal and rear-side connection Connection width extension Connection width extension  
 2 x 300 mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Solid  
 1 x 16 mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Stranded Stranded  
 1 x (25 - 185)<sup>2</sup> mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Stranded Double hole  
 1 x (50 - 240)  
 2 x (50 - 240) mm<sup>2</sup>  
 Al circular conductor Tunnel terminal Stranded  
<sup>2)</sup> Up to 240 mm<sup>2</sup> can be connected depending on the cable manufacturer.  
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Solid  
 1 x 16  
 2 x (10 - 16) mm<sup>2</sup>  
 Al circular conductor Bolt terminal and rear-side connection Direct on the switch Stranded  
 1 x (25 - 120)  
 2 x (25 - 120) mm<sup>2</sup>  
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]  
 6 x 16 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]  
 10 x 24 x 1.0  
 + 5 x 24 x 1.0  
 (2 x) 8 x 24 x 1.0 mm  
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,  
 with holes [min.]  
 6 x 16 x 0.8 mm  
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,  
 with holes [max.]  
 10 x 32 x 1.0 + 5 x 32 x 1.0 mm  
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Connection width  
 extension  
 (2 x) 10 x 50 x 1.0 mm  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection  
 M10  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]  
 20 x 5 mm  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]  
 30 x 10  
 + 30 x 5 mm  
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Connection width extension Connection  
 width extension [max.]  
 2 x (10 x 50) mm  
 Control cables  
 1 x (0.75 - 2.5)  
 2 x (0.75 - 1.5) mm<sup>2</sup>

## Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [ $I_r$ ]

630 A

Equipment heat dissipation, current-dependent [P<sub>id</sub>]

178.61 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I<sub>u</sub>

630 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V, 50 Hz

50 kA

Overload release current setting

315 - 630 A

Adjustment range short-term delayed short-circuit release

472 - 4410 A  
Adjustment range undelayed short-circuit release  
1260 - 5040 A  
Integrated earth fault protection  
No  
Type of electrical connection of main circuit  
Screw connection  
Device construction  
Built-in device fixed built-in technique  
Suitable for DIN rail (top hat rail) mounting  
No  
DIN rail (top hat rail) mounting optional  
No  
Number of auxiliary contacts as normally closed contact  
0  
Number of auxiliary contacts as normally open contact  
0  
Number of auxiliary contacts as change-over contact  
0  
With switched-off indicator  
No  
With under voltage release  
No  
Number of poles  
4  
Position of connection for main current circuit  
Front side  
Type of control element  
Rocker lever  
Complete device with protection unit  
Yes  
Motor drive integrated  
No  
Motor drive optional  
Yes  
Degree of protection (IP)  
IP20

## Characteristics

Characteristic curve

Characteristic curve

Let-through current

Characteristic curve

Let-through energy

Characteristic curve

## Dimensions

Blow out area, minimum clearance to adjacent parts

Minimum clearance to adjacent parts

## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-nzm3\\_4p](#)

File  
(Web)

## edz files

- [DA-CE-ETN.NZMN3-4-VE630](#)  
File  
(Web)

## Step files

- [DA-CS-nzm3\\_4p](#)  
File  
(Web)

## Additional product information

- [Temperature dependency, Derating](#)  
(Web)
- [CurveSelect characteristics program](#)  
(Web)
- [Eaton configurator](#)  
(Web)
- [additional technical information for NZM power switch](#)  
(PDF)

## Dimensions single product

- [123X332](#)  
Line drawing  
Circuit-breakers
  - Blow out area, minimum clearance to adjacent parts
  - Minimum clearance to adjacent parts
  - Does not apply to DC applications
- [123X553](#)  
Line drawing  
Circuit-breakers, switch-disconnectors

## 3D drawing

- [123612](#)  
Line drawing  
Protection of systems and cables

## Product photo

-   
[1230PIC-705](#)  
Photo

## Characteristic curve

- [1230DIA-11](#)  
Coordinate visualization  
Let-through current
- [1230DIA-19](#)  
Coordinate visualization  
Let-through energy
-

[123U172](#)

Coordinate visualization  
N2MB-VE250...630 tripping characteristic



[123U183](#)

Coordinate visualization  
N2MB-VE250...630 tripping characteristic

## Instruction Leaflet

- [IL01208009Z](#)

Asset  
(PDF, Language independent)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2021 by Eaton Industries GmbH

