

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZM2-4-XIPA - Protection against contact with a finger, IP2X, 4p, size 2



266778 NZM2-4-XIPA

[Overview](#) [Specifications](#) [Resources](#)



266778 NZM2-4-XIPA

Protection against contact with a finger, IP2X, 4p, size 2

EL-Nummer (Norway)

4358890

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Note: Type contains parts for a terminal located at top or bottom for 3 or 4 pole switches. Enhancement of the busbar tag shroud to IP2X. When mounting NZM2...-(C)NA or NZM...-NA the following applies: with 2 conductors maximum cross-section 25mm² or AWG4. Can be used for: NZM2(-4), FN2(-4), N2(-4)

- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

Delivery program

Accessories

IP2X protection against contact with a finger

Number of conductors

4 pole

Accessories

IP2X protection against contact with finger

For use with

NZM2(-4), FN2(-4), N2(-4)

For use with

for cover NZM2-XKSA or NZM2 or NZM2...(C)NA und N(S)2...NA

Notes

Type contains parts for a terminal located at top or bottom for 4 pole circuit-breakers.

Enhancement of the busbar tag shroud to IP2X.

When mounting NZM2...-(C)NA or NZM...-NA the following applies:

with 2 conductors max cross section 25 mm² or AWG4.

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase separation plate for power circuit breaker (EC002035)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Phase separation plate for circuit breaker (ecl@ss10.0.1-27-37-04-25 [ACN959011])

Model

Other

Dimensions



3 pole

4 pole

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)


DWG files

- [DA-CD-nzm2_xipa](#)
File
(Web)

Step files

- [DA-CS-nzm2_xipa](#)
File
(Web)

Dimensions single product



123X319

- Line drawing
- Shroud for screw terminals
- 3 pole
- 4 pole

3D drawing



123I656

- Line drawing
- Protection against contact with a finger for shroud

Product photo



1230PIC-1375

Photo

Instruction Leaflet

- [NZM\(-4\)-XIP\(K\)\(A\) \(IL01219008Z\)](#)
IL01219008Z
(PDF, 05/2021, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH