

# Eaton 266028

Catalog Number: 266028

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 3p 1600A BG4



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series NZM switch-disconnector	266028
	<b>Model Code</b>
	N4-1600
<b>EAN</b>	<b>Product Length/Depth</b>
4015082660284	401 mm
<b>Product Height</b>	<b>Product Width</b>
207 mm	210 mm
<b>Product Weight</b>	<b>Compliances</b>
19.2 kg	RoHS conform
<b>Certifications</b>	
IEC/EN 60947	
IEC	

## Type

Switch-disconnector

## Special features

Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.

Isolating characteristics to IEC/EN 60947-3 and VDE 0660.

Busbar tag shroud to VDE 0160 Part 100.

Rated current = rated uninterrupted current: 1600 A

## Application

Use in unearthed supply systems at 525 V

## Amperage Rating

1600 A

## Voltage rating

690 V - 690 V

## Circuit breaker frame type

N4

## Features

Motor drive optional

Version as main switch

Version as maintenance-/service switch

Version as emergency stop installation

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

## Brochures

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

## Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

## Certification reports

[DA-DC-03\\_N4](#)

## Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-022.eps](#)

## eCAD model

[ETN.N4-1600](#)

## Installation instructions

[IL012101ZU](#)

[IL01210010Z](#)

## Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

## mCAD model

[DA-CS-nzm4\\_3p](#)

[DA-CD-nzm4\\_3p](#)

## Technical data sheets

[eaton-nzm-technical-information-sheet](#)

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

#### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

#### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

### Pollution degree

3

### Mounting Method

Ground mounting

Fixed

Built-in device fixed built-in technique

Distribution board installation

Intermediate mounting

### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

### Equipment heat dissipation, current-dependent

284 W

### Isolation

300 V AC (between the auxiliary contacts)

500 V AC (between auxiliary contacts and main contacts)

### Rated short-time withstand current (I<sub>cw</sub>)

25 kA

### Degree of protection

IP20 (basic protection type, in the area of the HMI devices)

Other

### Direction of incoming supply

As required

### Electrical connection type of main circuit

Bolt connection

### Ambient operating temperature - max

70 °C

### Ambient operating temperature - min

-25 °C

### Ambient storage temperature - max

70 °C

### Ambient storage temperature - min

40 °C

### Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part  
263

Rated insulation voltage (Ui)

1000 V

Rated operating frequency

50 Hz

Rated operating power at AC-23, 400 V

800 kW

Rated operating power at AC-3, 400 V

0 kW

Switch positions

I, +, 0

Lifespan, mechanical

10000 operations

Overvoltage category

III

Rated operational current

1600 A (415 V AC-22/23A, making and breaking capacity)

1600 A (690 V AC-22/23A, making and breaking capacity)

Degree of protection (IP), front side

IP40 (with insulating surround)

IP20

IP66 (with door coupling rotary handle)

Degree of protection (terminations)

IP00 (terminations, phase isolator and band terminal)

IP10 (tunnel terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection  
(punched)

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor  
terminal

10 segments of 80 mm x 1 mm (2x) at rear-side width extension

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate  
Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection  
(punched)  
Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

#### Handle color

Black

#### Lifespan, electrical

2000 operations at 400 V AC-3  
2000 operations at 415 V AC-3  
2000 operations at 690 V AC-1  
3000 operations at 415 V AC-1  
3000 operations at 400 V AC-1  
1000 operations at 690 V AC-3

#### Functions

Voltage release optional  
Disconnectors/main switches  
Interlockable

#### Shock resistance

15 g (half-sinusoidal shock 11 ms)

#### Number of switches

1

#### Rated conditional short-circuit current (I<sub>q</sub>)

0 kA

#### Rated conditional short-circuit current with back-up fuse

100 kA at 400/415 V  
80 kA at 690 V  
N4-630...1600: 2 x 800 AgGgL

#### Rated conditional short-circuit current with downstream fuse

80 kA at 690 V  
N4-630...1600: 2 x 800 AgGgL  
100 kA at 400/415 V

#### Rated operating voltage (U<sub>e</sub>) at AC - max

690 V

#### Rated operational current for specified heat dissipation (I<sub>n</sub>)

1600 A

#### Rated permanent current at AC-21, 400 V

0 A

#### Rated permanent current at AC-23, 400 V

0 A

#### Rated short-time withstand current (t = 0.3 s)

25 kA

Rated short-time withstand current (t = 1 s)

25 kA

Switching power at 400 V

0 kW

Handle type

Rocker lever

Number of operations per hour - max

60

Rated short-circuit making capacity I<sub>cm</sub> at 690 V, 50/60 Hz

53 kA

Rated impulse withstand voltage (U<sub>imp</sub>) at auxiliary contacts

6000 V

Rated impulse withstand voltage (U<sub>imp</sub>) at main contacts

8000 V

Standard terminals

Screw terminal

Optional terminals

Connection on rear. Strip terminal. Tunnel terminal

Short-circuit protective device fuses - max

1600 A gL

Terminal capacity (copper busbar)

Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate

50 mm x 10 mm (2x) at rear-side 2-hole module plate

Min. 25 mm x 5 mm direct at switch rear-side connection

Max. 50 mm x 10 mm (2x) direct at switch rear-side connection

Max. 80 mm x 10 mm (2x) at rear-side width extension

M10 at rear-side screw connection

Min. 25 mm x 5 mm at rear-side 1-hole module plate

Min. 60 mm x 10 mm at rear-side width extension

Terminal capacity (copper solid conductor/cable)

95 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at rear-side width extension

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at 4-hole tunnel terminal

300 mm<sup>2</sup> (4x) at rear-side width extension

70 mm<sup>2</sup> - 185 mm<sup>2</sup> (2x) at rear-side 1-hole module plate

35 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) at rear-side 2-hole module plate

185 mm<sup>2</sup> - 240 mm<sup>2</sup> (1x) at rear-side 1-hole module plate

50 mm<sup>2</sup> (4x) at rear-side 2-hole module plate

Terminal capacity (aluminum solid conductor/cable)

70 mm<sup>2</sup> - 240 mm<sup>2</sup> (6x) at rear-side width extension

240 mm<sup>2</sup> (2x) at rear-side width extension

**Terminal capacity (copper stranded conductor/cable)**

120 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) direct at switch rear-side connection

50 mm<sup>2</sup> - 185 mm<sup>2</sup> (4x) direct at switch rear-side connection

**Terminal capacity (aluminum stranded conductor/cable)**

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (4x) at 4-hole tunnel terminal



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)