

# Eaton 266022

Catalog Number: 266022

Eaton Moeller series NZM - Molded Case Circuit Breaker. Switch-disconnector 4p, 630A, 3



Photo is representative

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series NZM switch-disconnector	266022
	<b>Model Code</b>
	PN3-4-630
<b>EAN</b>	<b>Product Length/Depth</b>
4015082660222	159 mm
<b>Product Height</b>	<b>Product Width</b>
275 mm	185 mm
<b>Product Weight</b>	<b>Compliances</b>
6.23 kg	RoHS conform
<b>Certifications</b>	
IEC	
IEC/EN 60947	

## Type

Switch-disconnector

## Special features

Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113.

Isolating characteristics to IEC/EN 60947-3 and VDE 0660.

Busbar tag shroud to VDE 0160 Part 100.

Rated current = rated uninterrupted current: 630 A

## Application

Use in unearthed supply systems at 690 V

## Amperage Rating

630 A

## Voltage rating

690 V - 690 V

## Circuit breaker frame type

PN4

## Features

Version as emergency stop installation

Version as main switch

Version as maintenance-/service switch

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

## Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

## Certification reports

[DA-DC-03\\_PN3](#)

[DA-DC-03\\_N3](#)

## Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-021.eps](#)

[eaton-circuit-breaker-switch-nzm-mccb-dimensions-016.eps](#)

## eCAD model

[DA-CE-ETN.PN3-4-630](#)

## Installation instructions

[IL01208009Z](#)

## Installation videos

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

## mCAD model

[DA-CD-nzm3\\_4p](#)

[DA-CS-nzm3\\_4p](#)

## Technical data sheets

[eaton-nzm-technical-information-sheet](#)

## 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

## 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

## 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

## 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

## 10.2.7 Inscriptions

Meets the product standard's requirements.

## 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## 10.4 Clearances and creepage distances

Meets the product standard's requirements.

## 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

## 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

## 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

## 10.8 Connections for external conductors

Is the panel builder's responsibility.

## 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

## 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Pollution degree

3

#### Mounting Method

Fixed

Distribution board installation

Ground mounting

Intermediate mounting

Built-in device fixed built-in technique

#### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

#### Equipment heat dissipation, current-dependent

107.16 W

#### Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

#### Rated short-time withstand current (Icw)

12 kA

#### Degree of protection

IP20 (basic protection type, in the area of the HMI devices)

Other

#### Direction of incoming supply

As required

#### Electrical connection type of main circuit

Screw connection

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

70 °C

#### Ambient storage temperature - min

40 °C

#### Number of auxiliary contacts (change-over contacts)

0

#### Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110

Rated insulation voltage (Ui)

1000 V

Rated operating frequency

50 Hz

Rated operating power at AC-23, 400 V

315 kW

Rated operating power at AC-3, 400 V

0 kW

Switch positions

I, 0

Lifespan, mechanical

15000 operations

Overvoltage category

III

Rated operational current

630 A (415 V AC-22A, making and breaking capacity)

500 A (415 V AC-23A, making and breaking capacity)

630 A (690 V AC-22A, making and breaking capacity)

500 A (690 V AC-23A, making and breaking capacity)

Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

IP20

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and band terminal)

Number of poles

Four-pole

Terminal capacity (copper strip)

Max. 8 segments of 24 mm x 1 mm (2x) at box terminal

Max. 10 segments of 32 mm x 1 mm + 5 segments of 32 mm x 1 mm at rear-side connection (punched)

10 segments of 50 mm x 1 mm (2x) at rear-side width extension

Max. 10 segments of 24 mm x 1 mm + 5 segments of 24 mm x 1 mm

Min. 6 segments of 16 mm x 0.8 mm at rear-side connection  
(punched)

Min. 6 segments of 16 mm x 0.8 mm at box terminal

#### Handle color

Black

#### Lifespan, electrical

3000 operations at 415 V AC-3

2000 operations at 690 V AC-3

3000 operations at 690 V AC-1

3000 operations at 400 V AC-3

3000 operations at 400 V AC-1

3000 operations at 415 V AC-1

#### Functions

Disconnectors/main switches

Interlockable

#### Shock resistance

20 g (half-sinusoidal shock 20 ms)

#### Number of switches

1

#### Rated conditional short-circuit current (I<sub>q</sub>)

0 kA

#### Rated conditional short-circuit current with back-up fuse

80 kA at 690 V

PN3(N3)-400...630: 630 AgGgL

100 kA at 400/415 V

#### Rated conditional short-circuit current with downstream fuse

PN3(N3)-400...630: 630 AgGgL

100 kA at 400/415 V

80 kA at 690 V

#### Rated operating voltage (U<sub>e</sub>) at AC - max

690 V

#### Rated operational current for specified heat dissipation (I<sub>n</sub>)

630 A

#### Rated permanent current at AC-21, 400 V

0 A

#### Rated permanent current at AC-23, 400 V

0 A

#### Rated short-time withstand current (t = 0.3 s)

12 kA

#### Rated short-time withstand current (t = 1 s)

12 kA

Switching power at 400 V

0 kW

Handle type

Rocker lever

Number of operations per hour - max

60

Rated short-circuit making capacity I<sub>cm</sub> at 690 V, 50/60 Hz

25 kA

Rated impulse withstand voltage (U<sub>imp</sub>) at auxiliary contacts

6000 V

Rated impulse withstand voltage (U<sub>imp</sub>) at main contacts

8000 V

Standard terminals

Screw terminal

Optional terminals

Box terminal. Connection on rear. Tunnel terminal

Short-circuit protective device fuses - max

630 A gL

Terminal capacity (copper busbar)

Max. 10 mm x 50 mm (2x) at rear-side width extension

Max. 30 mm x 10 mm + 30 mm x 5 mm direct at switch rear-side connection

Min. 20 mm x 5 mm direct at switch rear-side connection

M10 at rear-side screw connection

Terminal capacity (copper solid conductor/cable)

16 mm<sup>2</sup> (1x) direct at switch rear-side connection

300 mm<sup>2</sup> (2x) at rear-side width extension

16 mm<sup>2</sup> (2x) at box terminal

16 mm<sup>2</sup> (2x) direct at switch rear-side connection

Terminal capacity (aluminum solid conductor/cable)

10 mm<sup>2</sup> - 16 mm<sup>2</sup> (2x) direct at switch rear-side connection

16 mm<sup>2</sup> (1x) at tunnel terminal

16 mm<sup>2</sup> (1x) direct at switch rear-side connection

Terminal capacity (copper stranded conductor/cable)

25 mm<sup>2</sup> - 120 mm<sup>2</sup> (2x) direct at switch rear-side connection

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (1x) at 2-hole tunnel terminal

50 mm<sup>2</sup> - 240 mm<sup>2</sup> (2x) at 2-hole tunnel terminal

35 mm<sup>2</sup> - 240 mm<sup>2</sup> (1x) at box terminal

25 mm<sup>2</sup> - 120 mm<sup>2</sup> (1x) direct at switch rear-side connection

25 mm<sup>2</sup> - 120 mm<sup>2</sup> (2x) at box terminal

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal

**Terminal capacity (aluminum stranded conductor/cable)**

25 mm<sup>2</sup> - 185 mm<sup>2</sup> (1x) at 1-hole tunnel terminal up to 240 mm<sup>2</sup>

depending on the cable manufacturer.



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)