

Eaton 265772

Catalog Number: 265772

Eaton Moeller series NZM - Molded Case Circuit Breaker. Circuit-breaker, 3p, 1600A, N, frame 4, VE1600



Photo is representative

General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker electronic	265772
	Model Code
	NZMN4-VE1600
EAN	Product Length/Depth
4015082657727	401 mm
Product Height	Product Width
207 mm	210 mm
Product Weight	Compliances
17.28 kg	RoHS conform
Certifications	
IEC/EN 60947	
IEC	

Type

Circuit breaker

Special features

Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit breaker (Rated short-circuit breaking capacity I_{cn})

R.m.s. value measurement and “thermal memory”

Adjustable time delay setting to overcome current peaks I_{tr} at $6 \times I_r$ also infinity (without overload releases)

Adjustable delay time t_{sd}

i^2t constant function: switchable

Rated current = rated uninterrupted current: 1600 A

Application

Use in unearthed supply systems at 525 V

Amperage Rating

1600 A

Voltage rating

690 V - 690 V

Circuit breaker frame type

NZM4

Features

Protection unit

Motor drive optional

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

Certification reports

[DA-DC-03_N4](#)

Characteristic curve

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-049.eps](#)

[eaton-circuit-breaker-nzm-mccb-characteristic-curve-048.eps](#)

Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-022.eps](#)

eCAD model

[ETN.265772.edz](#)

[DA-CE-ETN.NZMN4-VE1600](#)

Installation instructions

[IL01210010Z](#)

Installation videos

[The new digital NZM Range](#)

[Introduction of the new digital circuit breaker NZM](#)

mCAD model

[DA-CS-nzm4_3p](#)

[DA-CD-nzm4_3p](#)

Technical data sheets

[eaton-nzm-technical-information-sheet](#)

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Pollution degree

3

Mounting Method

Fixed

Built-in device fixed built-in technique

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Equipment heat dissipation, current-dependent

284 W

Utilization category

B (IEC/EN 60947-2)

Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

70 °C

Ambient storage temperature - min

40 °C

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

0

Protection against direct contact

Finger and back-of-hand proof to DIN EN 50274/VDE 0106 part 110

Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

Direction of incoming supply

As required

Electrical connection type of main circuit

Screw connection

Lifespan, mechanical

10000 operations

Overvoltage category

III

Degree of protection (IP), front side

IP40 (with insulating surround)

IP66 (with door coupling rotary handle)

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Number of poles

Three-pole

Terminal capacity (copper strip)

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate

10 segments of 80 mm x 1 mm (2x) at rear-side width extension

Max. 10 segments of 50 mm x 1 mm (2x) at rear-side connection (punched)

Min. 5 segments of 25 mm x 1 mm at rear-side connection (punched)

Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor terminal

Lifespan, electrical

3000 operations at 415 V AC-1

2000 operations at 415 V AC-3

2000 operations at 690 V AC-1

3000 operations at 400 V AC-1

1000 operations at 690 V AC-3

2000 operations at 400 V AC-3

Functions

Systems, cable, selectivity and generator protection

Shock resistance

15 g (half-sinusoidal shock 11 ms)

Position of connection for main current circuit

Front side

Rated operational current for specified heat dissipation (I_n)

1600 A

Release system

Electronic release

Short-circuit total breaktime

< 25 ms (< 415 V); < 35 ms (> 415 V)

Rated short-time withstand current (t = 0.3 s)

19.2 kA

Rated short-time withstand current (t = 1 s)

19.2 kA

Short-circuit release delayed setting - max

16000 A

Short-circuit release delayed setting - min

1600 A

Short-circuit release non-delayed setting - max

19200 A

Short-circuit release non-delayed setting - min

3200 A

Terminal capacity (control cable)

0.75 mm² - 1.5 mm² (2x)

0.75 mm² - 2.5 mm² (1x)

Terminal capacity (copper busbar)

Min. 25 mm x 5 mm at rear-side 1-hole module plate

M10 at rear-side screw connection

Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate

Max. 50 mm x 10 mm (2x) direct at switch rear-side connection

Min. 60 mm x 10 mm at rear-side width extension

50 mm x 10 mm (2x) at rear-side 2-hole module plate

Max. 80 mm x 10 mm (2x) at rear-side width extension

Min. 25 mm x 5 mm direct at switch rear-side connection

Terminal capacity (copper solid conductor/cable)

120 mm² - 300 mm² (1x) at rear-side 1-hole module plate

95 mm² - 185 mm² (2x) at rear-side 2-hole module plate

35 mm² - 185 mm² (4x) at rear-side 2-hole module plate

50 mm² - 240 mm² (4x) at 4-hole tunnel terminal

300 mm² (4x) at rear-side width extension

95 mm² - 240 mm² (6x) at rear-side width extension
95 mm² - 300 mm² (2x) at rear-side 1-hole module plate

Terminal capacity (aluminum solid conductor/cable)

240 mm² (2x) at rear-side width extension
50 mm² (4x) at rear-side 2-hole module plate
70 mm² - 185 mm² (2x) at rear-side 1-hole module plate
70 mm² - 240 mm² (6x) at rear-side width extension
185 mm² - 240 mm² (1x) at rear-side 1-hole module plate

Terminal capacity (copper stranded conductor/cable)

120 mm² - 185 mm² (1x) direct at switch rear-side connection
50 mm² - 185 mm² (4x) direct at switch rear-side connection

Terminal capacity (aluminum stranded conductor/cable)

50 mm² - 240 mm² (4x) at 4-hole tunnel terminal

Handle type

Rocker lever

Short delay current setting (I_{sd}) - max

16000 A

Short delay current setting (I_{sd}) - min

1600 A

Instantaneous current setting (I_i) - max

19200 A

Instantaneous current setting (I_i) - min

3200 A

Number of operations per hour - max

60

Overload current setting (I_r) - max

1600 A

Overload current setting (I_r) - min

800 A

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 230 V, 50/60 Hz

37 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz

37 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 440 V, 50/60 Hz

26 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 525 V, 50/60 Hz

19 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 690 V, 50/60 Hz

15 kA

Rated short-circuit making capacity I_{cm} at 400/415 V, 50/60 Hz

105 kA

Rated short-circuit making capacity I_{cm} at 440 V, 50/60 Hz

74 kA

Rated short-circuit making capacity I_{cm} at 525 V, 50/60 Hz

53 kA

Rated short-circuit making capacity I_{cm} at 690 V, 50/60 Hz

40 kA

Standard terminals

Screw terminal

Optional terminals

Connection on rear. Strip terminal. Tunnel terminal

Rated short-circuit making capacity I_{cm} at 240 V, 50/60 Hz

105 kA

Rated impulse withstand voltage (U_{imp}) at auxiliary contacts

6000 V

Rated impulse withstand voltage (U_{imp}) at main contacts

8000 V

Rated insulation voltage (U_i)

1000 V AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)