



**265975**  
**NZMN4-4-VE800**

[Overview](#)

[Specifications](#)

[Resources](#)



[Delivery program](#)

[Technical data](#)

[Design verification as per IEC/EN 61439](#)

[Technical data ETIM 7.0](#)

[Characteristics](#)

[Dimensions](#)

## DELIVERY PROGRAM

Product range  
Circuit-breaker

Protective function  
Systems, cable, selectivity and generator protection

Standard/Approval  
IEC

Installation type  
Fixed

Release system  
Electronic release

Construction size  
NZM4

Description  
R.m.s. value measurement and "thermal memory"

Adjustable time delay setting to overcome current peaks  $t_r$  at  $6 \times I_r$  also infinity (without overload releases)  
Adjustable delay time  $t_{sd}$   
 $i^2t$  constant function: switchable  
Set value in neutral conductor is synchronous with set value  $I_r$  of main pole.

Number of poles  
4 pole

Standard equipment  
Screw connection

### Switching capacity


400/415 V 50 Hz [ $I_{cu}$ ]  
50 kA


### Rated current = rated uninterrupted current [ $I_n = I_u$ ]



Rated current = rated uninterrupted current [ $I_n = I_u$ ]  
800 A



Neutral conductor [% of phase conductor]  
100 %

### Setting range

Overload trip  
 [ $I_r$ ]  
400 - 800 A

Overload trip  
Main pole  [ $I_r$ ]  
400 - 800 A

Short-circuit releases  [ $I_{rm}$ ]  
Non-delayed  [ $I = I_n \times \dots$ ]  
2 - 15

Short-circuit releases  [ $I_{rm}$ ]  
Delayed  [ $I_{sd} = I_n \times \dots$ ]  
2 - 10

# TECHNICAL DATA

## General

Standards  
IEC/EN 60947

Protection against direct contact  
Finger and back of hand proof to VDE 0106 Part 100

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Ambient temperature, storage  
- 40 - + 70 °C

Ambient temperature  
Operation  
-25 - +70 °C


Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27  
15 (half-sinusoidal shock 11 ms) g

Safe isolation to EN 61140  
Between auxiliary contacts and main contacts  
500 V AC

Safe isolation to EN 61140  
between the auxiliary contacts  
300 V AC

## Mounting position

Vertical and 90° in all directions



With XFI earth-fault release:

- NZM1, N1, NZM2, N2: vertical and 90° in all directions

with plug-in unit

- NZM1, N1, NZM2, N2:  
vertical, 90° right/left

with withdrawable unit:

- NZM3, N3: vertical, 90°  
right/left

- NZM4, N4: vertical
- with remote operator:
- NZM2, N(S)2, NZMB, N(S)3, NZM4, N(S)4: vertical and 90° in all directions

Direction of incoming supply as required

Degree of protection  
Device  
In the operating controls area: IP20 (basic degree of protection)

Degree of protection  
Enclosures  
With insulating surround: IP40  
With door coupling rotary handle: IP66

Degree of protection  
Terminations  
Tunnel terminal: IP10  
Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)  
Temperature dependency, Derating

## Circuit-breakers

Rated current = rated uninterrupted current [ $I_n = I_u$ ]  
800 A

Rated surge voltage invariability [ $U_{imp}$ ]  
Main contacts  
8000 V

Rated surge voltage invariability [ $U_{imp}$ ]  
Auxiliary contacts  
6000 V

Rated operational voltage [ $U_e$ ]  
690 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [U]  
1000 V

Use in unearthed supply systems  
 525 V

## Switching capacity

Rated short-circuit making capacity [ $I_{cm}$ ]  
240 V [ $I_{cm}$ ]  
105 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
400/415 V [ $I_{cm}$ ]  
105 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
440 V 50/60 Hz [ $I_{cm}$ ]  
74 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
525 V 50/60 Hz [ $I_{cm}$ ]  
53 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
690 V 50/60 Hz [ $I_{cm}$ ]  
40 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
240 V 50/60 Hz [ $I_{cu}$ ]  
50 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
400/415 V 50/60 Hz [ $I_{cu}$ ]  
50 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
440 V 50/60 Hz [ $I_{cu}$ ]  
35 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
525 V 50/60 Hz [ $I_{cu}$ ]  
25 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Icu to IEC/EN 60947 test cycle O-t-CO [Icu]  
690 V 50/60 Hz [ $I_{cu}$ ]  
20 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
240 V 50/60 Hz [ $I_{cs}$ ]  
37 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
400/415 V 50/60 Hz [ $I_{cs}$ ]  
37 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
440 V 50/60 Hz [ $I_{cs}$ ]  
26 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
525 V 50/60 Hz [ $I_{cs}$ ]  
19 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
690 V 50/60 Hz [ $I_{cs}$ ]  
15 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.

Rated short-time withstand current  
 $t = 0.3$  s [ $I_{cw}$ ]  
12 kA

Rated short-time withstand current  
 $t = 1$  s [ $I_{cw}$ ]  
12 kA

Utilization category to IEC/EN 60947-2  
B

Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]  
10000

Lifespan, electrical  
AC-1  
400 V 50/60 Hz [Operations]  
3000

Lifespan, electrical  
AC-1  
415 V 50/60 Hz [Operations]  
3000

Lifespan, electrical  
AC-1  
690 V 50/60 Hz [Operations]  
2000

Lifespan, electrical  
AC--3  
400 V 50/60 Hz [Operations]  
2000

Lifespan, electrical  
AC--3  
415 V 50/60 Hz [Operations]  
2000

Lifespan, electrical  
AC--3  
690 V 50/60 Hz [Operations]  
1000

Lifespan, electrical  
Max. operating frequency  
60 Ops/h

Total break time at short-circuit  
< 25 □ 415 V; < 35 > 415 V ms

## Terminal capacity

Standard equipment  
Screw connection

Optional accessories  
Tunnel terminal  
connection on rear  
Strip terminal

Round copper conductor  
Tunnel terminal  
Stranded  
4-hole  
4 x (50 - 240) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Direct on the switch  
Stranded  
1 x (120 - 185)  
4 x (50 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [min.]  
1 x (120 - 300) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (95 - 300) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole [min.]  
2 x (95 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole [max.]  
4 x (35 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension  
4 x 300  
6 x (95 - 240) mm<sup>2</sup>

Al circular conductor  
Tunnel terminal  
Stranded  
4-hole  
4 x (50 - 240) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection



Module plate  
Single hole [min.]  
1 x (185 - 240) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (70 - 185) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole  
4 x 50 mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension  
2 x 240  
6 x (70 - 240) mm<sup>2</sup>

Cu strip (number of segments x width x segment thickness)  
Flat conductor terminal [min.]  
6 x 16 x 0.8 mm

Cu strip (number of segments x width x segment thickness)  
Flat conductor terminal [max.]  
(2 x) 10 x 32 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Module plate  
Single hole  
(2 x) 10 x 50 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Bolt terminal and rear-side connection  
Flat copper strip, with holes [min.]  
5 x 25 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Bolt terminal and rear-side connection  
Flat copper strip, with holes [max.]  
(2 x) 10 x 50 x 1.0 mm

Cu strip (number of segments x width x segment

thickness)  
Bolt terminal and rear-side connection  
Connection width extension  
(2 x) 10 x 80 x 1.0 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Screw connection  
M10

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Direct on the switch [min.]  
25 x 5 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Direct on the switch [max.]  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Single hole [min.]  
25 x 5 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Double hole  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension [min.]  
60 x 10 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension [max.]  
2 x (80 x 10) mm

Control cables

1 x (0.75 - 2.5)  
2 x (0.75 - 1.5) mm<sup>2</sup>

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_r$ ]  
800 A

Equipment heat dissipation, current-dependent  
[ $P_{rid}$ ]  
106 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+70 °C

### IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of  
enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating  
materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating  
materials to abnormal heat and fire due to internal  
electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts

10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I<sub>u</sub>  
800 A

Rated voltage  
690 - 690 V

Rated short-circuit breaking capacity I<sub>cu</sub> at 400 V,  
50 Hz  
50 kA

Overload release current setting  
400 - 800 A

Adjustment range short-term delayed short-circuit  
release  
800 - 8000 A

Adjustment range undelayed short-circuit release  
1600 - 9600 A

Integrated earth fault protection  
No

Type of electrical connection of main circuit  
Screw connection

Device construction  
Built-in device fixed built-in technique

Suitable for DIN rail (top hat rail) mounting  
No

DIN rail (top hat rail) mounting optional  
No

Number of auxiliary contacts as normally closed  
contact  
0

Number of auxiliary contacts as normally open  
contact  
0

Number of auxiliary contacts as change-over  
contact  
0

With switched-off indicator  
No

With under voltage release  
No

Number of poles

4

Position of connection for main current circuit  
Front side

Type of control element  
Rocker lever

Complete device with protection unit  
Yes


Motor drive integrated  
No

Motor drive optional  
Yes


Degree of protection (IP)  
IP20

## CHARACTERISTICS


Characteristic curve



Characteristic curve



## DIMENSIONS



Blow out area, minimum clearance to adjacent parts

$U_i \leq 690 \text{ V}$ : 100 mm

$U_i \leq 1500 \text{ V}$ : 200 mm

Minimum clearance to adjacent parts

$U_i \leq 1000 \text{ V}$ : 15 mm

$U_i \leq 1500 \text{ V}$ : 70 mm

