

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZM4-XDV - Rotary handle, lockable



266608 NZM4-XDV

[Overview](#) [Specifications](#) [Resources](#)



266608 NZM4-XDV

Rotary handle, lockable

EL-Nummer (Norway)

4358954

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Note: complete with rotary drive, can be combined with insulating surround, MODAN handle position detection by wire release can be retrofitted. Default, black/grey. Lockable on the 0 position on the switch using up to 3 padlocks. Can be used for: NZM4(-4), N(NO)4(-4)

- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)
- [Dimensions](#)

Delivery program

Product range

Accessories

Accessories

Rotary handle on circuit-breaker

Standard/Approval

UL/CSA, IEC

Construction size

NZM4

Description

Makes it possible to operate the switch with a rotational movement and provides locking facilities

Function

Standard, black/grey

Protection class

IP20

Locking facility

lockable on the 0 position on the switch using up to 3 padlocks

Project planning information

Complete with rotary drive

Cannot be combined with insulating surround

MODAN handle position detection by wire release can be retrofitted

Actuation

Rotary handle

For use with

NZM4(-4), N(S)4(-4)

Notes

Circuit-breaker can also be installed in a lying position 90 ° left/right, with the handle still in the same position.

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0


Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss10.0.1-27-37-04-14 [AKF012014])
Lockable
Yes
Colour
Black
Suitable for emergency stop
No
With extension shaft
No
Suitable for power circuit breaker
Yes
Suitable for switch disconnecter
Yes

Approvals

Product Standards
UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking
UL File No.
E140305
UL Category Control No.

DIHS
CSA File No.
022086
CSA Class No.
1437-01
North America Certification
UL listed, CSA certified
Degree of Protection
IEC: IP20

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm4_xd](#)
File
(Web)

Step files

- [DA-CS-nzm4_xd](#)
File
(Web)

Product photo



[sg07015](#)

Photo

Rotary handle, thumb-grip lockable


Dimensions single product

- d
 $d \frac{1}{2} = 4 - 8$
 $d \frac{3}{4} = 6 - 8$
 $b \geq 34$

[123X196](#)

Line drawing

Padlock



[123X464](#)

Line drawing

Rotary handle on circuit-breaker

3D drawing



1231525

Line drawing

Rotary handle on circuit-breaker

Instruction Leaflet

- [IL01210004Z](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

