

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



PN2-XPA - Paralleling mechanism



283472 PN2-XPA

[Overview](#) [Specifications](#) [Resources](#)



283472 PN2-XPA

Paralleling mechanism

EL-Nummer (Norway)

4359010

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: simultaneous actuation of 2 FN switch-disconnectors of the same type mounted side-by-side. Not UL/CSA approved. 1 x rotary handle on switch (-XD) included as standard. 1x door coupling rotary handle (-XTVD) included as standard. can be used for: FN2(-4) + FN2(-4)

• Delivery program

Design verification as per IEC/EN 61439

• Technical data ETIM 7.0

• Dimensions

Delivery program

Description

Simultaneous actuation of 2 FN switch-disconnectors of the same type mounted side-by-side not UL/CSA approved

For use with

FN2(-4) + FN2(-4)

Notes

PN1, PN2

- 1 x rotary handle on switch (-XD) supplied.
- 1 x door coupling rotary handle (-XTVD) supplied.

Notes

Extension shaft (-XV4(6)) additionally required for the door coupling rotary handle.

Cannot be combined with mechanical interlock, insulating surrounds, side wall operators or remote operators

For use as Emergency-Stop device

For this the door coupling rotary handle requires an exchange thumb-grip in red/yellow according to the following order nos.

- for FN1 and FN2: NZM2-XDGVR □ 100747
- for FN3: NZM3-XDGVR □ 100764; **Note:** The locking function of these thumb-grips must not be used.

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss10.0.1-27-37-04-14 [AKF012014])

Lockable

Yes

Colour

Black

Suitable for emergency stop

No

With extension shaft

No


Suitable for power circuit breaker

Yes


Suitable for switch disconnecter

Yes

Dimensions



FN2-XPA



FN2-XPA

3 pole

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)



DWG files

- [DA-CD-pn2_xpa](#)
File
(Web)

Step files

- [DA-CS-pn2_xpa](#)
File
(Web)


Dimensions single product

- 
[123X536](#)
Line drawing
Paralleling mechanism
- 
[123X543](#)
Line drawing
Paralleling mechanism

Product photo

- 
[1230PIC-749](#)
Photo

3D drawing

- 
[1230DRV-419](#)
Line drawing
Paralleling mechanism

Instruction Leaflet

- [IL01219019Z](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

