

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMN2-PX100 - NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 100A, 3p, Screw terminal



192239 NZMN2-PX100

[Overview](#) [Specifications](#) [Resources](#)



192239 NZMN2-PX100

NZM2 PXR25 circuit breaker - integrated energy measurement class 1, 100A, 3p, Screw terminal
EL-Nummer (Norway) 4362735






The xEffect NZM...-PX circuit breaker range with power expert release (PXR) electronic triggering system covers use cases for full range protection with only four compact sizes and is suitable for the IEC market. The integrated energy measuring function supplies currents, voltages and active energy (kWh) with accuracy class 1 according to IEC 61557-12. Test function and settings via micro USB port directly on the switch. Modular function groups always make mounting flexible and may be supplemented by the comprehensive range of accessories. r.m.s. value measurement and thermal memory.



- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions


Delivery program

Product range
Circuit-breaker
Protective function
Systems, cable, selectivity and generator protection
Standard/Approval
IEC
Installation type
Fixed
Release system
Electronic release
Construction size
NZM2
Description
LSI overload protection and delayed and non-delayed short-circuit protective device
Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"
USB interface for configuration and test function with Power Xpert Protection Manager software
Interface module in equipment supplied.
Optionally communication-capable with internal Modbus RTU module or CAM
Number of poles

3 pole
 Standard equipment
 Screw connection
 Rated current = rated uninterrupted current [$I_n = I_u$]
 Rated current = rated uninterrupted current [$I_n = I_u$]
 100 A
Setting range
 Overload trip  [I_t]
 40 - 100 A
 Short-circuit releases  [I_{rm}] Non-delayed  [$I_t = I_n \times \dots$]
 2 - 18
 Short-circuit releases  [I_{rm}] Delayed  [$I_{sd} = I_t \times \dots$]
 2 - 10

Technical data

General
 Standards
 IEC/EN 60947
 Protection against direct contact
 Finger and back of hand proof to VDE 0106 Part 100
 Climatic proofing
 Damp heat, constant, to IEC 60068-2-78
 Damp heat, cyclic, to IEC 60068-2-30
 Ambient temperature Ambient temperature, storage
 - 40 - + 70 °C
 Ambient temperature Operation
 -25 - +70 °C
 Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27
 20 (half-sinusoidal shock 20 ms) g
 Safe isolation to EN 61140 Between auxiliary contacts and main contacts
 500 V AC
 Safe isolation to EN 61140 between the auxiliary contacts
 300 V AC
 Mounting position

Vertical and 90° in all directions	
	With XFI earth-fault release:
	- NZM1, N1, NZM2, N2: vertical and 90° in all directions
	with plug-in unit
	- NZM1, N1, NZM2, N2: vertical, 90° right/left
	with withdrawable unit:
	- NZM3, N3: vertical, 90° right/left - NZM4, N4: vertical
with remote operator:	
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions	

Direction of incoming supply
 as required
 Degree of protection Device
 In the operating controls area: IP20 (basic degree of protection)
 Degree of protection Enclosures
 With insulating surround: IP40
 With door coupling rotary handle: IP66
 Degree of protection Terminations
 Tunnel terminal: IP10
 Phase isolator and strip terminal: IP00
 Other technical data (sheet catalogue)

Weight

Temperature dependency, Derating

Effective power loss

Circuit-breakers

Rated current = rated uninterrupted current [$I_n = I_u$]
 100 A
 Rated surge voltage invariability [U_{imp}] Main contacts
 8000 V
 Rated surge voltage invariability [U_{imp}] Auxiliary contacts
 6000 V
 Rated operational voltage [U_e]

690 V AC
 Overvoltage category/pollution degree
 III/3
 Rated insulation voltage [U_i]
 690 V
 Use in unearthed supply systems
 690 V
 Switching capacity
 Rated short-circuit making capacity [I_{cm}]240 V [I_{cm}]
 187 kA
 Rated short-circuit making capacity [I_{cm}]400/415 V [I_{cm}]
 105 kA
 Rated short-circuit making capacity [I_{cm}]440 V 50/60 Hz [I_{cm}]
 74 kA
 Rated short-circuit making capacity [I_{cm}]525 V 50/60 Hz [I_{cm}]
 53 kA
 Rated short-circuit making capacity [I_{cm}]690 V 50/60 H [I_c]
 40 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]240 V 50/60 Hz [I_{cs}]
 85 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]400/415 V 50/60 Hz [I_{cs}]
 50 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]440 V 50/60 Hz [I_{cs}]
 35 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]525 V 50/60 Hz [I_{cs}]
 25 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]I_{cs} to IEC/EN 60947 test cycle O-t-CO-t-CO [I_{cs}]690 V 50/60 Hz [I_{cs}]
 5 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}]
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.
 Rated short-time withstand current I_t = 0.3 s [I_{tw}]
 1.9 kA
 Rated short-time withstand current I_t = 1 s [I_{tw}]
 1.9 kA
 Utilization category to IEC/EN 60947-2
 A
 Lifespan, mechanical(of which max. 50 % trip by shunt/undervoltage release) [Operations]
 20000
 Lifespan, electricalAC-1400 V 50/60 Hz [Operations]
 10000
 Lifespan, electricalAC-1415 V 50/60 Hz [Operations]
 10000
 Lifespan, electricalAC-1690 V 50/60 Hz [Operations]
 7500
 Lifespan, electricalMax. operating frequency
 120 Ops/h
 Total break time at short-circuit
 < 10 ms
Terminal capacity
 Standard equipment
 Screw connection
 Optional accessories
 Box terminal
 Tunnel terminal
 connection on rear
 Round copper conductorBox terminalSolid
 1 x (10 - 16)
 2 x (6 - 16) mm²
 Round copper conductorBox terminalStranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Round copper conductorTunnel terminalSolid
 1 x 16 mm²
 Round copper conductorTunnel terminalStranded1-hole
 1 x (25 - 185) mm²
 Round copper conductorBolt terminal and rear-side connectionDirect on the switchSolid
 1 x (10 - 16)
 2 x (6 - 16) mm²

Round copper conductor Bolt terminal and rear-side connection Direct on the switch Stranded
 1 x (25 - 185)
 2 x (25 - 70) mm²
 Al circular conductor Tunnel terminal Solid
 1 x 16 mm²
 Al circular conductor Tunnel terminal Stranded Stranded
 1 x (25 - 185) mm²
 Cu strip (number of segments x width x segment thickness) Box terminal [min.]
 2 x 9 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Box terminal [max.]
 10 x 16 x 0.8
 (2x) 8 x 15.5 x 0,8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [min.]
 2 x 16 x 0.8 mm
 Cu strip (number of segments x width x segment thickness) Bolt terminal and rear-side connection Flat copper strip,
 with holes [max.]
 10 x 24 x 0.8 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Screw connection
 M8
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [min.]
 16 x 5 mm
 Copper busbar (width x thickness) [mm] Bolt terminal and rear-side connection Direct on the switch [max.]
 24 x 8 mm
 Control cables
 1 x (0.75 - 2.5)
 2 x (0.75 - 1.5) mm²

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_r]

100 A

Equipment heat dissipation, current-dependent [P_{vid}]

8.25 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_n

100 A

Rated voltage

690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz

50 kA

Overload release current setting

40 - 100 A

Adjustment range short-term delayed short-circuit release

2 - 10 A

Adjustment range undelayed short-circuit release

2 - 18 A

Integrated earth fault protection

No

Type of electrical connection of main circuit

Screw connection

Device construction

Built-in device fixed built-in technique

Suitable for DIN rail (top hat rail) mounting

No

DIN rail (top hat rail) mounting optional

Yes

Number of auxiliary contacts as normally closed contact

0

Number of auxiliary contacts as normally open contact

0

Number of auxiliary contacts as change-over contact

0

With switched-off indicator

No

With under voltage release

No

Number of poles

3

Position of connection for main current circuit

Front side

Type of control element

Rocker lever

Complete device with protection unit

Yes

Motor drive integrated

No

Motor drive optional


Yes

Degree of protection (IP)

IP20


Characteristics

Characteristic curve




Let-through current

Characteristic curve




Let-through energy

Dimensions



- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm2_3p](#)
File
(Web)

Step files

- [DA-CS-nzm2_3p](#)
File
(Web)

Additional product information

- [Weight](#)
(Web)
- [Temperature dependency, Derating](#)
(Web)
- [Effective power loss](#)
(Web)
- [additional technical information for NZM power switch](#)
(PDF)

Product photo



[wa_ren_00318_c](#)


Photo



[wa_ren_00318_r](#)

Photo

Dimensions single product




[123X312](#)

Line drawing

Circuit-breaker, switch-disconnector, 3-pole

Blow out area, minimum clearance to adjacent parts

Minimum clearance to adjacent parts




[123X341](#)

Line drawing


Circuit-breakers, switch-disconnectors

Characteristic curve



[1230DIA-176](#)

Coordinate visualization



[1230DIA-184](#)

Coordinate visualization

Tender text

- [Tender text NZMN2-PX100 \(TT-NZMN2-PX100\)](#)
(Text)

Instruction Leaflet

- [IL012099ZU](#)
Asset
(PDF, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

[Generate data sheet in PDF format](#)

[Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

