

Eaton 189620

Catalog Number: 189620

NZMH4-PX1600-TAZ. NZM4 PXR25 circuit breaker - integrated energy measurement class 1, 1600A, 3p, Screw terminal, earth-fault protection, ARMS and zone selectivity

General specifications

Product Name	Catalog Number
Eaton Moeller series NZM molded case circuit breaker electronic	189620
	Model Code
	NZMH4-PX1600-TAZ
EAN	Product Length/Depth
4015081875672	375 mm
Product Height	Product Width
170 mm	210 mm
Product Weight	Compliances
19 kg	RoHS conform
Certifications	
IEC	
IEC/EN 60947	

Product specifications

Rated operational current for specified heat dissipation (In)
1600 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz

37 kA

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting Method

Fixed

Built-in device fixed built-in technique

Amperage Rating

1600 A

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (copper strip)

10 segments of 80 mm x 1 mm (2x) at rear-side width extension

Min. 5 segments of 25 mm x 1 mm at rear-side connection
(punched)

Min. 6 segments of 16 mm x 0.8 mm at flat conductor terminal

Min. 10 segments of 50 mm x 1 mm (2x) at rear-side connection
(punched)

10 segments of 50 mm x 1 mm (2x) at 1-hole module plate

Max. 10 segments of 32 mm x 1 mm (2x) at flat conductor
terminal

Handle type

Rocker lever

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Ambient storage temperature - min

40 °C

Earth-fault current setting (I_g) - max

1600 x I_n

Resources

Brochures

[eaton-digital-nzm-brochure-br013003en-en-us.pdf](#)

[eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf](#)

Catalogs

[eaton-digital-nzm-catalog-ca013003en-en-us.pdf](#)

Drawings

[eaton-circuit-breaker-nzm-mccb-dimensions-022.eps](#)

Installation instructions

[IL012101ZU](#)

Installation videos

[Introduction of the new digital circuit breaker NZM](#)

[The new digital NZM Range](#)

mCAD model

[DA-CD-nzm4_3p](#)

[DA-CS-nzm4_3p](#)

Technical data sheets

[eaton-nzm-technical-information-sheet](#)

Protection against direct contact

Finger and back-of-hand proof to VDE 0106 part 100

Terminal capacity (copper busbar)

Max. 50 mm x 10 mm (2x) at rear-side 1-hole module plate

50 mm x 10 mm (2x) at rear-side 2-hole module plate

M10 at rear-side screw connection

Min. 25 mm x 5 mm at rear-side 1-hole module plate

Min. 60 mm x 10 mm at rear-side width extension

Max. 80 mm x 10 mm (2x) at rear-side width extension

Min. 25 mm x 5 mm direct at switch rear-side connection

Max. 50 mm x 10 mm (2x) direct at switch rear-side connection

10.8 Connections for external conductors

Is the panel builder's responsibility.

Special features

LSIG overload protection and delayed and non-delayed short-circuit protective device, earth-fault protection Class 1 energy measurement, r.m.s. value measurement, and "thermal memory"

USB interface for configuration and test function with Power

Xpert Protection Manager software Zone selectivity ZSI

Maintenance Mode ARMS Interface module in equipment

supplied. Optionally communication-capable with internal

Modbus RTU module or CAM Maximum back-up fuse, if the

expected short-circuit currents at the installation location exceed

the switching capacity of the circuit breaker (Rated short-circuit

breaking capacity I_{cn}) Rated current = rated uninterrupted

current: 1600 A

Ambient operating temperature - max

70 °C

Position of connection for main current circuit

Front side

Rated insulation voltage (U_i)

1000 V AC

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Terminal capacity (copper stranded conductor/cable)

120 mm² - 185 mm² (1x) direct at switch rear-side connection

50 mm² - 185 mm² (4x) direct at switch rear-side connection

Features

Motor drive optional

Protection unit

Lifespan, electrical

3000 operations at 415 V AC-1

2000 operations at 690 V AC-1

3000 operations at 400 V AC-1

Electrical connection type of main circuit

Screw connection

Short-circuit total breaktime

< 25 ms (415 V); < 35 ms (> 415 V)

Rated impulse withstand voltage (U_{imp}) at main contacts

8000 V

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 400/415 V, 50/60 Hz

50 kA

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Utilization category

B (IEC/EN 60947-2)

Number of poles

Three-pole

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Terminal capacity (control cable)

0.75 mm² - 2.5 mm² (1x)

0.75 mm² - 1.5 mm² (2x)

Equipment heat dissipation, current-dependent

284 W

Instantaneous current setting (I_i) - min

3200 A

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 230 V, 50/60 Hz

63 kA

Application

525 V

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Rated short-circuit making capacity I_{cm} at 240 V, 50/60 Hz

275 kA

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 440 V, 50/60 Hz

50 kA

Short-circuit release delayed setting - max

10 A

Degree of protection (IP), front side

IP66 (with door coupling rotary handle)

IP40 (with insulating surround)

Rated short-circuit making capacity I_{cm} at 525 V, 50/60 Hz

143 kA

Rated short-circuit making capacity I_{cm} at 690 V, 50/60 Hz

100 kA

Instantaneous current setting (I_i) - max

38400 A

Overload current setting (I_r) - min

640 A

Short delay current setting (I_{sd}) - min

2 A

Number of auxiliary contacts (normally closed contacts)

0

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Lifespan, mechanical

10000 operations

Overload current setting (I_r) - max

1600 A

Voltage rating

690 V - 690 V

Terminal capacity (copper solid conductor/cable)

120 mm² - 300 mm² (1x) at rear-side 1-hole module plate

95 mm² - 300 mm² (2x) at rear-side 1-hole module plate

300 mm² (4x) at rear-side width extension

35 mm² - 185 mm² (4x) at rear-side 2-hole module plate

50 mm² - 240 mm² (4x) at 4-hole tunnel terminal

95 mm² - 185 mm² (2x) at rear-side 2-hole module plate

95 mm² - 240 mm² (6x) at rear-side width extension

Degree of protection (terminations)

IP10 (tunnel terminal)

IP00 (terminations, phase isolator and strip terminal)

Short-circuit release delayed setting - min

2 A

Terminal capacity (aluminum stranded conductor/cable)

50 mm² - 240 mm² (4x) at 4-hole tunnel terminal

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Short-circuit release non-delayed setting - min

2 A

Degree of protection

IP20

IP20 (basic degree of protection, in the operating controls area)

Overvoltage category

III

Rated short-time withstand current ($t = 1$ s)

19.2 kA

Short delay current setting (I_{sd}) - max

10 A

Rated impulse withstand voltage (U_{imp}) at auxiliary contacts

6000 V

Earth-fault current setting (I_g) - min

320 x I_n

Number of auxiliary contacts (change-over contacts)

0

Rated short-time withstand current ($t = 0.3$ s)

19.2 kA

Ambient storage temperature - max

70 °C

Release system

Electronic release

Rated short-circuit breaking capacity I_{cs} (IEC/EN 60947) at 525 V, 50/60 Hz

50 kA

Optional terminals

Connection on rear. Strip terminal. Tunnel terminal

Pollution degree

3

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Functions

ARMS maintenance mode

Earth-fault protection

Integrated earth fault protection

Systems, cable, selectivity and generator protection

Zone selectivity

Short-circuit release non-delayed setting - max

12 A

Rated short-circuit making capacity I_{cm} at 400/415 V, 50/60 Hz

187 kA

Standard terminals

Screw connection

Type

Circuit breaker

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Rated short-circuit making capacity I_{cm} at 440 V, 50/60 Hz

187 kA

Number of auxiliary contacts (normally open contacts)

0

Isolation

500 V AC (between auxiliary contacts and main contacts)

300 V AC (between the auxiliary contacts)

Number of operations per hour - max

60

Circuit breaker frame type

NZM4

Direction of incoming supply

As required

Shock resistance

15 g (half-sinusoidal shock 11 ms)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)